

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 3 R. W. W. M.

MOKE-GARPMAN CO., EUGENE, ORE., 21881

Edwin S. Woodford.
Witnesses: M. E. Godfrey
Cliff Potter
Renewed April, 1953, on Hall - Potter job.
C. S. File No. 42/68.

Section corner to sections 19, 20, 29 and 30. 22
Found 30 inch Fir, N.70°E., 62 lks. set by Hathorne in 1857 and still standing with portion of bark scribing still visible. (tree is not 50 inches) - Rescribed this tree.
12 inch Fir, S.74°E., 30 lks. gone but depression in ground still shows that a tree once stood there.
12 inch maple N.35°W., 16 lks. gone but depression in ground and maple sprouts growing around it.
No evidence of 12 inch Fir, S.52°W., 37 lks. - Ground shows evidence of old slide area.
Set iron pipe for corner and mark new trees:
28 inch Cedar, S.68°15'E., 42.2 feet.
28 inch Cedar, N.55°W., 51.1 feet.
40 inch Fir, S.27°45'W., 106.7 feet.

 $\frac{1}{4}$ corner to secs. 18 and 19. 23
10 inch Cedar, S.2°W., 18 lks. set by Hathorne found. Tree was down but scribe marks visible.
No trace of 48 inch Fir to the N. E. was found.
Set iron pipe for corner and mark 2 new trees:
12 inch Cedar, N.23°30'W., 10.3 feet.
10 inch Cedar, S.54°15'W., 17.3 feet.

Robert M. Thompson
July 1, 1956
C. S. File No. 42/178.

 $\frac{1}{4}$ sec. corner to secs. 28 and 29. 24
Found no trace of original corner.
I reset corner on true sec. line at mid-point between section corners.
Set a $\frac{3}{4}$ inch iron pipe,
from which I scribe two new trees:
12 inch Madrone, S.63°40'E., 1.6 feet.
15 inch W. Fir, N.69°50'W., 42.3. feet.

Section Corner to Sections 23, 24, 25, & 26. 25
Det. by Old BTs: 30" La. stump bears N.50°E. 29.7 ft. dist. O.B.T.
44" Fir Snag bears S.35°W. 15.2 ft. dist. O.B.T.
10" Laurel bears N.64°W. 21.1 ft. dist. found scribe (should be N.72°W. 28.4 ft)
At Corner point set $1\frac{1}{4}$ "X 24" Iron Pipe from which: 26
9" La. bears N.64°W. 49.7 ft. dist. marked S.23 T29S B.T.
6" Cedar bears N.48°W. 56.8 ft. dist marked S23 R3W B.T.
10" Laurel bears N.29W. 39.2 ft. dist. markd S23 T29S R3W W.M. B.T.
9" Fir bears N.22°W 22.9 ft. dist. marked S23 B.T.

John H. Markham, Jr.
For Stomar Lumber Co.
Witness: R. G. Boyd
Oct. 29, 1957
C. S. File No. 42/315

N. E. Corner of Section 24. Determined by Old BTs. 27
40" Fir Snag bears S.72 $\frac{1}{2}$ °W. 124.0 ft. distance O.B.T. Found Scribe.
40" Fir N.16°W. 170.0 ft. O.B.T. - West $\frac{1}{4}$ Corner Sec. 19, T29S R2W (brass cap) bears North 13.2 ft. dist.
At Corner point found stone and Set $1\frac{1}{4}$ "X 24" Iron Pipe from Which:
9" Fir bears N.42°W. 19.4 ft. dist. mkd. S13 B.T.
8" Fir bears S.67°W. 19.0 ft. dist. mkd. S24 B.T.
10" Fir bears S.31°W. 18.0 ft. dist. mkd. S24 B.T.
Creek bears North 14.0 ft. distance.

 $\frac{1}{4}$ Section Corner to Sections 23 & 24. Determined by Old BTs. 28
24" Cedar bears S.25°E. 10.0 ft. O.B.T.
13" Hemlock bears N.79°W. 11.0 ft. O. B. T.
At Corner point set $1\frac{1}{4}$ "X 30" truck axle with spline up from which 28
10" Hemlock bears N.53°E. 20.5 ft. dist. mkd. $\frac{1}{4}$ S24 B.T.
15" Fir bears N.31°W. 26.5 ft. dist. mkd. $\frac{1}{4}$ S23 B.T.
Creek bears South 25.0 ft. dist. Road bears South 85.0 ft. dist.

 $\frac{1}{4}$ Section Corner to Sections 24 & 25. Determined by Old BTs. 29
15" Fir Snag N.55°W. 10.5 ft. O.B.T.
36" Fir bears S.39°W. 23.7 ft. O.B.T.
At Corner Point set $1\frac{1}{4}$ "X 24" Iron Pipe from which:
9" Fir bears S.66°E. 26.0 ft. dist. mkd. $\frac{1}{4}$ S25 B.T.
9" Fir bears S.86°W. 37.0 ft. dist. mkd. $\frac{1}{4}$ S25 B.T.