

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Closing Corner to Sections 2 and 3, T30S R3W.

Found - All Orig. BT's. as recorded.

The S. E. BT. shows good scribing.

Also find marked Stone at Corner.

All BT's. in good condition.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960

C C	T29S
S 3/S 2	T30S

52

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
July 1960
C. S. File No. 49/47

Section Corner to Secs. 35 & 36, T29S R3W & Sec. 1 & 2, T30S R3W.

Found - Fir Tree, now 30", N.80°W. 27.7 ft., shows good scar, did not open.

Fir Tree, now 22", West 38.9 ft., shows good scar, old bark scribing "S2 T30S" visible, above scar, did not open.

Fir Tree, now 18", S.35½°E. 30.4 ft., shows good scar, did not open.

Dead Fir Snag, 36", N.66°E. 41.6 ft., shows good scar. Fragments of very old bark scribing visible above scar "S3" is all that is legible at present time, but traces of more fragmentary scribing also in evidence.

Set Brass Cap mkd: County Surveyor's Office, 1960

T29S R3W
S35 S36
S 2 S 1
T30S R3W

53

Blaze & Scribe: 14" Fir N.29°E. 9.7 ft. mkd. "T29S R3W S36 CS BT."

No trace found of orig. Chinquapin to S. E.

Corner lies on steep N. slope approximately ½ way from top of spur to draw. August 18, 1960

¼ Corner to Sections 26 and 35.

Proportionate Measurement.

Set 1½" Iron Pipe 36" Long 18" in ground.

Scribed two Bearing Trees:

12" Laurel N.45°E. 5.0 ft. scribed ¼ S26

10" Fir S.37°W. 25.0 ft. scribed ¼ S35

54

Donald R. Martin
For A. Kindred
Oct. 1960
C.S. 51/143

Section Corner common to Sections 3 and 4.

This corner is not common to Secs. 33 & 34, T28S R3W.

I locate the true corner point from a 13" Fir BT, blazed & scribed as per the 1910 notes; this corner is 9.8 ft. North and 15.0 ft. West of corner set previously. - Rev. = 2

I set a 1" Iron Pipe and Witness the corner as follows:

13" Fir DBH bears S.41°E. 34.6 ft. Mkd. in 1910 scribe marks clearly visible.

14" Laurel DBH bears N.3°30'W. 11.6 ft. Mkd. T28S R3W S33 B.T.

The trees marked for the previous corner lay as follows:

20" Cedar bears S.49°E. 38.7 ft. Mkd: T29S R3W S 3 BT.

20" Fir bears S.28°W. 21.0 ft. Mkd: S 4 B.T.

55

Warren D. Hootman
For Mr. J. P. Heath
September 21, 1960
Filed January 13, 1961
C.S. File No. 51/164
Map File M 20 - 5

North ¼ Corner of Section 4.

Find a Maple 12" DBH which bears S.80°E. 19.5 ft. faced by no scribe marks left. #129 56

The true corner point falls under a large log.

I set a 2" x 2" x 3" stake on top of the log & witness as follows:

20" D. Fir DBH bears N.67°30'E. 46.7 ft. Mkd: B.T. S33.

Remark Orig: 12" Maple DBH bears S.80°E. 3.96 ft. Mkd: B.T. ¼ S4 399.

FOR FURTHER INFO. SEE C.S. 59/38 7/28/27 - G. SURVEYOR NOTES.

Section Corner to Section 5 and 4.

Find two firs of approx. size which match for bearing & distance which I believe to be the orig. BT's.

I set a ¾" Iron Pipe from the 2 BT's at the distance & bearing called for by the government notes and witness the corner 5 & 4 as follows: #128

Madrone 4" DBH bears West 5.2 ft.

Madrone 16" DBH bears S.45°E. 13.5 ft.

57

RE-RECORDED SEE CORNER NO. #129 56
RE-RECORDED SEE CORNER NO. #128