

Douglas County Surveyor's Record of
Government Corners Renewed

29 T.S. 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Warren D. Hootman
Surveyed for Mr. J.P. Heath
September 21, 1960
Filed Jan. 1961
C. S. File No. 51/164
Map M 20 - 5

Section Corner common to Sects. 4, 3, 10 and 9. ^{#20 #91}
This corner was re-established by Kerr, 1950; ^{REN} ~~point~~ being
witnessed by a Fir and a Cedar as described in Kerr's notes

57A

Section Corner to Sections 4, 5, 8 and 9. 58
The corner is gone but three of the Orig. BT's. are there and
check for bearing and distance with the notes. One Madrone is
unmarked, the Cedar is a stump cut below the possible marking.
The other Madrone is faced but without a discernable scribe.
I drive a 2" pipe for the corner point and rewitness the corner as follows:
(Orig.) Madrone 10", bears S.66°W. 12.2 ft.
(New) Madrone 16", DBH bears S.45°E. 9.0 ft.
(New) Madrone 10" DBH bears N.66°E. 50.0 ft.
(New) Fir 20" DBH bears N.35°W. 12.4 ft.

James W. Byron, Deputy Co. Surveyor
Milo Godfrey
Clete Putnam
April 11, 1961
C. S. File No. 49/47

$\frac{1}{4}$ Section Corner to Sections 22 and 27. 59
Found - Orig. 14", new 18" Fir, down, N.40°E. 2.0 ft., shows good
bark scribing " $\frac{1}{4}$ "S".
S. E. Laurel BT., new down. This BT. recorded by Markham. ^{REN #7}
Also find 1" Iron Pipe at Corner.
Set Brass Cap alongside 1" I. Pipe & MKd: County Surveyor's $\frac{1}{4}$ S22 T29-3W
Office, 1961 S27
New BT's: 20" Cedar bears S.68°E. 46.0 ft. scribed $\frac{1}{4}$ S27 CS BT.
9" R.Fir bears N.45 $\frac{1}{2}$ °E. 13.4 ft. scribed $\frac{1}{4}$ S22 CS BT.

Section Corner to Section 22 - 23 - 26 - 27. 60
Found - All BT's. & Iron Pipe as recorded by Markham. S.E. BT. new down.
New BT's: 12" Cedar bears S.64°E. 102.8 ft. scribed S26 T29S R3W CS BT.
5" W.Fir bears N.28°E. 25.6 ft. scribed S23 CS BT.
RE-RENEWED, SEE CORNER NO. #122

Section Corner to Sections 15 - 16 - 21 - 22. 61
Found - Orig. 10", now 30" Cedar N.80°E. 46.2 ft., previously opened,
shows good reverse scribing.
Stump of Orig. S.W. BT.
The S.E. BT. is now a snag, shows old axe blaze.
The Orig. N.W. BT. shows good scar.
Set - Brass Cap at Corner Mkd:

S16	S15
S21	S22

 T29S R3W County Surveyor's
Office, 1961
New BT's: 18" W.Fir bears N.51°W. 9.0 ft. scribed S16 T29S R3W CS BT.
12" W.Fir bears N.82°E. 21.6 ft. scribed S15 T29S R3W CS BT.
17" R.Fir bears S.62°W. 29.7 ft. scribed S21 T29S R3W CS BT.
19" Pine bears S.46°E. 55.7 ft. scribed S22 T29S R3W CS BT.

$\frac{1}{4}$ Corner to Sections 15 and 16. 62
Found - Orig. 12" R. Fir, now 24" S.75°W. 34.3 ft., shows good scar
near base, I rescribe this BT. $\frac{1}{4}$ S16 CS BT.
Orig. 30", now 40" R.Fir N.45°E: 9.9 ft., shows bark
scribing & good scar below.
Set - Brass Cap Mkd: County Surveyor's Office, 1961 $\frac{1}{4}$ S16/S15 T29S R3W.
*FIND OK 6/92
J. RUPPERT M115-48*

James W. Byron, Deputy
Dale McFarland
J. Powell
August 15, 1961
C.S. File No. 49/47

Section Corner to Sections 27 - 26 - 34 - 35. 63
Found - Orig. 20", now 30" Cedar, previously opened, shows good scribing
"29", now down. Orig. 15", now 24" Fir N.42°E. 21.8 ft., now
down, shows scribing. Orig. 10", now 16" Fir Snag S.81°E.,
not S.89°E. 19.8 ft., shows good scars. Orig. 10", now 18" Fir
Snag N.50°W. 19.1 ft., shows scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's

S27	S26
S34	S35

 T29S R3W
Office, 1961
New BT's: 13" Cedar bears N. 9 $\frac{1}{2}$ °E. 22.0 ft. scribed S26 T29S R3W CS BT.
10" R.Fir bears N.27°W. 43.7 ft. scribed S27 T29S R3W CS BT.
9" Cedar bears S.43°E. 14.6 ft. scribed S35 T29S R3W CS BT.
6" Cedar bears S. 1°W. 32.7 ft. scribed S34 CS BT.