

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C.S. File No. 49/47

James W. Byron, Deputy County Surveyor  
John Powell and Mike Stone  
July 10 - 20, 1962  
C. S. File No. 52/126

October 1962

64  
1/4 Section Corner to Sections 27 and 26.  
Found - Orig. 48", now 50" R. Fir Snag N.42°E. 9.9 ft., shows good bark scribing "BT". Orig. N.W. BT. not found.  
Note - Corner falls on Right Bank of small stream. I set Wit. Corner 30' North of True Corner.  
Mkd:- Brass Cap W.C. 30' South to 1/4 S27/S26 T29S R3W County Surveyor's Office, 1961  
New BT's: 9" R. Fir bears N.37°W. 13.5 ft. scribed W.C. 1/4 S27 CS BT.  
8" R. Fir bears N.61°E. 30.4 ft. scribed W.C. 1/4 S26 CS BT.

65  
Renew Corner to Sections 31 and 32 only, T28S-R3W.  
Found - Both Orig. BT's. - Orig. 10", now 18" Fir N.32°W. 50.8 ft., not 52.8 ft. (May have been measured as slope dist.) #126  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 S31 / S32 T28S R3W T29S  
Note - Corner is at base of 48" Cedar Snag.

66  
North 1/4 Corner Section 5.  
Found - Orig. 8", now 20" Fir S.10°W. 5.9 ft. previously opened, shows good scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 N 1/4 S5 T29S R3W  
New BT: 8" R. Fir bears S.88°W. 16.3 ft. scribed N 1/4 S5 CS BT.  
(Dist. to BT. measured to base - Tree leans to West)

67  
Corner to Sections 3 and 2 only. T28S R3W  
S 3 / S 2 T29S R3W  
Found - 3 Orig. BT's. Orig. 48", now 52" Cedar shows good scribing, N.50°E. 46.2 ft. Orig. 15", now 28" Cedar S.62°W. 23.1 ft., shows good scribing. Orig. 20", now 40" Fir N.54°W. 39.6 ft., not N.62°W., shows good bark scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 T28S R3W S 3 / S 2 T29S  
New BT's: 11" R. Fir bears S.29°E. 24.3 ft. scribed S2 T29SR3W CS BT. Rescribed, now 28" Cedar S.56°W. 23.1 ft. S 2 T29S R3W CS BT.  
Note - Corner is on West Slope about 200 ft. West from top of ridge.

68  
Closing Corner Sections 33 and 34, T28-3W.  
Found - Both Orig. BT's. & Stone at Corner. Orig. N.E. BT., shows good scribe marks. Orig. N.W. BT., shows scars.  
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1962 C C S33/S34 T28S R3W T29S  
New BT: 24" Cedar bears N.62°W. 27.5 ft. scribed C C S33 T28S R3W CS BT.

69  
1/4 Corner to Sections 10 and 15.  
Found - Both Orig. BT's. Orig. 18", now 26" Fir S.87°E. 17.2 ft., shows bark scribing "1/4 S".  
Orig. 15", now 22" R. Fir N.28°E. 54.8 ft., shows bark scribng, "1/4 S" - Note - Scribing seems to have been made with a knife & not old enough for Orig. trees. Do check record & shows old axe work.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 1/4 S10 T29S R3W S15  
New BT: 8" R. Fir bears N.17°W. 35.1 ft. scribed 1/4 S10 CS BT.  
27" Cedar bears S.29°E. 25.5 ft. scribed 1/4 S15 CS BT.

70  
Section Corner to Sections 9 - 10 - 15 - 16.  
Found - All Orig. BT's. except N.E. BT., now stump hole. All check record. N.W. BT. shows scribing old face "BT". S.W. BT., now snag. S 9 | S10  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 S16 | S15 T29S R3W  
Note - Orig. BT's. show knife scribing same as 1/4 Cor. 10 & 15, above.  
New BT's: Rescribe Orig., now 19" Fir N.85°W. 31.0 ft. S9 T29S R3W CS BT.  
15" Cedar bears S.22°E. 24.8 ft. scribed S15 T29S R3W CS BT.  
6" Myrtle S.46°W. 12.4 ft. S16 CS BT.  
6" Pine N.34°E. 35.0 ft. S10 CS BT.