

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy County Surveyor  
John Powell and Wm. Stoffel  
October 1962  
C. S. File No. 52/126

Section Corner to Sections 3 - 4 - 9 - 10.

71

Found - No Orig. BT's. We do find Keer's 20" Fir N.6°W. 30.0 ft., shows good scribing. Also find Stake at Corner. - *REN # 2A # 57A*

Set - Brass Cap alongside Stake & Mkd: County Surveyor's Office, 1962 

S 4	S 3
S 9	S 10

 T29S R3W

Note - Call to creek East of corner checks about 20 ft. short of record.

New BT's: 7" R.Fir S.19°W. 9.0 ft. scribed S9 CS BT.

7" R.Fir S.10°E. 13.9 ft. scribed S10 CS BT.

1/4 Corner to Sections 20 and 21.

72

Found - Both BT's. as recorded by Evans, 1952, East BT. is bark scribed. Do not find I.P. at corner. Cor. is near top of cut bank for log. road.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 1/4 S20/S21 T29S R3W

New BT: 16" R.Fir bears N.83°E. 21.5 ft. scribed 1/4 S21 CS BT.

1/4 Corner to Sections 29 and 28.

73

Found - Pipe & Both BT's. as recorded by Thompson, Laurel to S.E., now down, & Pipe out of ground. - *REN # 24 # 133*

Reset - 2" I.P. at corner & scribe New BT:

9" Cedar bears N.67°E. 16.0 ft. scribed 1/4 S28 CS BT.

Section Corner to Sections 28 - 29 - 32 - 33.

74

Found - 4" x 4" squared & scribed Post at corner & all BT's. as recorded by B.E.I., 1941. Cedar to S.W., now stump, (scribed) Fir to S.E., down. Fir to N.W., down. Cedar to N.E., dead. - *REN # 14*

Set - Brass cap alongside Cor. Post Mkd: County Surveyor's Office, 1962 

T29S3W	S29	S28
	S32	S33

New BT's: 23" Cedar bears S.26°E. 27.2 ft. scribed S33 T29S R3W CS BT.

8" Fir bears N.81°W. 42.1 ft. scribed S29 CS BT.

16" R.Fir bears N.42°E. 67.7 ft. scribed S28 T29S R3W CS BT.

No trees near to S.W.

1/4 Corner to Sections 1 and 12.

75

Found - Both Bearing Trees & Corner Stake set by Kerr, 1950. (B.T's. are bark scribed) - *REN # 20*

Set - Brass Cap alongside Corner Stake & Mkd: County Surveyor's Office, 1962 

1/4 S 1	T29S R3W
S 12	

Rescribe Kerr's BT's: 25" R.Fir N.52°E. 7.0 ft. Wood Scribe 1/4 S1 CS BT.

28" R.Fir S.52°W. 22.0 ft. Wood Scribe 1/4 S12 CS BT.

Section Corner to Sections 1 - 2 - 11 - 12.

76

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1962 

T29S R3W	S 2	S 1
	S 11	S 12

Found - Orig. 10", now 37" Fir Stump N.50°W. 28.4 ft. We open & find good scribing "2".

Orig., now 48" Fir N.80°E. 30.4 ft., no scribing found.

New BT's: 20" Fir bears N.12°W. 16.7 ft. scribed S2 T29S R3W CS BT.

Rescribe(bark)44" Fir N.83°E. 28.4 ft. Mkd: S1 T29S R3W CS BT.

14" R.Fir bears S.35°E. 19.3 ft. scribed S12 T29S R3W CS BT.

12" R.Fir bears S.87°W. 30.0 ft. scribed S11 T29S R3W CS BT.

Section Corner to Secs. 31 & 32, T29-3W. & Secs. 5 & 6, T30-3W.

77

Found - Both BT's. as recorded by Eppstein, 1927. Each shows good scars. Also find 1/2" Iron Rod at Corner. - *REN # 9 T 30-3*

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 

S31	S32	T29S
S 6	S 5	T30S R3W

New BT's: 10" Cedar bears N.60°E. 21.0 ft. scribed T29S R3W S32 CS BT.

15" R.Fir bears N.42°W. 55.0 ft. scribed T29S R3W S31 CS BT.

FOOK  
10-92  
By LAWG  
M117-2

FOOK 10-93  
M. HULL M118-4