

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29. S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

⁷⁸
 $\frac{1}{4}$ Corner to Sections 31 and 32. ^{FOOK 10-20 BY LONG MINTZ}
 Found - Orig. 30", now 20" Cedar S. 35°E. 8.6 ft., shows good scribing " $\frac{1}{4}$ ". Orig. S.W. BT. not found.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S31/S32 T29S R3W
 New BT: 10" R.Fir bears N. 66 $\frac{1}{2}$ °W. 27.6 ft. scribed $\frac{1}{4}$ S31 CS BT.

⁷⁹
 Sec. Cor. Secs. 36 & 31, T29-3W. and Secs. 1 & 6, T30-3 & 4W.
 Found - 4" x 4" x 6' scribed Cedar Post at Cor. ^(See Rev. #42, T30-4W)
 14" B.Oak S. 84°W. 40.3 ft., shows rotted face.
 12", now 16" R.Fir N. 53°E. 19.7 ft., shows good scar.
 Other BT's. not found.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

$\frac{1}{4}$ S36 | S31 T29S
 S 1 | S 6 T30S
 R4W R3W
 New BT's: 10" R.Fir bears N. 71°W. 38.0 ft. scribed S36 T29S R4W CS BT.
 7" Cedar bears S. 55°W. 31.9 ft. scribed S1 CS BT.
 No trees near to S. E.

Fence Corner Thus:



⁸⁰
 S. E. Corner to D. L. C. No. 37.
 Found - 6", now 24" Cedar N. 57°W. 35.0 ft. We open & find good scribe marks. S.W. BT. not found. ^{- REN #19A}
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 S.E. DLC 37 T29S R3W
 Note - $\frac{3}{4}$ " I.R. at South R/W Line of Co. Road Sta. 567 + 59.96 P.T. bears N. 25°W. 56.8 ft. from D.D.C. Cor. Also top of West bank of Myrtle Creek is 20 ft. East of Corner.
 New BT: 23" R.Fir bears S. 36 $\frac{1}{2}$ °W. 225.8 ft. scribed S E DLC 37 CS BT.
 This BT. is at top of North Bank of Myrtle Creek.

⁸¹
 $\frac{1}{4}$ Corner to Sections 11 and 14.
 Found - Brass Cap at Cor. & Both BT's. as recorded. ^{- Rev #32}
 Cedar to S. E., now dead.
 New BT: 8" W. S. 72°W. 15.5 ft. scribed $\frac{1}{4}$ S14 CS BT.

⁸²
 Corner to Sections 11 and 14 only.
 Found - $\frac{3}{4}$ " I. R. at Cor. & all BT's. as recorded. S.E. BT. is ^{REN #34}
 in good condition. N.W. BT. is now stump, shows scribing. N.E. BT., now down.
 New BT: 14" Fir N. 1°W. 14.0 ft. scribed S15 T29S R3W CSBT.

⁸³
 $\frac{1}{4}$ Corner to Sections 14 and 15.
 Found - Both Orig. BT's. & Corner Tree. We open N.E. BT. & find good scribing. Also find good bark scribing on West Side of Corner Tree, " $\frac{1}{4}$ S". S.W. BT. now snag.
 Set - Brass Cap 3.0 ft. North of center of corner tree, now 40" Fir Mkd: County Surveyor's Office, 1962
 W. C. 3.0 ft. South to $\frac{1}{4}$ S15/S14 T29S R3W.
 New BT's: 17" Cedar bears N. 71°W. 29.3 ft. scribed W.C. $\frac{1}{4}$ S15 CS BT.
 10" Cedar bears S. 46°E. 12.6 ft. scribed W.C. $\frac{1}{4}$ S14 CS BT.

⁸⁴
 Section Corner to Sections 17 - 18 - 19 - 20.
 Found - All BT's. as recorded by B.B.I., except Sugar Pine N. 17°W., not N. 27°W. 40.3 ft. shows good scar. S.E. BT., down. ^{REN #18}
 S.W. & N.E. BT's. O.K., show good bark scribing.
 Also find 6"x6" scribed stake on ground at cor. & 1 $\frac{1}{2}$ " I.P.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

$\frac{1}{4}$ S18 | S17 T29SR3W
 S19 | S20
 Note - B.B.I.'s. BT's. check for dist. O.K., as measured to faces.
 New BT's: 24" Cedar bears N. 26°W. 12.5 ft. scribed S18 T29S R3W CS BT.
 10" R.Fir bears S. 2°E. 57.4 ft. scribed S20 T29S R3W CS BT.

James W. Byron, Deputy County Surveyor
 John Powell and Bill Stoffel
 October 1962
 C. S. File No. 52/126