

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29-S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21821

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
October and November 1962
C. S. File No. 52/126

$\frac{1}{4}$ Corner to Sections 18 and 17. 85
Found - Both BT's. & 1" I.P. at Corner as recorded by Markham. *-Ren. #8*
Also find both Orig. BT's. with scribing as recorded
except, now 30" Laurel O.B.T., should be N.71°W. 15.0 ft.,
not N.60°W. 9.6 ft. This tree may have slid downhill.
Note - Markham's S.42°E. BT. dist. is 19.5 ft.
New BT: 7" Cedar bears S.11°W. 18.6 ft. scribed $\frac{1}{4}$ S18 CS BT.

Section Corner to Sections 7 - 8 - 17 - 18. 86
Found - Orig. BT. 18" Laurel N.12°E. 27 lks., scribing on tree,
Tree now 27", 18.4 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's

S 7	S 8
S18	S17 R3W

 T29S
Office, 1962
New BT's: 8" Hemlock S.25°E. 12.8 ft. scribed T29S R3W S17 CS BT. *pd. 7/90*
13" D.Fir N.27°W. 38.4 ft. scribed T29S R3W S7 CS BT. *M110-40*
12" Cedar S.87°W. 67.8 ft. scribed T29S R3W S18 CS BT.

$\frac{1}{4}$ Corner to Sections 12 and 13. 87
Found - Orig. BT. N.35°E. 10.6 ft., showing good reverse scribing.
Stake at Cor. & both BT's. as recorded by Kerr, except 12", now
13" Fir should be N.50°W. 11.9 ft. not N.50°E. 11.9 ft. *-Ren. #21*
Orig. N.E. BT. has been rescribed in bark " $\frac{1}{4}$ S BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's

$\frac{1}{4}$ S12
S13

 T29S R3W
Office, 1962
No New Bearing Trees scribed.
Note - Corner is on West slope & 150 ft. West of top of ridge.

$\frac{1}{4}$ Corner to Sections 23 and 24. 88
Found - Axle at Cor. & N.W. BT., now down. N.E. BT. dead. *-Sec Ren. #28*
New BT's: 12" Fir bears S.50°E. 87.0 ft. scribed $\frac{1}{4}$ S24 CS BT.
10" Hemlock bears S.1°W. 37.4 ft. scribed $\frac{1}{4}$ S23 CS BT.

$\frac{1}{4}$ Corner to Sections 22 and 23. 89
Found - 1" I.Pipe at corner. S.W. BT. as recorded by Markham is O.K.
S. E. Bearing Tree now dead. *-Ren. #6*
New BT: 15" Pine bears N.43°E. 59.4 ft. scribed $\frac{1}{4}$ S23 CSBT.
Note - Corner is 30 ft. South of top E. W. Ridge.

$\frac{1}{4}$ Corner to Sections 11 and 12. 90
Found - Both Orig. BT's. Orig. 5", now 7" Cedar shows good scribing, " $\frac{1}{4}$ S",
S.63°W. 6.6 ft. Orig. 20", now 20" Laurel snag, shows good scars,
N.75°E. 14.5 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S11/S12 T29S R3W
New BT's: 7" Fir bears S.71°W. 12.8 ft. scribed $\frac{1}{4}$ S11 CS BT.
12" Fir bears N.58°E. 10.1 ft. scribed $\frac{1}{4}$ S12 CS BT.

$\frac{1}{4}$ Corner to Sections 2 and 1. 91
Found - Both Orig. BT's: Orig. 10", now 16" R.Fir N.25°W. 11.9 ft, shows
good scribing, now down.
Orig. 8", now 10" Dead Fir N.40°E. 5.9 ft., shows good scribe marks.
These two trees are very old. Also call to creek checks O.K.
Stake set for $\frac{1}{4}$ Cor. bears East 99.0 ft. from which:
36" R.Fir bears N.12°W. 13.0 ft., bark scribed, and shell of
Fir Snag bears N.40°E. 5.5 ft., shows bark scribing. This corner
was probably set not later than 1937. Corner is 20 ft. North of
creek, should be 100 ft. South.
Set - Brass Cap at True Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S2/S1 T29S R3W
New BT's: 12" R.Fir bears N.17°E. 50.2 ft. scribed $\frac{1}{4}$ S1 CS BT.
11" Cedar bears S.36°W. 19.5 ft. scribed $\frac{1}{4}$ S2 CS BT.