

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 3. W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97881

West $\frac{1}{4}$ Corner to Section 6 only, T29-3W. 92
as determined by Old Bearing Trees:
20" Fir S.40°E. 17.2 ft. O.B.T., found scribe.
31" Fir S.45°W. 17.2 ft. O.B.T., found scribe.
At Cor. Point set $1\frac{1}{2}$ " x 30" Truck Axle from which:
20" Fir bears N.56°W. 34.6 ft. mkd: $\frac{1}{4}$ S6 BT.
40" Fir bears S.65°E. 30.6 ft. dist., bark scribed $\frac{1}{4}$ S6BT29SR3W.
Rock road bears West 80.0 feet.

Hohn H. Markham,
Jr.

Oct. 17, 1962
C. S. File
No. 42/315

Corner to Sections 6 and 7, only. 93
Found - Orig. 10", now 30" R. Fir N.40°E. 30.0 ft., not 23.1 ft,
previously opened, shows good scribing.
Orig. 40", now 44" Cedar Snag(shell only) S.40°W. 5.9 ft. no scribng.
Set - Brass Cap at Cor. Mkd: County Surveyor's

S 6	T29S
S 7	R3W

Office, 1962 R4W
New BT: 6" Hemlock bears S.20°E. 6.6 ft. scribed S7 CS BT.

Corner to Sections 25 and 36 only. T29-4W 94
Found - Stump of S.W. BT. as recorded by A.R. Evans., shows good
bark scribing "BT".
No trace of N.W. BT, nor Brass Cap set by Evans. -M1-31
This area has been disturbed by logging roads.
Set - Brass Cap at Cor. Mkd: County Surveyor's

S25	T29S
S36	R3W

Office, 1962 R4W
New BT's: 14" Cedar bears S.21°W. 123.0 ft. scribed S36 T29S R4W CS BT.
18" Cedar bears N.84°W. 88.2 ft. scribed S25 T29S R4W CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
November and December 1962
C. S. File No. 52/126

Corner to Sections 24 and 25 only, T29-4W. 95
Found - Brass. Cap at Cor. & Both BT's. as recorded by A.R. Evans,
except N.W. BT., now down. See M1-31
New BT: 7" R. Fir N.14°00'W. 23.4 ft. scribed S24 CS BT.

FD OK 10-93 M. HULL M118-A
 $\frac{1}{4}$ Corner to Sec. 32, T29-3W & Sec. 5, T30-3W. 96
Found - $\frac{3}{4}$ " I. Bolt at Cor. & Both BT's. as recorded, each shows
Sec Ren #16 good bark scribing.
New BT: 10" Cedar bears N.19°E. 18.4 ft. scribed $\frac{1}{4}$ S32 CS BT.

$\frac{1}{4}$ Corner to Sections 30 and 29. 97
Found - No scribing, but we do find, now 24" Laurel, that checks
dist. & bear. for N. W. BT. & it is now down, & mostly
rotted. It does show real old axe marks.
Now 36" Laurel that checks for S.E. BT. The N.W. face is
gone & just a shell of the rest of the tree left.
Find old axe blazes to North and to West.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S30/S29 T29S R3W.
New BT's: 7" Cedar bears S.62°W. 29.6 ft. scribed $\frac{1}{4}$ S30 CS BT.
14" R. Fir bears S.81°E. 18.4 ft. scribed $\frac{1}{4}$ S29 CS BT.

Section Corner to Sections 14 - 15 - 22 - 23. 98
Found - 1" I. P. at corner & all BT's. as recorded, except S.W. BT.,
Ren # 5 top is broken.
New BT's: 6" W. Fir bears S.82°W. 57.9 ft. scribed S22 CS BT.
6" W. Fir bears S.52°E. 32.4 ft. scribed S23 CS BT.

Section Corner to Sections 29-30-31-32. 99
Found - Orig. 10", now 12" rotted stump, shows scribing; S.65°W. 25.1 ft.
Stump Hole of N.E. BT. & Orig. 10", now 20" Fir N.10°W. 22.3 ft.,
not 19.8 ft., shows good scars. Orig. S.E. BT. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's

S30	S29
S31	S32

 T29S R3W
Office, 1962
New BT's: 58" R. Fir bears S.30°W. 34.2 ft. scribed S31 T29S R3W CS BT.
12" Cedar bears S.12°E. 35.9 ft. scribed S32 T29S R3W CS BT.
Rescribe Orig., now 20" R. Fir N.10°W. 22.3 ft. S30 T29S R3W CS BT.
12" W. Fir bears N.44°E. 3.4 ft. scribed T29S R3W S29 CS BT.