

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97331

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffell
December 1962 & January 1963
C. S. File No. 52/126

S. E. Corner Section 36 only. 100
Found - Both Original BT's. & Cor. Tree, all as recorded.
Orig. 15", now 20" Fir N.45°W. 2.6 ft., shows good scar, face
may be rotted. I rescribe this BT. S36 T29S R3W CS BT.

South $\frac{1}{4}$ Corner to Section 34 only. 101
Found - Both BT's. & Corner Tree as recorded. Cor. Tree & N.W. BT.
are good log trees and could now be cut.
Set - Brass Cap 4.0 ft. North of center of corner tree & Mkd.
County Surveyor's Office, 1962 Wit. Cor. 4' South to S $\frac{1}{4}$ S34
T 29 S R 3 W
New BT's: 14" R.Fir bears N.31°W. 54.5 ft. scribed W.C. $\frac{1}{4}$ S34 CS BT.
Orig., now 26" Cedar bears S.30°E. 39.3 ft., shows good scar.

East $\frac{1}{4}$ Corner to Section 25, only. 102
Found - Brass Cap at Cor. & Both BT's. N.W. BT. shows good scar.
S. W. BT., now down, shows scribing on stump section.
New BT's: 6" R.Fir bears N.68°W. 18.0 ft. scribed $\frac{1}{4}$ S25 CS BT.
8" Chinquapin bears S.38°W. 4.4 ft. scribed $\frac{1}{4}$ S25 CS BT.

Corner to Sections 30 and 31 only, T29-2W. 103
Found - Brass Cap at Corner & both BT's., show scars.
New BT's: 13" Laurel bears N. 47° E. 29.9 ft. scribed S30 T29S R2W CS BT.
12" R.Fir bears S.46°E. 34.0 ft. scribed S31 T29S R2W CS BT.

West $\frac{1}{4}$ Corner to Section 30 only, T29-2W. 104
Stone at Corner & Both BT's. as recorded. S.E. BT., now snag, shows scribing.
Set - Brass Cap at Corner Stone & Mkd: $\frac{1}{4}$ S30 T29S R2W
R3W West
New BT: 22" R.Fir bears S.36°E. 24.5 ft. scribed $\frac{1}{4}$ S30 CS BT.

Corner to Sections 24 and 25 only, T29-3W. 105
Found - Stone at Corner & Both BT's. as recorded.
Set - Brass Cap alongside Corner Stone & Mkd: County Surveyor's S24 T29S
Office, 1962 R3W S25 R2W
Note - The 2 corners listed above are both on steep South Slope.

Renew Corner to Sections 25 and 36 only, T29-3W. 106
Found - Both Bearing Trees. Orig. 16", now 30" Fir S.65°W. 26.0 ft.,
not 29.7 ft., shows good scar & bark scribing.
N.W. Bearing Trees shows good scar.
Corner Stone not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's S25 T29S
Office, 1963 R3W S36 R2W
No New Bearing Trees Scribed.

Renew Corner Set 20 chains East of Section Corner $\frac{S32}{S5} \frac{S33}{S4}$ T29S R3W T30S 107
Found - Orig. 36", now 40" Dead Fir N.25°E. 4.6 ft., shows old bark
scribing above newer bark scribe, also shows good scar near base
which is typical of Hathorne's work. - Ren #13A ??
Also find 1" I.P. at Cor. Orig. SW. BT. not found.
Note - Orig. Surveyor, 1857 set this corner, see gov't. notes.
New BT's: 18" R.Fir bears S.16°E. 27.2 ft. scribed S4 T30S R3W CS BT.
8" R.Fir bears East 38.4 ft. scribed S33 T29S R3W CS BT.

THIS CORNER NOW BECOMES AN ANGLE POINT PER: CADASTRAL SURVEY - VOL. 34 Pg. 14634