

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 3 W. R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97101

108

1/4 Corner to Sections 21 and 28.  
Found - 50" D. Fir, now snag, S. 77° E. 23.1 ft., faint bark  
scribe "1/4 S". Opened BT scar for old burnt face. No  
legible scribing.  
18" Pine N. 58° E. 75.9 ft., now hole in ground, good  
bearing & distance. Pine down the hill about 50.0 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office  
1966 T 29 S R 3 W  
S 21  
S 28  
New BT's: 9" Laurel N. 39° E. 7.0 ft. mkd. 1/4 S21 CS BT.  
6" Cedar S. 8° W. 9.8 ft. mkd. 1/4 S28 CS BT.  
Note - This corner lies east of creek 325 ft. Yellow tag on W. Fir  
at end of cat. trail, 137 ft. east of corner.

John M.  
Powell &  
Crew  
6/30/66  
C.S. File  
No. 52/126

June 30, 1966

109

Wit. Cor. to C.C. of Sections 35 & 36 only, T28-3W.  
Found - 12", now 14" R.Fir, N. 33° W., 21.6 ft., alive, blazes healed.  
7", now 10" R.Fir, N. 2° E. 38.2 ft., alive, blazes healed.  
Orig. Laurel N. 26° W. 25.1 ft. Alive, scribe visible  
on decaying face. (See Ren. #13, T28-3W.)  
Corner falls in pond 60' in diam & approx. 5' deep.  
Set - Wit. Cor. 30' N. of true cor. T28S R3W  
Brass Cap at Cor. Mkd: County Survey's Office, 1966 CC S 35/S 36  
Wit. Cor. T29S R3W  
30 ft. S. to Corner.  
Rescrbd. - 10" R.Fir N. 3° E. 8.2 ft., added "WC" between blazes.  
New BT; 9" R.Fir N. 70° W. 9.1 ft. mkd. "WC T28S R3W S35 CC CS BT.  
Note - Witness Corner lies 7 ft. N. of edge of pond.

John M. Powell  
& Crew  
12/22/66  
C. S. File No. 52/126

12/22/66

110

Corner to Sections 7 and 18 only, T29S-R2W.  
Found - Brass Cap at Corner & both BT's:  
Orig. 12", now 20" Cedar, N. 21° E. 28.4 ft. (not N. 18° E.)  
shows good scribing and scar.  
Orig. S.E. BT., now down.  
New BT: 12" Yewood bears S. 46° E. 28.0 ft. scribed S18 T29S R2W CS BT.

East 1/4 Corner to Section 12, T.29S-3W.  
Found - Stone & both BT's. as recorded  
Orig. 20", now 32" Fir, West 10.5 ft., shows good scars.  
Orig. S.W. BT. now snag.  
Note - Dist. & Bearing from cor. to Secs. 7 & 18, (See Ren. #110), checks O.K.  
New BT: 22" Cedar bears S. 80° W. 20.0 ft. mkd. 1/4 S12 CS BT.

111

Corner to Sections 1 and 12 only, T29-3W.  
Found - Stone at corner & both BT's; as recorded.  
SW. BT., now stump. N.W. BT. shows scribing.  
Set - Brass Cap alongside cor. stone & mkd: S 1 T29S  
County Surveyor's Office, 1962 R3W S 12 R2W  
New BT's: 20" Cedar bears S. 81° W. 38.3 ft. mkd. S12 T29S R3W S BT.  
7" Cedar bears N. 22° W. 29.2 ft. mkd. S 1 T29S R3W CS BT.

112

Corner to Sections 12 and 13 only, T29-3W.  
Found - Stone at corner. Both BT's., now snags, as recorded,  
show scribing.  
Brass Cap set for West 1/4 S18 R2W, as recorded.  
New BT's: 7" R.Fir bears N. 74° W. 29.3 ft. mkd. S12 CS BT.  
7" R.Fir bears S. 58 1/2° W. 42.3 ft. mkd. S13 CS BT.

113

West 1/4 Corner to Section 18, T29-2W.  
Found - Brass Cap at corner 7 both BT's; as recorded.  
N.E. BT., now snag, shows scribing. S.E. BT., now down.  
New BT: 20" Fir bears S. 24° E. 20.2 ft. scribed 1/4 S18 CS BT.  
No other BT's. scribed.

114

JAMES W. BYRON, Deputy  
M. Darby and B. Stoffel  
Nov. & Dec. 1962  
R.S. File No. 52/126