

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy
Mike Darby & B. Stoffel
Nov. & Dec., 1962
C.S. File No. 52/126

Vernon "Ray"
Tracy &
Crew
6/28/67
C.S. File
No. 52/126

Larry E. Monrean, Surveyors Office
P. E. Earle
C.S. 56/41
Nov. 7, 1973

Corner to Sections 18 and 19 only, T29-2W. 115
Found - Orig. 42", now 48" Fir, N. 1° 45' E. 167.0 ft. (not 173.6 ft.)
shows good bark scribing and old scar.
Do not find either corner stone, but both Orig. BT's. for
East $\frac{1}{4}$ Cor. Sec. 13, R3W.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 29 S
1962 R3W $\frac{S}{S}$ $\frac{18}{19}$ R2W
New BT's: 12" R.Fir bears S. 12 $\frac{1}{2}$ ° E. 21.4 ft. mkd. S19 T29S R2W CS BT.
8" R.Fir bears N. 87° E. 22.6 ft. mkd. S18 CS BT.
Note - Corners are on steep north slope.

East $\frac{1}{4}$ Corner to Section 13, T29-3W. 116
Found - Both Orig. BT's., check o.k. for bearings & distances,
shows scribing and scars.
Set - 2" x 2" x 4.0 ft. Stake at corner, 10.5 ft. south of Brass Cap
for cor. to Secs. 18 & 19, R2W (above)
New BT's: 16" R.Fir bears S. 53° W. 8.8 ft. scribed $\frac{1}{4}$ S13 CS BT.
18" R.Fir bears N. 41° W. 14.5 ft. scribed $\frac{1}{4}$ S13 CS BT.

Corner to Sections 10 and 11. 117
Found - 1964 Cadastral Brass Cap, firmly set & properly marked.
12", now 13" Fir N. 53° E. 23.1 ft., alive, scribe marks
visible on partially healed blaze. (Record N.67°E.)
7", now 8" Fir, N. 84 $\frac{1}{2}$ ° W. 81.2 ft., alive, scribe
marks visible on partially healed blaze. (This
tree to be removed for cultivation of field.)
New BT: 6" D. Fir S. 20° W. 92.7 ft. mkd. " $\frac{1}{4}$ S10 CS BT".
Note - This corner lies 40 ft. East of roadway, course N. & S.

MICROFILM TO HERE 10/67

Sec. Cor. Secs. 26-25-35-36. 118
Found - 3" I.P. 10" High. shows recent breakage from which a
34" Fir, stump 7' high bears S.14°E., 42.2 ft. (rec./
orig. notes, Fir. 18", S.15°E., 42.9 ft. ; Ren. No. 44
30" fir, S.18°E., 44.8 ft.) I open face.
40" Fir, stump, bears N.58°E., 11.4 ft. (rec./orig.
N.63°E., 13.86 ft.; Ren. No. 44, N.75°E., 16.2 ft.)
Scar visible.
12" Fir stump, bears N.48°W., 11.3 ft. (Rec/orig. notes
10" Fir, N.45°W., 7.26 ft.; Ren. #44, N.40°W., 7.0 ft.)
Rotted & burned stump, bears N.49°E., 15.8 ft. (rec/ren.
#44, N.61°E., 18.5 ft.)
30" Fir stump, bears N.81°E., 28.5 ft. (rec. 34.0 ft.)
scribing visible "S29" has been dislodged.
12" Fir stump, bears S.69°E., 32.3 ft. (rec/ren. #44,
S.66°E., 36.8 ft.)
26" Fir stump bears S.54°W., 15.6 ft. (rec/ren. #44,
S.41°W., 13.4 ft.) Bark scribed "BT"
Also find rotted remains of tree at section corner.
Set - Brass cap mkd. COUNTY SURVEYORS T 29 S R 3 W
OFFICE S 26 | S 25
1973 S 35 | S 36
from which a
34" Fir stump, 7' high, bears S.17°E., 44.6 ft.
40" Fir stump, 8' high bears N.71 1/2°E., 13.7 ft. scars
visible.
12" fir stump, bears N.44°W., 8.0 ft. scar visible grown
rings show extreme slow growth.
Rotted & burned stump, bears N.58 1/2°E., 16.4 ft.
12" fir stump, bears S.67°E., 35.8 ft. scribed "S36 BT"
26" Fir stump, bears S.41°E., 14.5 ft. scribed "BT"
Rotted remains of tree bears S.52°W., 3.3 ft. (rec/orig.
survey S.53°W., 4.62 ft.; & /ren. #44 S.43°W., 3.6 ft.)
3" I.P. shows signs of recent breakage. bears S.56°E.,
3.4 ft.

11/7/73