

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

4

R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 97196

Set by Arthur R. Evans - Deputy County Surveyor # 2741
F. D. Smith - Harvey Potter - Ivan Taylor - Witnesses

May 1949

Claude Kerr
June 6, 1950

CS 40/252

SEE CORNER NO. 90 17
Corner ²⁰⁺²¹~~29+28~~ Set Post Marked Old and New B.T.
White Oak 10" N 10° W 165 links O.B.T.
Laurel 16" S 36¼° W 118 links O.B.T.
White Oak 12" N 47½° E 266 links N/B . T
May 26, 1891 Briggs

¼ COR. BETWEEN 25/36 18
Set ¾" x 36" G. I. P. for cor., blazed and scribed B. T's.
15" Cedar S 58° E 23.8 ft., mkd. T 29 S, R 4 W, ¼ S 34.98 C.S.B.T.
10" Fir N 77° W 21.8 ft. mkd. T 29 S, R 4 W, ¼ S 25 C.S.B.T.
Nailed brass disk to Fir B.T., mkd. Co. Surv. Off., ¼ Cor. 25/36
Set by Reg. Engr. Ore. No. 2741.

SEC. COR. 25-26-35-36 19
Found 4" x 4" Cedar Stake rotted and on ground, O. B. T's. standing and dead.
14" Laurel S 15° E 13 lks.
18" Laurel N 35° E 62 lks.
10" Laurel N 70° W 15 lks.
Drove 1¼" x 30" G. I. O. for corner, marked New B. T's.
30" Fir S 61¾° W 36.0 ft., mkd. T 29 S, R 4 W, S 35 C.S.B.T.
12" Fir N 8½° W 46.0 ft., mkd. T 29 S, R 4 W, S 26 C.S.B.T.
22" Cedar S 30° E 20.1 ft. mkd. T 29 S, R 4 W, S 36 C.S.B.T.
12" Fir N 27½° E 55.5 ft. mkd. T 29 S, R 4 W, S 25 C.S.B.T.

¼ COR. 25/26 20
Set 1¼" I. P. for cor., blazed and scribed B. T's.
14" Laurel N 46° E 24.4 ft. mkd. T 29 S, R 4 W, ¼ S 29.4 B.T.
14" Fir S 35° W 11.3 ft. mkd. T 29 S, R 4 W, ¼ S 26 C.S.B.T.
nailed brass disk to this tree, mkd. Co. Surv. Off.
¼ Cor. 25/26 set by Reg. Engr. Ore. No. 2741.

¼ COR. EAST SIDE SEC. 25. ONLY 21
Set ¾" x 36" G. I. P. for cor., blazed and scribed B. T's.
10" Fir N 55° W 8.3 ft.
15" Laurel S 35° W 41.3 ft.
both mkd. T 29 S, R 4 W, E ¼ S 25 C.S.B.T., brass disk
nailed to Laurel mkd. Co. Surv. Off., E ¼ S 25
T 29 S, R 4 W, set by Reg. Engr. Ore. #2741.

¼ COR BETWEEN 9 and 10 **SEE CORNER NO. 122** 22
The original Pine BT still there and scribe marks found.
I put a new cedar post in for corner and marked a new BT.
Red Fir 20", bears S15°W for 40 lks marked ¼ S 9 BT.
The original BT 32" Pine bears N 45° E for 6 lks. marked ¼ S.

SEC. COR. 3-4-9-10. **SEE CORNER NO. 146** 23
Found scribe on the Incense Cedar, and the scar on the 6" Fir, now a 26" tree.
I set a 4" x 4" cedar post and scribed S3, S4, S9, and S10 on it.
I rescribed the small original BT on bark ¼ S B T.
This tree now is a Red Fir 26", Bears N 36° E 30 lks.

¼ COR COR BETWEEN 3 and 10 **SEE CORNER NO. 203** 24
Found both the Original BTs. Scribe of ¼ S on the 36" Laurel.
I reset the corner by putting in a 4" x 4" Cedar Post, scribed
¼ S on E & W sides, S 3 on North side, and S 10 on South side.

SEC. COR 8-9-16-17 **SEE CORNER NO. 134, 25, 4135**
Found all four small Fir BTs.
Put 4" x 4" cedar post in at corner and scribed it with S8, S9,
S 16, and S 17.

¼ COR. BETWEEN 8 and 9 **SEE CORNER NO. 134, 25, 4135** 26
Found the Laurel, bearing N 66° E for 150 lks.
I reset the corner putting a 4" x 4" Fir stake at corner and scribed it
¼ S on north and south sides, S 9 on East side, and S 8 on West side.
I marked a new BT.
A 30" Fir, bearing N 10° W for 14 lks. **5/1963 THIS COR. NOT LOCATABLE & QUESTIONABLE** By J. BYRON, 1963