

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 4 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 97198

1/4 SEC. COR. BETWEEN SECTIONS 11 and 12  
I found the Fir BT but the Maple BT is gone.  
The Fir BT is now a snag with the scribe (E S) showing plainly on  
the loose bark.  
I reset the corner from the notes putting in a 3" x 4' cedar post and  
marked 1/4 S 11 and 1/4 S 12 on post.  
I marked two BTs which bear

New BT 12" Inc. Cedar, Bears S 70° W, for 39 lks, marked T29S, R4W  
1/4 S 12 BT

New BT 18" Red Fir, bears N 70° E, for 40 lks, marked T29S, R 4 W  
1/4 S 11 BT

S. E. COR. SEC. 32

Determined by O. B. T.

A Laurel 15 in. diam. bears N 30° E, 59.0 ft. dist. O. B. T.

A Pine 20 ins. diam. bears N 12° W, 32.0 ft. dist. O. B. T.

I remark both O. B. T.

At corner point set 1" x 24" iron pipe

SEE CORNER NO. 126 29

SEC. COR. 4 - 5 - 8 - 9

Original government post still standing. Two witness trees found.

10 in. Fir. S 34° E 10 lks.

36 in. Fir S 70° W 35 lks. *Ren. 4*

Bother rotting, but scribing could be read on 10 in. Fir.

Set 1 1/2" x 24" galv. pipe on North edge of existing post

8 in. W. Fir marked S 8 B.T. 268

South 1/4 Section Corner Section 31 (determined by O.B.T.)

A fir 52" diameter bears N 32° W, 12.5' distant, scribe showing.

At corner point set 1" x 30" Iron Pipe from which

A Cedar 10" diameter bears N 1° E, 30.0' distant marked 1/4 S, S 31, B.T.

A Maple 10" diameter bears N 80° W, 62.0' distant marked 1/4 S,  
2880 B.T.

Township Corner bears S 76 1/2° W, 700.0' distant

North 1/4 Corner of Section 6 bears N 76° 30' E, 2076.0' distant

T30S, R4W.

N.W. CORNER OF SECTION 18 as determined by O. B. T.'s

A Dead White Oak Snag 11" diam. bears S. 5° E, 20.0' dist. old  
scribe showing (R 4 W, T 29 S, S 18)

A Laurel Stump 12" diam. bears N. 68° W, 11.0' dist., O.B.T.

At corner point I set a 1" x 30" Iron Pipe, from which:

A Laurel 36" diam. bears S. 85° W, 27.0' dist. marked S. 13,

T. 29 S., R. 5 W., B.T.

A Fir 10" diam. bears N. 64° W., 31.0' distant marked S. 12, B.T.

A Fir 20" diam. bears N. 38° E., 9.5' distant marked S. 7, B.T.

(bark scribe)

A Fir 10" diam. bears S. 40° E., 25.5' distant marked S. 18, B.T.

There is an old fence running East and West from the corner.

N. W. CORNER OF SECTION 31 (as determined by O.B.T.'s)

A Black Oak windfall 8" diam. bears N. 55° E., 35.0' distant

O. B. T.

A Black Oak 14" diam. bears S. 64° E., 20.0' O.B.T.

At corner point I set 1" x 30" Iron Pipe, from which:

A Fir 5" diam. bears S. 4° E., 10.5' distant marked S. 31, B.T.

A Fir 6" diam. bears S. 20° W., 24.5' distant marked S. 36, B.T.

A Laurel 12" diam. bears N. 28° W., 13.0' distant marked S. 25, B.T.

A Black Oak 10" diam. bears N. 87° E., 28.0' distant marked S. 30, B.T.

CS 40/252

Claude Kerr  
June 6, 1950

John H. Markham, Jr.  
Wit.- Geo. Vaughn  
Don Weathers  
April 7, 1951  
C. S. 40/304

Thomas R. Eslinger  
April 9, 1951

John H. Markham Jr.  
Witness  
George Vaughn  
July 18, 1951  
C.S. 40/304

Witness  
Geo. Vaughn  
Dennis Vaughn  
8-17-51 C.S. 40/315

John Markham, Jr.

Witness  
Geo. Vaughn  
8-30-51 C.S. 40/375