

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 4 R. W. W. M.

- ✓ SECTION CORNER BETWEEN 11, 12, 13 and 14. 43  
Set Iron Pipe 2" x 2' from one old B.T. Marked  
Fir 15" S. 71° 30' W., 36 lks. B.T. S. 14 C.S.  
Fir 15" N. 72° 30' E., 23 lks. B.T. S. 12 C.S.  
Fir 12" N. 8° 00' W., 32 lks. B.T. S. 11 C.S.  
Cedar 30" S. 42° E., 56 lks. B.T. S. 13 C.S. 166

---

- ✓ 1/2 CORNER BETWEEN 11 and 14. 44  
Set Iron Pipe 2" x 6' by proportional measurement.  
No B.T.s. 75 or 81A

---

- ✓ SECTION CORNER 10, 11, 14 and 15. 45  
Set Oak Stake scribed S. 10-11-14-15 C.S. Marked  
S. 61° 30' W., 38 lks. Red Fir 15" S. 15 C.S.  
S. 10° 00' E., 20 lks. Red Fir 15" S. 14 C.S.  
N. 26° 00' W., 48 lks. Red Fir 15" S. 10 C.S.  
N. 45° 00' E., 209 lks. Black Oak 18" Old B.T. 189

---

- ✓ 1/2 CORNER BETWEEN 11 and 2. 46  
Set Cedar Stake from one old B.T.  
Fir 36" dia. N. 25° 30' E., 30 lks. S. 2 C.S.  
S. 14° 00' W., 61 lks. Old B.T. 76 or 81

---

- ✓ N.W. CORNER OF D.L.C. NO. 38 (BENJ. STEPHENS) 47  
Boulder 4" x 10" x 20" long. Old B.T.s okay but badly  
rotted. Blazed and scribed as new B.T.s  
10" Oak S. 38° W., 86 lks. N.W.C. 38 C.S. B.T. 121  
12" Oak S. 62° E., 58 lks. N.W.C. 38 C.S. B.T. CS 37/62

---

- ✓ 1/4 CORNER BETWEEN 13 and 24. 48  
Reestablished as follows: Set White Oak Post 5" x 5" x 3'  
from which  
Red Cedar 5" bears S. 44° 30' W., 22.5 lks.  
Red Fir 8" bears N. 11° 30' E., 24.0 lks. 148

---

- ✓ 1/4 CORNER BETWEEN SECTIONS 24 and 25 49  
I set for 1/4 Corner a Yew Wood Post 4" x 4" x 3' from  
which  
White Fir 6" dia. S. 45° 12' E., 32 lks.  
Maple 6" dia. N. 31° 48' W., 6 lks. 68

---

- ✓ S.E. CORNER OF HANS WEAVER, D.L.C. 39. 50  
Set from evidence furnished by P. R. Weaver and from  
remains of old fence: no evidence, except stump holes of  
original bearing trees remains. Marked  
A 8" Fir N. 33° E., 95.0 ft.  
A 6" Fir N. 86° W., 31.5 ft.  
Drove a 1/2" steel drive shaft for corner on E. and W. fence  
line. 179

---

- ✓ N.E. CORNER HANS WEAVER D.L.C. 39. 51  
Found one of two original B.T.s (to S.W.) okay. B.T.  
to N.E. dead. Set 4 x 4 Oak Post and one new B.T. 176  
A 8" White Oak N. 1° S., bark blaze

---

- ✓ N.W. CORNER OF D.L.C. 39 IN SECTION 16. 52  
Original B.T.s dead. Stump of original Fir corner tree  
still standing. <sup>BENJ</sup> New B.T. #268  
Red Fir 24" dia. bears N. 87 1/2° W., 30 ft.

---

- ✓ S.W. CORNER OF N.W. 4 N.E. 4 SECTION 16. 53  
Note: In 1883 County Surveyor set this corner and marked  
one tree: This tree was cut down about two years ago and  
laying at stump. The scribe marks were cut out of stump and  
"cut off" tree. The corner, a 4" x 4" Cedar Post, was set  
from this stump and a New B.T.  
18" Fir marked which is N. 62 1/2° W., 21.5 ft. bark blaze  
"P. C. C.S. B.T.  
15" Cedar marked which is N. 38° E., 48 ft. bark blaze  
"P.C. C.S. B.T.

C.S. 3127  
 102-312-234  
 W. H. Wood Aug. 29, 1932  
 Geo. Spaur Chain  
 A. C. Redifer chain  
 W. E. Hollinger  
 Elmer Heath  
 Ralph Smith  
 Ben B. Irving  
 Phil Birges  
 M. B. Germond  
 Sept. 1908  
 A. Boyer Dep.  
 P. R. Weaver  
 Mrs. A.S. Rettaman  
 Delbert Trask  
 Ted Shellabarger  
 Oct. 12, 1938  
 A. Boyer  
 Ted Shellabarger  
 Delbert Trask  
 Oct. 12, 1938.  
 Ted Shellabarger  
 Oct. 18, 1938.  
 Arthur Boyer  
 W. H. Wood  
 W. E. Hollinger  
 Elmer Heath  
 Ralph Smith  
 Ben B. Irving  
 Phil Birges  
 M. B. Germond  
 Sept. 1908  
 A. Boyer Dep.  
 P. R. Weaver  
 Mrs. A.S. Rettaman  
 Delbert Trask  
 Ted Shellabarger  
 Oct. 12, 1938  
 A. Boyer  
 Ted Shellabarger  
 Delbert Trask  
 Oct. 12, 1938.  
 Ted Shellabarger  
 Oct. 18, 1938.  
 Arthur Boyer