

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

4

R. W. W. M.

SEC. COR. 31-32-6 (S line of Twp.)

64

Found laurel bearing tree set in 1889, dead and fallen over but could still read scribing.

Measure S 30° E a dist. of 37 lks. from stump hole and set 153 1/4" iron pipe for the sec. cor., from which:

- A 16" fir bears N 24° 14' W 31.5 ft.
- A 14" fir bears N 33° 51' E 31.5 ft.
- A 12" fir bears S 51° 19' E 34.0 ft.
- A 40" fir bears S 69° 26' E 4.0 ft.

G. A. Barnhart
Surv.
Weber
Stubblefield
Witnesses.
June 1947

C. 540/19

1/4 COR. BETWEEN SECS. 31 & 32

65

Co-ordinated a true line and distance between the cors. found it to be S 22° 23' W and 4152.76 ft. Then by proportional measure set a 3/4" x 30" iron rod 2076.4 ft. from both corners and on true line between them for 1/4 cor. from which:

- A 5" white fir bears S 80° 40' W 9.0 ft.
- A 36" red fir bears N 40° 25' E 26.6 ft.

G. A. Barnhart
Surv.
June 1947

1/4 COR. 32 & 5 (S line of twp.) NOT COMMON -

66

Found old B. T., an 8" Oak (dead) and 24" Laurel (in good condition) from Laurel measured S 70° W 63 lks. and set a bottle and 4" x 4" oak post for 1/4 cor., from which;

- A 24" Laurel bears N 70° E 41.6 ft.
- A 10" fir bears N 59° 30' E 2.9 ft.
- A 12" fir bears N 11° 00' W 14.5 ft.

(Re-survey made by Markhem in 12/5/49, Reset corner. See file 40-238 214)

G. A. Barnhart
Surv.
June 1947

SEC. COR. 21-22-27-28

SEE # 110

67

Found 2" x 2" madronna post, replaced with 3/4" iron pipe.
O.B.T. 66" Fir scribed S 27° C.S. B.T. S 37° 44' E 29.2 ft.
Remarked madronna stump with illegible scribed marks S 57° 12' W 28.3 ft., and 44" Fir S 38° E 37.5 ft.
New B. T.
14" W. Fir S 35° W 22.6 ft.
40" D. Fir N 31 1/2° W 66.6 ft.
10" D. Fir N 70° E 68.1 ft.

B.B. Irving
County Surveyor
A. R. Evans
Witness
March 1948
M 13-69

1/4 COR. BETWEEN SECS. 24-25 ONLY

FO OK 1-95 BY R. Brown M 121-38

68

Set by proportionate measurement, set 1 1/2" x 30" I. P. 6" underground. Blazed and scribed B. T's. SEE COR. # 49
30" Cedar N 10 1/2° W 28.6 ft., mkd. T 29 S, R 4 W, S 24, C.S.B.T.
6" Fir S 16 1/2° E 28.4 ft., mkd. T 29 S, R 4 W, 1/4 S 25 C.S.B.T.
Nailed brass disk to 30" Cedar - mkd. Co. Surv., 1/4 cor. 24/25 set by Reg. Engr. Ore. No. 2741.

Set by Arthur R. Evans - Deputy County Surveyor # 2741
F. D. Smith, Harvey Potter, Ivan Taylor - Witnesses

SEC. COR. 24/25 ONLY

69

Found rotted & burned stumps of NW & SW B. T's., scribe mks. visible. Set 1" G.I.P. with brass cap, marked Co. Surv. Off. T 29 S, R 4 W, Sec. Cor. 24/25, R. E. 2741. Nailed brass disk on 30" Fir, mkd. Co. Surv. Off., Sec. Cor. 24/25 T 29 S, R 4 W, set by Reg. Engr. No. 2741.
30" Fir bearing N 20° W 14.2 ft., mkd. T 29 S, R 4 W, S 24 C.S.B.T. 161
24" Fir bearing S 40° E 20.9 ft., mkd. T 29 S, R 4 W, Sec. 25 C.S.B.T.
No trees in Sec. 25.

May 1949
M A P M 1 - 31

SEC. COR. 25/36 ONLY

70

Set 1" G. I. P. with brass cap for Cor. Secs. 25/36, mkd. Co. Surv. Off., T 29 S, R 4 W, Sec. Cor. 25/36 R. E. 2741. Blazed and scribed B. T's.
15" Fir, N 80° W, 21.3 ft., mkd. T 29 S, R 4 W, S 25, C.S.B.T.
18" Fir, S 26° W, 27.7 ft., mkd. T 29 S, R 4 W, S 36, C.S.B.T. 160
Found old B. T's.
White Oak stump N 32° W definite axe marks and 2 distinct blazes, deed and face of blaze rotted.
B. Oak, N 37° E, down and rotted, but axe marks and blaze definite.