

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 4 R. W. W. M.

BOYE-CHAPMAN CO. EUGENE, ORE. 97106

Jno. H. Markham, Jr. John H. Markham Jr.

Witness
Dennis Vaughn
Geo. Vaughn

Nov. 2, 1951

C.S. 40/386

Witness
Geo. and Dennis
Vaughn

Nov. 2, 1951

J. H. Markham Jr.
Wit; Frank White
Work For

Paul Barber
Drawer 41
File 102

A. R. Evans

Drawer 41
File 102

Also see
Drawer 41
File 102

Ben B. Irving

Jim Byron
Ray Irving
Dec. 17, 1953
File 45/234
pgc. 5.

Ben B. Irving

Jim Byron
Ray Irving
July 23, 1953
File 45/234
pgc. 5.

S.W Corner of Section 35, T 29 S R 4 W, W.M. as determined by O.B.T.

- A B.O. 14" diam. bears S.41°W.18.5' dist. O.B.T.
- A B.O. stump bears S 57°E.25.0' O.B.T.
- A B.O. 16" diam. bears N 86°E.34.0' O.B.T.
- A corner point set 1"x30" I.P. from which
- A. Laurel 8" diam. bears N.42°W 12.0' dist. marked S.34 2880, B.T.
- A Pine 8" diam. bears N 41°E, 25.0' dist. marked S.35,13. T.

71

South 1/4 Corner Sec. 35, T 29 S R 4 W W.M. as determined by O.B.T.

- A Fir stump bears N 7 E.14 1/2' dist. O.B.T. REN #2
- At corner point set 1"x30" I.P. from which
- A Cedar 14" diam. bears N.30 W.20.0' dist. mkd. 1/4 s 35, B.T.
- A Fir 12" diam. bears N 57E, 61.0 dist. mkd. 1/4 s B.T.
- Section corner 2 - 3 bears West, 165.0'
- There is a fence running approx. North and West from 1/4 corner.

72

1/4 cor. sections 13 / 14, as determined by 06/06/16/ proportional measurement.

- At midpoint on section line, I set a 1/2" X 12" I.P. from which;
- A yellow Pine, 22" bears N 66° W, 18.0', mkd. 1/4 S SL4 B.T.
- A Cedar 10", bears N 44°E 18.0' mkd. 1/4 S SL3 B.T.
- N. E. cor. 14 bears N. 2570'
- S. E. " " " S. "

73

1 / 16 north of 1/4 cor section 13 / 14

- On. Midpoint on the section line between E 1/4 cor & the N. E. Cor. of Section 14.
- I set a 2" X 2" wood post from which;
- A Fir, 32" daim. bears N 60° E, 18.0', mkd with bark scribe 1/16s BT
- A fir, 10", Bears S 21° W, 12.5' mkd. 1/16S BT
- 1/4 Cor. Bears S. 1285'
- N. E. Cor. Bears N. 1285'

74

1/4 Cor. 11 / 14

- Fd. 2" I. P. REN #44 SAME AS #81A
- Blaze & scribe B. T. s
- 36" Fir N 15° E, 171.6', mkd. 1/4 S 11 BT, Copper Tag mkd. R.E. 2741
- 28" Cedar, S 80° E, 98.9', mkd. 1/4 S 14 BT, Copper Tag mkd. R.E. 2741

75

1/4 Cor. 2 / 11

- Fd. Fir Stake & 1 O.B.T. REN #46 SAME AS #81
- 36" Fir., N 25 1/2° E, 30 lks., Rescribed O.B.T.
- Blaze & scribe N.B.T.
- 30" Fir, S 48°45' W 23.9' Mkd. 1/4 S 11 B.T. Copper Tag Mkd. 2741

76

1/4 cor. to secs. 5 and 8.

- Blazed and scribed two trees;
- 10 inch Cedar, N.36°E., 155.5 feet, mkd. 1/4 S 5 CS BT. (3 prong tree).
- 12 inch Alder, S.37°E., 78.8 feet, (East bank N. Myrtle Creek), mkd. 1/4 S 8 CS BT. SEE REN # 5
- Copco pole bears S.75°47'W., 26.8 feet.
- Set a 1 inch X 36 inch iron pipe with brass cap, 1/4 cor. 5-8 T29S R4W. W.M.

77

1/4 Cor. secs. 7 and 8.

- Pos identified from stump of OBT - 12 inch Fir N.15°E., 60 lks (tree 36 inches when cut).
- Blazed and scribed two new BTs.
- 12 inch Fir, N66°W., 9.3 feet, mkd. 1/4 S 7 CS BT.
- 12 inch Fir S.14°E., 42.3 feet, mkd. 1/4 S 8 CS BT.
- Set 1 inch iron pipe with brass cap mkd. - - County Surveyors Office

78

1/4 cor.
Sec. 7 | Sec. 8