

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

79
 $\frac{1}{4}$ corner sec. 18 and section 13 of T 29 S, R 5 W.
 Set a 1 inch X 30 inch iron pipe ^{WITH BRASS CAP} 18 inches above ground-mound of stone.
 Positive identification by both orig. B.Ts.
 Blazed and scribed 24 inch W.O. S.80°E., 37 feet, mkd. $\frac{1}{4}$ S 18 C.S. B.T.
 Reblazed and scribed O.B.T. N.18°W., 38 lks., (24 inch W.O.) and mkd.
 $\frac{1}{4}$ S 13 CS. BT. Orig. record showed this BT N.78°W., should be N.18°W.

B. B. Irving
 J. Byron
 R. Irving
 File 45/234
 Page K.
 July 24, 1953

N. E. Cor. D.L.C. No. 48. (in T29S, R5W)
 Found $\frac{1}{4}$ inch pipe.
 Old B.T. in good condition, Now 24 inch, S.85°W., 131.0 feet.
 Scribed and blazed 12 inch W. O., S.5°52'W., 102.1 feet, CL 48, C.S. BT.

B. B. Irving
 J. Byron
 R. Irving
 File 45/234
 Page P.

Sec. cor. secs. 7 and 18, T29S, R4W, and secs. 12 and 13, T29S, R5W.
 Found 1 inch iron pipe and 2 orig. B.T.'s - REN #31
 10" B.O. S.5°E., 30 lks.
 9" B.O. S.68°W., 23 lks.
 New B.T.s -
 30" Mad. N.81°W., 28.2 feet, mkd T29-R5 S 12 - BT. RE 2741.
 22" Fir, N.30°E., 11.4 feet, mkd T29-R4, S 7.

A. R. Evans
 Wlt:
 G. E. Johnson
 E. E. Evans
 J. I. Clinton
 April 10, 1953
 For I.K. Snyder
 File C541/247

80
 $\frac{1}{4}$ corner secs. 2/11. REN #4
 Found Cedar Stake and O. B. T. - 36" Fir, N.25°E., 30 lks. - (Rescribe)
 N.B.T. Blazed and scribed.
 30" Fir, S.48°W., 23.9 dist. mkd $\frac{1}{4}$ S-11-B.T., Copper tag R.E. 163

A. R. Evans
 Wlt:
 J. I. Clinton
 N. E. Evans
 Dec. 15, 1952
 For Walter Hodges
 Filed in 41/247

81A
 $\frac{1}{4}$ corner secs. 11/14.
 Found 2" iron pipe. SEE REN #44
 Blaze and scribed 2 N.B.T.s. SEE CORNER NO. 167
 36" Fir, N.15°E., 171.6 ft. mkd. 13 - 11 - BT - Copper tag R E 2741.
 28" Cedar, S.80°E., 98.9 feet, mkd $\frac{1}{4}$ S - 14 - BT - Copper tag R E 2741.

SAME AS #76
 SAME AS #75

82
 $\frac{1}{4}$ corner secs. 14 and 28.
 Found 1 inch iron pipe at fence intersection and old R. Fir BT S.43°W.,
 67 feet in good condition. REN #33
 Blazed and scribed new trees.
 6" White Oak, S.42°30'W., 26.2 feet, mkd. $\frac{1}{4}$ S 23 CS BT.
 6" White Oak, S.69°E., 66.5 feet, mkd. $\frac{1}{4}$ S 14 CS BT.

County Sur. Off.
 Jim Byron
 Ray Irving
 Jan. 22, 1954
 File 45/236

83
 $\frac{1}{4}$ corner secs 7/18.
 $\frac{1}{4}$ corner set at midpoint on a line between sec. cots. 7, 8, 18, & 17 and 12, 7, 13 & 18. - REN #
 Set brass cap mkd. County Surveyor's Office $\frac{1}{4}$ S 7 - 18.
 Blazed and scribed two trees
 18" R. Fir $\frac{1}{4}$ S 18 CS BT R4W., S.23°20'W., (48:3' - 24°10')=44.1 feet.
 20" R. Fir $\frac{1}{4}$ S 7 CS BT R4W., N.85°20'W., 29.1.

Ben B. Irving
 County Surveyor
 J. Byron
 R. Irving
 J. Fee
 File 45/234

84
 Sec. corner to secs. 7, 8, 17, and 18.
 Location indefinite but found 24" Fir tree at location that would fit B. T. established by Briggs 1899 N.89 $\frac{1}{2}$ °W., 23 lks. from cor. This tree does not show identifiable axe blazes but old fence E. and W. tied to it with old picket gate on E. side.
 The corner as located from this tree would be over the bank where N. Myrtle Creek has washed. The distance fits very close to old creek bank noted by Hathorn at 76.30 chs. E. of cor. secs. 7, 12, 13 and 18. Myrtle Creek has changed its channel and is now east of the corner though right creek bank is identifiable. By using this location for the corner we find it to be S.89°59'47"E., 5177.15 feet from the corner 7,12,13 and 18. This location fits old fence line claimed by owners to be property line.
 The $\frac{1}{4}$ sec. corner to secs 8/17 is S.89°59'E., 2583.41 feet from this location.
 The $\frac{1}{4}$ sec. corner to secs. 7/8 is N.0°18'W., 2711.06 from this location.
 A traverse was run south but $\frac{1}{4}$ cor. 17/18 has been lost as is the C. C. sec. corner 17/18 and the cor. 19/20 on the S. bdy sec. 19. An old oak with ancient line blazes was found S.5390.84 feet and E. 502.71 feet from this corner location. As the cor. location fell on a sand bar below the present creek bank and subject to wash, a witness corner was set at the base of the tree noted as follows - -

March 4, 1954 - File 45/234
 Ben B. Irving, County Surveyor
 Witnesses:
 J. W. Byron
 R. G. Irving
 John Fee