

Douglas County Surveyor's Record of
Government Corners Renewed

29

4

T. S.

R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

Continued from preceding page.

84

Set a 1" by 36" Galvanized Iron pipe with brass pipe at base of tree for a W. C. to the sec. cor. Mkd. County Sur. office-W. C. T29S, R4W - 1954. - from which

- A Fir, 24" diam. bears N.89 $\frac{1}{2}$ °W., 3.0 feet.
- A 24" Cedar, N.27°E., 31.8 feet.
- A 10" Cedar S.47°50'W., 36.8 feet.
- all blazed and scribed T29S, R4W., W. C. S 7-8-17-18. CS BT.
- A 14" Cedar N.7°W., 93.2 feet.

see also #186

$\frac{1}{4}$ sec. corner to secs. 8 and 17.

FD. OK 12/94 BY DOLAN M121-29

85

Set 1" iron pipe and brass cap m'k'd.

County Surveyors

$\frac{1}{4}$ S

8

17 R4W

1954

Office

(See C.S. 18/50 for 1934 Boyer Renewal not typed)

from which;

- 14" Cedar N.36°45'W., 41.3.
- 35" Pine, S.38°45'E., 29.6 Fd. BT.

Renewed from original stake.

Ben B. Irving
R. Irving
John Fee
J. Byron
March 4, 1954
File 45/234

$\frac{1}{4}$ sec. corner to secs. 35/36

86

Determined by O. B. T.

- A 12" Fir bears S.87°W., 14.0 feet dist., - O. B. T. - found scribe.
- A 24" Fir, Windfall bears S.70°E., 11.0 feet dist., - O. B. T.
- At corner point set 1" x 30" iron pipe.
- from which
- A 16" Cedar bears S.59°W., 17.2' dist. mkd. $\frac{1}{4}$ S 35, B. T.
- A 30" Sugar Pine bears S.23°W., 45.5 feet dist. mkd. $\frac{1}{4}$ S B. T.
- A 12" Cedar bears N.35°E., 77.2 feet dist., mkd. $\frac{1}{4}$ S 36, B.T.
- Creek bears East approx. 210 feet.
- Creek bears South approx. 380 feet.

RENEWED, SEE CORNER NO. 200

John H. Markham Jr.
Wit: Geo. Vaughn
Done for Stomar Lumber Co.
File 49/386

Northwest corner section 19.

Corner set by proportional measurement.

FD. OK by G. GRUBB
Dec 1981
RM 3-52

87

At corner point set 1" x 30" iron pipe and large rock, from which

- A 13 inch Fir bears S.65°E., 21.0 feet dist. mkd. S 19 B. T.
- A 14 inch Fir bears N.24°E., 10.0 feet dist. mkd. S 18 B. T.
- A 6 inch Fir bears N.37°W., 16.0 feet dist. mkd S 13 B. T.
- A 10 inch Fir bears S.22°W., 33.0 feet dist. mkd. S 24 B.T.

West $\frac{1}{4}$ corner section 18 bears North 2667.0 feet.

West $\frac{1}{4}$ corner section 19 bears South 2600.0 feet.

Corner lies on a 75% North slope.

Top of divide lies South 650 feet.

SEE GOVT. NOTES
1957 BRASS CAP
4' SOUTH

Closing corner to secs. 19 and 20. (on S. bdy sec. 18.)

88

Set a 1 inch by 36 inch iron pipe in ground for the corner from down B. O. S.35°W., 126 lks. chopped out and found scribe and B. O. N.45°W., 25 lks. down and rotten.

Scribed two new trees:

- A 12 inch Fir, S.38 $\frac{3}{4}$ °W., 33.7 feet on level.
- A 10 inch Fir, S.45°E., 55.0 feet (slope.)

SEE CORNER NO. 204

Closing corner to secs. 17 and 18. (on N. bdy sec. 20.)

89

Set a 1 inch by 36 inch iron pipe with brass cap 14 inches above ground from O. B. T. - 20 inch Fir N.68°W., 30 lks. chopped out - in good condition.

Marked two new bearing trees:

- A 12 inch Fir, N.79°11'W., 49.1 feet, mkd. T29S, R4W, S 18 C.C.-CS BT.
- A 12 inch Fir, N.43°33'E., 21.1 feet, mkd. T29S, R4W, S 17 C.C.-CS BT.

Ben B. Irving, County Surveyor
Work done for J. E. Pruitt - July 2, 1954
John H. Markham Jr.
Joe Pruitt
July 7, 1954
Witnesses:
C. C. Pruitt
J. E. Pruitt
C. S. File 41/279
See File No. 45/234