

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

4

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97196

90

Section corner to secs. 20-21-28 and 29.

Affidavit:

I, I. C. Dyer, age 60, having been born and raised on the SE $\frac{1}{4}$ of Sec. 20, T 29 S, R 4 W., W. M., did replace a badly decayed stake with a 2 inch iron pipe at the corner of sections 20-21-28-29., then later built a fence to it.

I. C. Dyer
Witnessed by
Jack L. Sheppard
L. S. 180.
Feb. 9, 1955.

91

Section corner to secs. 27, 28, 33 and 34.

Set 1 inch iron pipe from original Government B. T.s.

32 inch Fir, S.60°E., 16.5 feet - Old bearing tree.

36 inch Fir, N.60°E., 59.4 feet - Old bearing tree.

44 inch Cedar, S.47°W., 17.8 feet - Old bearing tree.

12 inch White Fir, N.16°W., 27.0 feet - New bearing tree, Scribed

S 28 LS 180 B.T.

92

Closing corner to secs. 32 and 33.

Found 1 inch iron pipe set from original B. T.s.

14 inch Laurel, N.30°E., 58.7 feet - Old bearing tree.

20 inch Pine, N.72°W., 32.3 feet, Old bearing tree.

93

Section corner to sections 29, 30, 31 and 32.

Found $\frac{3}{4}$ inch iron rod as by Barnhart - 1946

8 inch Fir, N.19°52'W., 4.0 feet - Barnhart New bearing tree.

16 inch Cedar, S.50°03'W., 20.5 feet - " " " "

Other 2 B. Ts. destroyed by logging road.

Marked:

10 inch Soft Maple, S.37°E., 51.9 feet, S 32 LS 180 BT.

12 inch Cedar, N.47°E., 44.3 feet, S 29 LS 180 BT.

94

Section corner to secs. 28, 29, 32 and 33.

Set 1 inch iron pipe by double proportion.

Scribed 4 trees:

18 inch Fir, S.8 $\frac{1}{2}$ °E., 43.0 feet, scribed S33 LS 180 BT.

9 inch Yew, S.34 $\frac{1}{2}$ °W., 38.9 feet, scribed S32 LS 180 BT.

32 inch Cedar, N.60 $\frac{1}{2}$ °E., 69.4 feet, scribed S 28 LS 180 BT.

12 inch Fir, N.42 $\frac{1}{2}$ °W., 36.3 feet, scribed S29 LS 180 BT.

95

$\frac{1}{4}$ sec. corner to secs. 29 and 32.

Set 1 inch iron pipe. (By proportion).

Scribed two trees:

8 inch Cedar, S.13°E., 20.8 feet, scribed $\frac{1}{4}$ S 32 LS 180 B.T.

24 inch Fir, N.67 $\frac{1}{2}$ °E., 26.0 feet, scribed $\frac{1}{4}$ S 29 LS 180 BT.

96

$\frac{1}{4}$ sec. corner to secs. 32 and 33.

Set 2 inch iron pipe. (Halfway between sec. corners)

Scribed two trees:

30 inch Fir, N.19°E., 9.4 feet, scribed $\frac{1}{4}$ S 33 LS 180 BT.

18 inch Cedar, S.26°W., 16.0 feet, scribed $\frac{1}{4}$ S 32 LS 180 BT. 210

97

$\frac{1}{16}$ corner, on south half of line between secs. 32 and 33.

Set 1 inch iron pipe.

18 inch Fir, N.17°E., 26.4 feet, scribed S $\frac{1}{16}$ S 33 LS 180 BT.

12 inch Fir, S.36°W., 18.0 feet, scribed S $\frac{1}{16}$ S 32 LS 180 BT.

98

$\frac{1}{4}$ sec. corner to secs. 27 and 28.

Set 1 inch iron pipe. (Proportioned).

Scribed two trees:

30 inch Fir, S.58°E., 9.2 feet, scribed $\frac{1}{4}$ S 27 LS 180 BT. 212

26 inch Fir, N.31°W., 10.3 feet, scribed $\frac{1}{4}$ S 28 LS 180 BT.