

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 97196

Jack L Sheppard - L. S. 180.  
January and February, 1955.  
C. S. File 41/337.

John H. Marldham, Jr.  
Witness C. C. Pruitt.  
April 27, 1955.  
C. S. File No. 41/386.

James W. Byron, Deputy Co. Surveyor  
May, 1956  
C. S. File No. 47/101

$\frac{1}{4}$  sec. corner to secs. 28 and 33.  
Set 1 inch iron pipe. (Proportioned).  
20 inch Cedar, S.  $53^{\circ}$ E., 22.5 feet, scribed  $\frac{1}{4}$  S 33 LS 180 BT.  
8 inch Fir, N.  $22\frac{1}{2}^{\circ}$ E., 48.9 feet, scribed  $\frac{1}{4}$  S 28 LS 180 BT.

99

$\frac{1}{4}$  sec. corner to secs. 28 and 29.  
Set 1 inch iron pipe. (Proportioned).  
Scribed two trees:  
8 inch Cedar, N.  $68^{\circ}$ E., 9.0 feet, scribed  $\frac{1}{4}$  S 28 LS 180 BT.  
6 inch Cedar, S.  $34^{\circ}$ W., 46.9 feet, scribed  $\frac{1}{4}$  S 29 LS 180 BT.

100

$\frac{1}{4}$  sec. corner to secs. 21 and 28.  
Set 1 inch iron pipe. (Proportioned).  
Scribed two trees:  
26 inch Fir, N.  $18^{\circ}$ E., 9.1 feet scribed  $\frac{1}{4}$  S 21 LS 180 BT. 215  
36 inch Fir, S.  $3^{\circ}$ E., 26.0 feet scribed  $\frac{1}{4}$  S 28 LS 180 BT.

101

Center  $\frac{1}{4}$  section corner to section 28.  
Set by intersection of mid section lines.  
Set 1 inch iron pipe.  
Scribed two trees:  
20 inch Fir, N.  $81^{\circ}$ W., 22.7 feet, scribed  $\frac{1}{4}$  S 28 LS 180 B. T.  
28 inch Fir, S.  $79^{\circ}$ E., 17.9 feet, scribed  $\frac{1}{4}$  S 28 LS 180 B. T.

102

South  $\frac{1}{4}$  sec. corner to sec. 18 only.  
Set by proportional measurement.  
At a point 271.4 feet east of the Southwest corner of sec. 18 and 2622 feet  
West of the Southeast corner of sec. 18, I set  $\frac{3}{4}$  inch x 24 inch iron pipe  
for  $\frac{1}{4}$  corner, from which:  
A 24 inch Fir bears N.  $52^{\circ}$ E., 8.0 feet dist., bark scribed  $\frac{1}{4}$  S 18 B. T.  
A 23 inch Fir bears N.  $43^{\circ}$ W., 21.6 feet dist., bark scribed  $\frac{1}{4}$  S 18 B. T.  
North  $\frac{1}{4}$  corner section 19 bears West 60.0 feet.  
Dry wash bears West 100.0 feet.

103

North  $\frac{1}{4}$  sec. corner to sec. 19 only.  
Set by proportional measurement.  
At a point 265.4 feet East of the Northwest corner of sec. 19 and 275.4 feet  
West of the Northeast corner of sec. 19, I set  $\frac{3}{4}$  inch by 24 inches  
iron pipe for  $\frac{1}{4}$  corner, from which:  
A 6 inch W. O. bears N.  $81^{\circ}$ E., 17.5 feet dist., mkd.  $\frac{1}{4}$  S 19 B. T.  
A 12 inch Fir bears S.  $30^{\circ}$ E., 15.7 feet dist., mkd.  $\frac{1}{4}$  S 19, B. T.  
South  $\frac{1}{4}$  corner to Sec. 18 bears East 60.0 feet dist.

104

Section corner to secs. 14, 15, 22 and 23.  
Found 1 inch iron pipe at corner. - REN. # 16 & # 59  
Found 12 inch Fir, Bears N.  $62^{\circ}$ E., 23.5 feet.  
Found 8 inch Laurel, S.  $44^{\circ}30'$ E., 26.0 feet, mostly grown over.  
Found old stump, S.  $43^{\circ}$ W., 22.0 feet, no scribing left - may be original B. T.  
Blaze and scribe new tree:  
12 inch R. Fir, N.  $22^{\circ}$ W., 91.0 feet marked S 15 C. S. B. T.

105

$\frac{1}{4}$  sec. corner to secs. 22 and 23.  
Corner set half way between section corners.  
Set an iron pipe with brass cap marked  $\frac{1}{4}$  S 22/23 County Surveyors Office  
1956, T 29 S, R 4 W.  
Blazed and scribed two trees: 241  
14 inch Apple tree, N.  $74^{\circ}$ E., 14.0 feet, marked  $\frac{1}{4}$  S C. S. B. T.  
24 inch Ash, North 101.0 feet, marked  $\frac{1}{4}$  S C. S. B. T.  
South Myrtle Creek 350 feet to North.  
S. W. corner of house bears N.  $10^{\circ}$ E., 90 feet.

106