

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97195

107

Section corner to secs. 22, 23, 26, 27.
Corner set by double proportional measurement.
Set iron pipe with brass cap at corner point marked $\frac{22}{27}$ / $\frac{23}{26}$ County Surveyors
Office, 1956. - RESET BEARS CAP $S 81^{\circ} W. 9.25$ FT.
OCT. 1959 J.L.
Scribed 4 trees:
24 inch Fir, $S. 25^{\circ} W. 40.3$ feet, marked S 27 C.S.B.T. T 29 S, R 4 W.
30 inch Laurel, $S. 95^{\circ} E. 72.7$ feet, mkd. S 26 C.S.B.T. T 29 S, R 4 W.
30 inch Pine, $N. 74^{\circ} E. 40.5$ feet, mkd. S 23 C. S. BT., T 29 S, R 4 W.
8 inch Laurel, $N. 29^{\circ} W., 21.3$ feet, mkd. S 22 C.S. BT., T 29 S, R 4 W.

108

$\frac{1}{4}$ sec. corner to secs. 23 and 26.
Corner set half way between section corners.
Set and iron pipe with brass cap mkd. County Surveyors Office $\frac{1}{4}$ S 23/26,
T 29 S, R 4 W., 1956.
Scribed:
6 inch Fir, $N. 5^{\circ} E., 27.0$ feet, mkd. $\frac{1}{4}$ S 23 C. S. BT.
24 inch Laurel, $S. 4^{\circ} E., 16.3$ feet, mkd. $\frac{1}{4}$ S 26 C. S. BT., T 29 S, R 4 W.

109

$\frac{1}{4}$ sec. corner to secs. 22 and 27.
Corner set half way between section corners.
Set an iron pipe with brass cap mkd. $\frac{1}{4}$ S 22/27, T 29 S, R 4 W., County
Surveyors Office, 1956.
Scribed:
20 inch Fir, $S. 65^{\circ} E., 35.5$ feet, mkd. $\frac{1}{4}$ S 27 C. S. BT., T 29 S, R 4 W.
30 inch Fir, $N. 10^{\circ} W., 62.0$ feet, mkd. $\frac{1}{4}$ S 22 C. S. BT., T 29 S, R 4 W.
30 inch Laurel, North 80 feet, mkd. $\frac{1}{4}$ S BT.

110

Section corner to secs. 21, 22, 27, and 28.
Found $\frac{3}{4}$ inch iron pipe at corner and all BTs.
Scribed 12 inch W. Fir, $S. 80^{\circ} W., 25.0$ feet, mkd. S 28 C. S. BT.

111

$\frac{1}{4}$ sec. corner to secs. 26 and 27.
Corner set half way between section corners.
Set an iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S 27/26, T 29 S,
R 4 W., County Surveyor's Office 1956.
Scribed:
30 inch Fir, $N. 43^{\circ} E., 25.8$ feet, mkd. $\frac{1}{4}$ S 26 C. S. BT., T29S, R4W.
28 inch Fir, $N. 63^{\circ} W., 61.0$ feet, mkd. $\frac{1}{4}$ S 27 C. S. BT., T29S, R 4W.
30 inch Laurel, $S. 74^{\circ} W., 10.0$ feet, mkd. $\frac{1}{4}$ S C. S. BT.

112

$\frac{1}{4}$ sec. corner to secs. 26 and 35.
Corner set half way between section corners.
Set and iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S 26/35, T 29 S,
R 4 W., County Surveyors Office, 1956.
Bark scribed two trees:
30 inch R. Fir, North 23.0 feet, mkd. $\frac{1}{4}$ S 26 C. S. BT., T29S, R4W.
40 inch R. Fir, $S. 33^{\circ} 30' E., 19.8$ feet, mkd. $\frac{1}{4}$ S 35 C. S. BT., T29S, R4W.

113

Section corner to secs. 26, 27, 34 and 35.
Corner set by double proportional measurement.
Set an iron pipe with brass cap at corner point mkd. County Surveyors
Office, 1956 $\frac{27}{34}$ / $\frac{26}{35}$ T 29 S, R 4 W.
From which:
10 inch Fir, $N. 29^{\circ} 30' E., 78.1$ feet, mkd. S 26 C. S. BT., T29S, R4W.
10 inch Fir, $S. 37^{\circ} E., 32.0$ feet, mkd. S 35 C. S. BT., T29S, R4W.
8 inch Fir, $S. 15^{\circ} W., 29.8$ feet, mkd. S 34 C. S. BT., T29S, R4W.

114

$\frac{1}{4}$ sec. corner to secs. 27 and 34.
Corner set half way between section corners.
Set an iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S 27/34 T 29 S, R 4 W.,
County Surveyors Office, 1956.
From which:
10 inch R. Fir bears $N. 45^{\circ} E., 40.0$ feet mkd. $\frac{1}{4}$ S 27 C. S. BT.
12 inch R. Fir bears $N. 56^{\circ} W., 27.0$ feet mkd. $\frac{1}{4}$ S 27 C. S. BT.
30 inch Cedar bears $S. 52^{\circ} W., 35.5$ feet mkd. $\frac{1}{4}$ S 34 C. S. BT.

James W. Byron, Deputy County Surveyor
C. S. File No. 47/101.
RM 1 - 8

MAY, 1956