

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 4 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy County Surveyor
May, 1956
C. S. File No. 47/101. R.M. 1-8

John H. Maricham Jr.
Work done for Stomer Lumber Co.
Aug. - Dec., 1956
C. S. File No. 42/186.

$\frac{1}{4}$ sec. corner to secs. 34 and 35. 115
Corner set half way between section corners.
Set an iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S 34/35, County
Surveyors Office, 1956.
From which:
10 inch W. Fir bears N.46°W., 54.5 feet mkd. $\frac{1}{4}$ S 34 C. S. BT/
8 inch W. Fir bears S.21°E., 93.0 feet mkd. $\frac{1}{4}$ S C. S. BT.

Closing corner to sections 34 and 35 on South boundary of township. 116
Found 1 inch iron pipe at corner. REN #71
Found the following trees:
16 inch Oak BT., N.86°E., 36 feet in good condition.
8 inch Laurel, N.42°W., 12.0 feet, down.
14 inch B. Oak, old BT, stump only. 219
8 inch Pine, N.50°E., 25 feet, in good condition.

Scribed:
12 inch R. Fir, N.55°W., 31.2 feet mkd. T 29 S, R 4 W., C. S. BT.

Center $\frac{1}{4}$ corner to section 35. 117
Corner set at the intersection of $\frac{1}{4}$ sec. lines.
Set a 1 inch iron pipe at corner.
From which:
12 inch Fir bears N.52°E., 12.2 feet mkd. C $\frac{1}{4}$ S 35 C. S. BT.
12 inch Fir bears S.45°E., 29.8 feet mkd. C $\frac{1}{4}$ S 35 C. S. BT.

Center of Section 26. 118
At corner point set $\frac{3}{8}$ inch x 30 inch iron rod.
From which:
A 10 inch White Fir bears West 44.0 feet dist., mkd. C $\frac{1}{4}$ S 26, 2880 B.T.
A 12 inch Fir bears N.7°E., 21.4 feet dist., mkd. C $\frac{1}{4}$ S 26 B. T.
A 48 inch Fir bears S.81°E., 23.4 feet dist., mkd. C $\frac{1}{4}$ S B. T. on bark.
Road bears West 23.0 feet.
Creek bears South 40.0 feet.

$\frac{1}{4}$ corner to secs. 10 and 15. 119
Corner determined by old B. T. - 10 inch Alder stump bears N.15°E., 10 ft. - OBT.
Set a 2 inch x 30 inch steel shaft at corner point with 4 inch collar up.
From which:
A 30 inch Fir bears S.36°W., 6.5 feet, dist, mkd. $\frac{1}{4}$ S B. T. 175
A 15 inch Maple bears N.44°W., 114.0 feet dist., mkd. $\frac{1}{4}$ S 10 B. T.
An 11 inch Fir bears S.47°W., 77.5 feet dist., mkd. $\frac{1}{4}$ S 15 B. T.
An 18 inch Cedar bears N.89°E., 113.0 feet dist., mkd. $\frac{1}{4}$ S 10 B. T.
Ben branch creek bears West 112.0 feet dist.
Road bears East 78.0 feet dist.
Corner lies in small side creek.

$\frac{1}{4}$ corner to secs. 9 and 16. 120
At corner point found scribed post - set by C. S. in 1938. REN #54
Drove a 2 inch x 30 inch solid steel shaft 22 inches in ground at corner
point.
From which:
A 4 inch B. O. bears S.4°E., 29.0 feet dist., mkd. $\frac{1}{4}$ S 16 B. T.
A 7 inch La. bears N.50°W., 57.0 feet dist., bark scribed $\frac{1}{4}$ S, S 9,
T 29 S., R 4 W., B. T.
A woven wire fence bears East and West from corner. 180
School Hollow Creek bears East 350.0 feet dist.

Northwest corner of Benj. L. Stephens D. L. C. No. 38. 121
Found stone set by County in 1938, at a point 1016.0 feet South of the
Northeast corner of the H. Weaver D. L. C. No. 39. - REN # 47
Set a $\frac{3}{8}$ inch x 36 inch iron rod at corner point, 24 inches in ground.
From which:
A 10 inch Fir, bears N.20°E., 35.0 feet dist., mkd. CL. 38 B. T.
A 12 inch W. O., bears S.36 $\frac{1}{2}$ °W., 58.7 feet dist., mkd. CL. 39,
T29S, R4W., B. T.
A 12 inch Square marble grave stone bears S.89°E., 285.0 feet.
Fence bears N - S. from corner.