

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

122
 $\frac{1}{4}$ corner to secs. 9 and 10.
Corner point determined by O. B. T.:
A 48 inch Pine bears N.45E., 4.6 feet dist. - found scribe, O. B. T.
A 20 inch Fir bears S.17W., 27.0 feet dist. - O. B. T. *REN. #22*
At point for corner set $1\frac{1}{2}$ inch x 36 inch iron pipe, 24 inches in ground,
from which:
A 20 inch Fir bears S.26E., 27.5 feet dist. mkd. $\frac{1}{4}$ S 10 B. T.
A 20 inch Pine bears S.85W., 40.8 feet dist. mkd. $\frac{1}{4}$ S 9 B.T.

John H. Markham Jr.
Work done for Stomar
Lumber Co.
Feb. 18, 1957.
C. S. File No.
42/248.

123
 $\frac{1}{4}$ corner to sec. 33 on So. boundry of Twp. (only)
Found iron pipe, $1\frac{1}{2}$ ins. dia., 10 ins. above ground, firmly set, unmarked,
from which:
A Douglas Fir, 26 ins. dia., bears N.21°30'W., 15.18 ft., mkd. $\frac{1}{4}$ S
33 RS 298 BT.
A Madrona, 10 ins. dia., bears N.78°30'E., 21.12 ft., mkd. $\frac{1}{4}$ S 33 RS
298 BT.
I mkd. iron pipe RS 298 as true position of $\frac{1}{4}$ cor. to Sec. 33.

Fredrick E. Warner
Survey for J. H. Baxter and Company.
March 20 - April 2, 1957.
C. S. File No. 42/257.

124
Sec. corner to secs. 33 and 34 only, on So. boundary of Twp.
Found remains of decayed post.
Set an iron pipe at corner point, 2 ins. dia., 3 ft. long, 28 ins. in ground,
from which:
A Douglas Fir, 30 ins. dia., bears N.32°E., 24.42 ft., chopped with
partial scribe marks.
A Douglas Fir, 26 ins. dia., bears N.60°30'W., 7.26 feet., chopped and old
scar visible.
(See later renewal - next page)

SEE CORNER NO. 132 + 144
#223

125
 $\frac{1}{4}$ corner to secs. 17 and 18.
Location of corner determined by proportional measurement.
At corner point set a $\frac{3}{4}$ inch x 24 inch iron rod 18 inches in ground.
From which:
A 7 inch Fir bears S.40W., 26.0 feet dist. mkd. $\frac{1}{4}$ S 18 B. T.
A 10 inch Fir bears S74W., 28.6 feet dist. mkd. $\frac{1}{4}$ S 18 B. T. *240*
A live Laurel Stump 30 inches in diam., 7 feet tall bears N.77E.,
53.0 feet dist., mkd. $\frac{1}{4}$ S 17 B. T. - This stump is on top of side
ridge and on cat road.

John H. Markham Jr.
May 7, 1957
C. S. File No.
42/270.

126
Section corner to secs. 4, 5, 8 & 9.
Point for corner determined from O. B. T.:
A 28 inch Fir, N.8°10'E., 17.0 feet - O.B.T.
A 14 inch W. Fir, S.30W., 17.2 feet - O.B.T., I rescribed S 8 B.T.
A 36 inch Fir, S.62°W., 25.0 feet - O.B.T.
At corner point found 4 x 4 wood post scribed & $\frac{3}{4}$ inch iron pipe. - *REN. #29*
I set a $2\frac{1}{2}$ inch x 44 inch iron pipe 24 inches in ground,
from which:
A 8 inch Cedar bears N.71°W., 23.0 feet dist. mkd. S 5 B.T.
A 15 inch Cedar bears S.21°30'W., 60.2 feet dist. mkd. S 8 B. T.
An 8 inch Yew wood bears S.3°W., 39.0 feet dist. mkd. S 9 B. T.
A 5 inch Alder bears S.21°E., 30.7 feet dist. mkd. S 9 B. T.
Creek bears South 97.0 feet.
Road bears West 123.0 feet.

John H. Markham Jr.
Work done for Stomar Lumber Co.
June 21, 1957.
C. S. File 42/272.

127
 $\frac{1}{4}$ corner to sec. 5, T29S, R4W., and sec. 32, T28S, R4W.
Found - $1\frac{1}{2}$ inch iron pipe at corner bent over by cat. replaced by brass
cap. The 14 inch Fir, S.2°10'W., in good condition and shows good face -
I do not open. The 10 inch Fir, S.70°36'W., down. Both B.T.s check for
bearing and distance. - *REN. #8*
Set an iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S- $\frac{32}{5}$ T28S, 4 W
T29S, 4 W
County Surveyers Office, 1957.
Also I find lower section of charred post as set by Cole same location as
 $1\frac{1}{2}$ inch iron pipe.
Balzed and scribed:
8 inch R. Fir, N.8°W., 23.2 feet mkd. T28S R4W $\frac{1}{4}$ S 32 CS BT.

James W. Byron, Deputy
County Surveyer
April - May, 1957.
C. S. File No. 47/180.

FILE OK
5/11/57 M 113-4