

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

169

$\frac{1}{4}$  Corner to Sections 3 and 2.  
Found - Orig. 24", now 32" Fir N.55°E. 11.2 ft., shows good bark scribing.  
No trace of Original N.W. Bearing Tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963  
 $\frac{1}{4}$  S 3/S 2 T29S R4W 229  
New BT's: 10" R.Fir bears N.65°W. 21.3 ft. scribed  $\frac{1}{4}$  S 3 CS BT.  
Rescribed - Now 32" Fir N.55°E. 12.1 ft. "BT" in wood.

170

$\frac{1}{4}$  Corner to Sections 13 and 24.  
Found - Brass Cap at Corner & both BT's. scribed in 1960, now down. REN.No.148  
New BT's: 16" R.Fir bears N.59°W. 27.5 ft.  
10" Cedar bears S.23°W. 49.2 ft. scribed  $\frac{1}{4}$  S24 CS BT.

171

$\frac{1}{4}$  Corner to Sections 23 and 24. FD. OK 1-95 BY R. BROWN M121-38  
Found -  $1\frac{1}{4}$ " I.P. at Corner & 30" R.Fir, bark scribed  $\frac{1}{4}$ S23 CS N.72°W. 8.0 ft.  
20" Fir Stump S.52°E.13.2 ft., shows good bark scribing - REN.#13 & 133  
New BT: 8" W.Fir bears S.66°E. 16.9 ft. scribed  $\frac{1}{4}$  S24 CS BT.

172

Section Corner to Sections 29 - 30 - 31 - 32.  
Found - All BT's. &  $\frac{3}{4}$ " I.Red at Corner. - N.W. BT. now down. - REN.# 93  
New BT: 12" R.Fir N.67°W. 22.9 ft. scribed S30 T29S R4W CS BT.

173

$\frac{1}{4}$  Corner to Sections 30 and 29.  
Found -  $\frac{3}{4}$ " I.R. at Cor. & Both BT's. as recorded: REN.#63  
2", now 5" R.Fir S.82°E. 4.2 ft., shows good scribing.  
12", now down Fir, S.68°W. 22.7 ft., shows scar.  
Set - Brass Cap alongside  $\frac{3}{4}$ " I.R. & Mkd: County Surveyor's Office, 1963  
 $\frac{1}{4}$  S30/S29 T29S R4W  
New BT: 12" Maple bears N.83°W. 5.3 ft. scribed  $\frac{1}{4}$  S30 CS BT.  
Note - Corner is 20" North of bottom of small E. W. draw.

174

Section Corner to Sections 19 - 20 - 29 - 30.  
Found - Spring with Shackle at Cor. & 1" I.P. alongside. REN.#58  
30", now 36" R.Fir N.32°E. 7.0 ft., not 5.8 ft., shows bark scribng.  
20", now 24" R.Fir S.55°E. 32.4 ft., shows bark scribing.  
18", now 18" Fir N.52°W., not N.45°W. 27.4 ft., shows bark scribing,  
S.W. Bearing Tree now stump.  
Fence Corner at N.E. Bearing Tree.  
New BT's: 10" R. Fir bears N.82°W. 7.2 ft. scribed S20 T29S R4W CS BT.  
6" R.Fir bears S.89°W. 28.5 ft. scribed S30 CS BT.  
14" Laurel bears S.12°E. 37.5 ft. scribed S29 T29S R4W CS BT.

175

$\frac{1}{4}$  Corner to Sections 10 and 15.  
Found - All new BT's. as recorded by Markham, except N.W. & 30" Fir to  
S.W. are now stumps. - REN.#119  
Do not find I.P. set at corner which now falls in old cat road.  
Set - Brass Cap at Cor. Mkd: County Surveyor's  $\frac{1}{4}$  S10 T29S R4W  
Office, 1963 S15  
New BT: 6" Fir bears S.49°W. 48.0 ft. scribed  $\frac{1}{4}$  S15 CS BT.

176

N. E. Corner D. L. C. No. 39.  
Found - 8", now 8" W.Oak N.1°E. 6.0 ft., shows good scribing. REN.#51  
Also find scribed post at Cor. - Orig. BT's. not found.  
Fence Corner Thus: \* \* \* ← D.L.C. Cor.  
Note - See Map File M 3 - 67 for BT. recorded by Boyer, 1938.  
Set - Brass Cap at Cor. Mkd: County Surveyor's NE. DLC 39 T29S R4W  
Office, 1963 S15 237  
New BT: 12" R.Fir bears S.24°W. 50.8 ft. scribed NE DLC 39 CS BT.

James W. Byron, Deputy County Surveyor  
Mike Darby and Wm. Stoffel  
April 1963  
C. S. File No. 52/126