

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

By B.B. Irving
Sept. 1953
See C. S.
File No.
45/234
Co. Rd.
No. 15.


Witness Corner to
Section Corner to Sections 7 - 8 - 17 - 18. 185
Set - 1" x 36" I.P. with Brass Cap Mkd: W.C. S 7-8-17-18, T29S R4W
Witness Corner set 12.0 feet West of true corner. *SEE #160 #84*
New BT's: 24" Fir N.89°30'W. 3.0 ft. *FD. OK 12/74 BY DOLAN M121-29*
24" Cedar N.27°E. 31.8 ft.
10" Cedar S.47°50'W. 36.8 ft.
14" Cedar N. 7° W. 93.2 ft.
(All trees blazed & scribed T29S R4W S7-8-17-18 W. C.)

Sec. Cor. to Secs. 4 & 5, T29-4W. & Sec.s 32 & 33, T28-4W. 186
Found - Angle Iron Fence Post at Corner. *-REN.*7-SEE M28-78A*
20" Fir, now 28", N.70°E. 52.8 ft. Good scar.
20" Fir N.82°E. 36.2 ft., dead, found scribing. *FILE OK 5/91 M113-14*
42" Fir S.72°E. 82.5 ft., cut down, shows scribing.
New BT's: 8" Laurel S.44°W. 47.7 ft. scribed T29S R4W S5 CS BT.
10" Laurel S.20°E. 31.9 ft. scribed S4 CS BT.
29" Fir N.42°W. 31.2 ft. scribed T28S R4W S32 CS BT.
Note - Corner 1 foot East of North-South Fence.

$\frac{1}{4}$ Corner to Section 4 and 3. *FD. OK 4/83 4-93 6-10-77 M118-13* 187
Found - $\frac{1}{2}$ " I.P. at Corner & both BT's. as recorded by Stewart. *-REN.*34*
12", now 20" Fir N.21°W. 23.5 ft., shows good scar.
S. W. BT., now down.
Set - Brass Cap alongside Cor. I.P. & Mkd: County Surveyor's Office, 1963
 $\frac{1}{4}$ S4/S3 T29S R4W
New BT: 22" R.Fir bears S.3°E. 28.0 ft. scribed $\frac{1}{4}$ S3 CS BT.

Section Corner to Sections 2 - 3 - 10 - 11. 188
Found - Orig. 18", now 24" Laurel Stump N.88°E. 28.4 ft. We open &
find good scribing "BT". *FD. OK 4/83 W. RUPPERT M 94-61*
Stump Hole that checks for Orig. N.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R4W $\frac{S3}{S10} | \frac{S2}{S11}$
Office, 1963
New BT's: 5" Cedar bears N.23°W. 16.6 ft. scribed S3 CS BT.
15" R.Fir bears N.83°E. 35.8 ft. scribed S2 T29S R4W CS BT.
7" R.Fir bears S.25°W. 22.0 ft. scribed S10 T29S R4W CS BT.
16" W.Fir bears S.28°E. 31.8 ft., previously scribed S11 T29S R4W
BT. We add "CS".
Note - This corner was renewed about 5 - 10 years ago but not of record.
We find scribed corner stake from which 16" W.Fir bears S.11°E.
27.2 ft. scribed S11 T29S R4W BT. & 12" Laurel bears S.48°W.
29.8 ft. scribed T29S R4W BT.

Section Corner to Sections 10 - 11 - 14 - 15. 189
Found - Old BT's: 15", now 21" Fir S.10°E. 13.2 ft. Cut into & fd. scrbing.
15" Fir, now Snag, N.26°W. 31.7 ft. Found good scar. *-REN.*45*
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R4W $\frac{S10}{S15} | \frac{S11}{S14}$
Office, 1963
New BT's: 9" Cedar N.74°E. 42.4 ft. scribed T29S R4W S11 CS BT.
13" Fir S.69°W. 34.2 ft. scribed T29S R4W S15 CS BT.
10" Cedar N.48°W. 46.0 ft. scribed S10 CS BT.

Section Corner to Sections 20 - 21 - 28 - 29. 190
Found - 2" I.P. at Fence Corner Thus: *-REN.*90*  2" I.P.
New BT's: 6" Laurel bears N.57°E. 7.0 ft. scribed S21 T29S R4W CS BT.
4" Laurel bears S.6°E. 29.6 ft. scribed S28 CS BT.
7" R.Fir bears S.73°W. 52.0 ft. scribed S29 T29S R4W CS BT.
No trees near to N.W.

Section Corner to Sections 4 - 5 - 8 - 9. 191
Found - 2 $\frac{1}{2}$ " I.Pipe at corner and all BT's. recorded by Markham,
corner No. 126. N.E. BT. now down. *-REN.*126*
New BT: 7" R.Fir bears N.56°E. 26.8 ft. scribed S4 CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
April 1963
C. S. File No. 52/126

*FD. B.C.
7/75 HAINES
SEE C.S. FILE*

*FD. C. 6/83
W. RUPPERT
M 94-61*