

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

192

$\frac{1}{4}$ Corner to Sections 5 - 4.

Found - 1" I.P. at corner & both BT's. as recorded by Frear,
SEE M 28-78A *SEE Corner No. 11.*

Orig. 12", now 30" W.Fir N.10°W., not N.20°W. 21.1 ft.,
shows scribe marks.

Orig. 40", now 44" R.Fir S.79°E., not S.89°E. 21.8 ft.,
shows bark scribing.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1963

$\frac{1}{4}$ S5/S4 T29S R4W

New BT: Rescribe, now 30" W.Fir N.10°W. 22.0 ft. $\frac{1}{4}$ S5 CS BT.

193

$\frac{1}{4}$ Corner to Section 17 and 16.

Found - I.P. & Post at corner & all BT's. as recorded by Markham; *Ren. #138.*

Laurel to S. E. is dead. We remark 12" R.Fir N.45°W. 10.8 FT.,
 $\frac{1}{4}$ S17 CS BT.

We destroy scribing on 6" Laurel S.54°W. 12.4 ft.

New BT: 8" R.Fir bears N.32°E. 6.3 feet scribed $\frac{1}{4}$ S16 CS BT.

194

$\frac{1}{4}$ Corner to Sections 26 and 25.

Found - 1 $\frac{1}{2}$ " I.P. at Corner. N.E. BT. is O. K.

14" Fir S.35°W. 11.3 ft., now stump. *REN. #20*

New BT: 9" Fir S.14°W. 14.9 ft. scribed $\frac{1}{4}$ S26 CS BT.

195

FOOK 1-95 BY R. BROWN M121-38
Section Corner to Sections 23 - 24 - 25 - 26.

Found - 1 $\frac{1}{4}$ " I.P. at Corner. N.W. and S.W. BT's. now down. *-REN. #12*

New BT: 38" Laurel N.19°W. 51.0 ft. scribed S23 T29S R4W CS BT.

196

$\frac{1}{4}$ Corner to Sections 26 and 35.

Found - Brass Cap at Corner. North BT., now stump. *-REN. #112*

40" Fir S.53°E. 19.8 ft, not S.33°E. 19.8 (snag).

New BT's: 18" Fir N.77°E. 93.5 ft. scribed $\frac{1}{4}$ S26 CS BT.

4" Fir S.32°W. 20.3 ft. scribed $\frac{1}{4}$ S36 CS BT.

197

Section Corner to Sections 25 - 26 - 35 - 36.

Found - 1 $\frac{1}{4}$ " I.P. at Cor. & 22" Cedar S.30°E. 20.1 ft., O.K.

30" Fir S.61°W. 36.0 ft., O.K. *REN. #19*

12" Fir N.8°W. 46.0 ft., stump. - 12" Fir N.27°E. 55.5 ft., stump.

New BT's: 9" Laurel S.77°W. 51.6 ft. scribed S35 T29S R4W CS BT.

9" R.Fir N.45°W. 11.6 ft. scribed S26 CS BT.

198

$\frac{1}{4}$ Corner to Sections 25 and 36.

Found - $\frac{3}{4}$ " I.P. at Corner & 15" Cedar S.58°E. 23.8 ft. (Snag).

10" Fir N.77°W. 21.8 ft., now stump. *REN. #18*

New BT's: 8" W.Fir S.72°E. 20.5 ft. scribed $\frac{1}{4}$ S36 CS BT.

9" Laurel N.10°E. 48.3 ft. scribed $\frac{1}{4}$ S25 CS BT.

199

South $\frac{1}{4}$ Corner to Section 35 only.

Found: 1" I.Pipe at corner & 14" Cedar N.30°W. 20.0 ft., now down.

12" Fir N.57°E. 61.0 ft., now stump. *-REN. #72*

New BT's: 20" Cedar N.42°W. 28.8 ft. scribed $\frac{1}{4}$ S35 CS BT.

7" W.Oak N.57°W. 32.4 ft. scribed $\frac{1}{4}$ S35 CS BT.

200

$\frac{1}{4}$ Corner to Sections 35 and 36.

Found - 1" I.P. & 16", now Cedar Snag S.59°W. 17.2 ft. *-REN. #86*

30" Sugar Pine S.23°W. 45.5 ft., now stump

12" Cedar N.35°E. 77.2 ft., stump.

New BT's: 7" Cedar S.44°E. 29.2 ft. scribed $\frac{1}{4}$ S36 CS BT.

12" Cedar N.12°W. 34.2 ft. scribed $\frac{1}{4}$ S35 CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Wm. Stoffel
April and May 1963
C. S. File No. 52/126