

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 4 W. R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE., 31801

James W. Byron, Deputy County Surveyor  
Mike Darby and Wm. Stoffel  
May and June 1963  
C. S. File No. 52/126

John H. Markham, Jr.  
for Hult Lbr. Co.  
April & June, 1964  
C. S. File No. 51/292  
Map File: M 28-25

Corner to Sections 4 and 3, T30-4W. 220  
Found - 1" I.P. at Corner. - 20" Cedar S.5°E. 31.0 ft., scribing visible.  
SW. Bearing Tree, now stump.  
New BT: 8" R.Fir bears S.56°W. 51.3 feet scribed S4 T30S R4W CS BT.

North  $\frac{1}{4}$  Corner Section 5, T30-4W. 221  
Found - 1" I.Pipe at Corner - 20" Laurel S.52°W. 73.0 ft., shows scribing.  
S. E. Bearing Tree, now stump.  
New BT: 11" W.Oak bears S.64°E. 88.0 ft. scribed  $\frac{1}{4}$  S5 CS BT.

North  $\frac{1}{4}$  Corner to Section 4, T30-4W. 222  
Found - 1 $\frac{1}{4}$ " I.Pipe at corner and 8" Laurel S.3°E. 18.5 ft. We  
rescribe this Bearing Tree  $\frac{1}{4}$  S4 CS BT.  
6" Fir S.26°W. 23.1 ft., shows scribing.

Corner to Sections 33 and 34 only. <sup>FOOD BY G LANS 1117-1</sup> 223  
Found - 2" I.P. at corner - 16" Laurel N.42°E. 46.5 ft., down, shows scribing.  
20" Fir N.72°W. 36.2 ft., shows scribing. - Ren. = 132 + 12A - 144  
New BT: 9" Laurel bears N.48°E. 41.8 ft. scribed S34 T29S R4W CS BT.

Section Corner to Sections 22 - 23 - 26 - 27. 224  
Found - Brass Cap at Corner & all bearing trees except N. W. BT. - Ren. = 107  
New BT; 20" R.Fir bears N.89°W. 65.9 ft. scribed S22 T29S R4W CS BT. RM 1-8

$\frac{1}{4}$  Corner to Sections 16 & 21. 225  
Set - 1" x 36" Iron Pipe at mid-point.  
New BTS: 9" W. Oak bears N. 4° 30' W. 149.7 ft. Dist. Mkd:  $\frac{1}{4}$ S 16 BT.  
14" W. Oak bears N 20° W. 175.8 ft. Dist. Mkd  $\frac{1}{4}$ S XX BT.  
A 3-way fence corner bears N. 34° 30' W. 213.2 ft. dist.  
corner lies in a level cow pasture.

Section Corner to Sections 15, 16, 21 & 22. 226  
(set by double proportional measurement)  
Found - 40" laurel and set 1" x 36" I.P. in hollow butt.  
New BTs: 12" Cedar bears S 57° W 26.3 ft. dist. Mkd: S 21 BT.  
14" Fir bears N. 44° 30' W. 27.0 ft. dist. Mkd: S 16 BT.  
11" Fir bears N. 8° 30' E. 22.4 ft dist. Mkd: S 15 BT.  
13" Fir bears S 60° E. 24.0' dist. Mkd: S 22 BT.  
I mkd. 40" Laurel at corner point S 21 S 22 S 15 S 16 T 29 S  
R 4 W. on SE face.

$\frac{1}{4}$  Corner to Sections 15 & 16. 227  
(set by proportional measurement)  
Set - 1" x 30" truck axle with flange up.  
New BTs: 15" Fir bears N. 38° E 7.9 ft dist. Mkd:  $\frac{1}{4}$  S 15 BT.  
9" Fir bears S 82° E 8.7 ft. dist. Mkd:  $\frac{1}{4}$  S 15 BT.  
16" Cedar bears S. 26° W 42.9 ft dist. Mkd:  $\frac{1}{4}$  S 16 BT.  
Road bears West 180.0 ft. dist.

Section Corner to Sections 9, 10, 15 & 16. 228  
(set by double proportional measurement)  
Set - 1" x 30" I.P.  
New BTs: 12" Cedar bears S 35°E. 32.1 ft. dist. Mkd: S 15 BT  
15" Fir bears S 20°W. 53.0 ft. dist. Mkd: S 16 BT.  
36" Fir bears N. 10°W 40.5 ft. dist. Mkd: S 9 XX BT.  
48" Laurel bears N. 40 ° E 38.2 ft. dist. Mkd: S 10 T29 SR W BT.  
Note: All bears to BTs. were estimated since compass was lost.

RE-OPENED CORNER NO. # 265  
RE-OPENED CORNER NO. # 266