

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S.T.S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued) 1/4 Cor. Sec. 22/23.
New BT: 14" Apple S.69°E. 41.3 ft., scribed "1/4 S23 CS BT".
N.E. Corner of Barn S.58°W. 81.8 feet.
S.W. Cor. House(Porch) N. 3° E. 87.3 feet.

10/19/71 *JAN. 1972*

242

Closing Corner to Sections 3 and 2, T30-4W.
Found - 12" Cedar BT mkd. by J. Markham, S.8°W. 66.5 ft.,
shows good scar. (See Ren. #92, T30-4)
At Corner Point Brass Cap Mkd: (No Record)
County Surveyor's T29S R4W
Office

C.S.
Sole
49/67
John M.
Powell
&
J. Heritage
2/17/72
C.S.File

1956 CC S3 | S2 T30S R4W
Mkd. New BT: 8" W.Oak S.55°E. 64.5 ft.mkd:"T30S R4W S2
CC CS BT"

No.
53/26

Note: This corner lies S.86°W. 168.0' of Sec. Cor.S.35
and, as noted, corner lies on W. edge of upper road.
No trace of Orig. BT's. or I.P. set by Markham.

243

1/4 Corner Sections 5 and 8.
Found - 10" Cedar, now 16", N.36°E., 155.5 ft. shows good scar. Ren. #77
Brass Cap mkd. County Surveyors Office, 1/4 Sec. 5, Sec. 8.
New BT: 6" Maple, S.51°W., 28.3 ft. scribed 1/4 S8 CS BT.
Bearing Object: Copco Pole #C11715, N.58°E., 50.0 ft.
Location tag on E-W fence line N.11°E., 37.2 ft.

10/6/72

JAN. 1973

John Powell
J. Heritage
C.S.File 49/67

Center 1/4 Corner Section 29.

244

Set 8-5/8" Iron Rod
5.0 ft/ steel fence post bears North 2.0 feet.
14" Cedar bears S. 1 1/2°E. 16.8 ft. scribed:
C1/4 S29 BT.
April, 1973

Garrett, Don
For: Vern
Lively
Map File
M 48 - 33

Center 1/4 Cor. of Sec. 8

245

Found - 1/2" I.R set at point of intersection of lines
from opposite 1/4 corners of sec. 8. See Map file
M 51 - 68.

Set - Brass cap mkd.

COUNTY SURVEYORS T 29 S R 4 W
OFFICE C 1/4 S 8
1974

Gary Langlitz
P. Earle
C.S. 56/51
5/3/74

and deposit I.R. alongside brass cap.

New BT's - 7" Fir, bears S.8°E., 29.6 ft. scribed "T29S R4W C1/4
S8 CS BT"
6" Fir, bears S.87°E., 18.4 ft. scribed "C 1/4
S8 CS BT"

This corner is located on the edge of a road cutbank, on the
easterly side of a dirt easement road and directly beneath
a high voltage electrical transmission line.

Declination: 20°E.

5/3/74

JAN 75

246

Center 1/4 corner for Sec. 19

Set - 5/8" Iron rod.

247

NE Cor. D.L.C. #42

Set - 5/8" Iron rod.

William J. Ruppert
For: Allen, Coffey,
Phillips, Dame
and Wilson
May 1976
M 60 - 35

248

Center 1/4 Corner for Sec. 4

Set - Iron Pipe
BT's - 18" Fir, N.52°E., 20.0 ft.
24" Laurel bears N.30°W., 58.8 ft.

270

2/27/22

G. G. Stewart
For: Dr. Banks
Feb. 27, 1922
M 2 - 4
Vol. 3 Pg. 115

JAN 78