

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 29 S.      T. S.      R. 4 W.      R.W.W.M.

MOORE-CHAPMAN CO., EUGENE, ORE. 21881

(Continued)

252

New BTs.- 8" cedar BT, I scribed "T29S R4W S2 BT" bears  
S.27°E., 52.0-ft. 12/81

253

1/4 Corner common to Sec. 2, and Sec.35 Of T.28-4.  
BTs. - 48" cedar stump w/remains of old face, bears Orig.  
S.12°W., 27.7-ft.  
Root hole of Madrona bears N.12°W., 27.7-ft.  
(young madrona about it), (Rec.N.22°W.)  
U.S.G.L.O. Corner tag faces into corner, signed by H.Langdon &  
H. Carlson, others, Oct.28, 1945.  
U.S.G.L.O. Witness tag faces corner, signed by Burt Holt  
(circa 1940)  
Cruiser blaze "K" faces corner (Al Keatley, Stomar Lumber Co.)  
(circa 1955)

New BTs.- 10" D. fir BT I scribed "1/4 S2 BT" bears S.49°E., 12.0-ft.  
10" D. fir BT I scribed "1/4 S35 BT" bears N.45°E., 11.2-ft.  
12/81

254

1/4 Corner common to Secs. 2, & 11.  
Found - Brass Cap, properly marked, from which: Ren.#163.  
BTs. - 32" D. fir BT, snag w/scribes visible bears S.48-3/4°W.,  
24.9-ft. (Rec. 23.9-ft.).  
36" D. fir w/healed over face bears S.14°W., 40.3-ft. Orig.  
40" D. fir BT, stump w/bark scribes vis. bears N.25-1/2°E., 19.8ft.  
New BT - 16" cedar BT, I scribed "1/4 S2 BT", bears N.32°W., 49.0-ft.  
12/81

255

Center 1/4 Corner for Sec. 2.  
Set - 5/8" x 34" I.R. in pavement with "Shaner Eng" Alum.Cap  
BTs. - 14" cedar BT, I scribed "C1/4 S2 BT" bears N.21°E., 52.3-ft.  
26" cedar BT, I scribed "C1/4 S2 BT" bears N.69°W., 74.8-ft.  
16" cedar BT, I scribed "C1/4 S2 BT" bears S.76-1/2°E., 44.0-ft.  
12/81

256

Section corner for Secs. 5, 6, 7 and 8  
Found - 1 1/2" I.P. with 1963 County Brass cap, properly marked.  
Cap protrudes 11". Ren. #182  
15" fir now 18" stump with heavily pitched over face bears  
S.33°W., 15.8 ft. (Rec. 16.9 ft.)  
14" fir now 14" snag 20 ft. tall with heavily pitched over  
face bears N.21°W., 21.4 ft. (rec. N.18°W., 22.4 ft.)  
12" fir now 12" rotted stump with scribed "BT" visible on unhealed  
face bears N.6 1/2°E., 13.2 ft. (Rec. N.8°E., 12.8 ft.)  
New BT's- 3" madrone bark scribed "S6 CS BT" bears N.83°W., 14.5 ft.  
4" madrone bark scribed "S5 CS BT" bears N.23°E., 10.4 ft.  
4" madrone scribed "S8 CS BT" in double blaze bears S.52°E.,  
6.1 ft.  
4" madrone bark scribed "S7 CS BT" bears S.36°W., 25.4 ft.  
Sketch in C.S. file.

257

1/4 Corner for Secs. 6 and 7  
Found - 1/2" I.P set flush with the Ren. #141 ground along the south edge of 1 1/2"  
I.P. with 1963 properly mkd. brass cap. Ren. #183. Cap is  
firmly set and protrudes approx. 10" out of ground.  
Orig. 10" fir now 26" stump bears S.60°W., 17.2 ft. (rec. 16.5 ft.)  
I find butt section of tree alongside stump with scribed "1/4S"  
visible on an opened face. (this piece is rotting badly.)  
20" now 27" madrone with scribed "1/4S / ^" (83 BT" visible in an  
unhealed blaze, bears S.40°E., 19.6 ft. (rec. dist. of 17.8 ft.  
fits well to face.) Ren. #141  
12" now 14" madrone now a windfall bears N.5°E., 21.0 ft. to root  
hole. Scribed 1/4 S6 368 visible in unhealed blaze.  
New BT's- 13" fir scribed "1/4 S7 CS BT" in double blaze bears S.7°W., 38.6 ft  
16" fir scribed "1/4 S6 CS BT" in double blaze bears N.83 1/2°E.,  
21.5 ft.  
14" fir scribed "1/4 S6 CS BT" in double blaze bears N.3°E., 8.4 ft

4/5/82

Bruce Shaner  
For: Longview Fibre Co.  
Oct., 1981 thru Jan., 1982  
RM 3-54

Gregory Quibell, Deputy  
Douglas County Surveyors Office  
Witnesses: John Powell - Karen Reed  
April 4, 1982  
C.S. 61/30