

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 4 W R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(Contd. From Last Page)

273

New Accessories -

8" dia. D.Fir, double blazed and scribed "T29S R4W S27 CS BT",  
bears N.89°W., 7.2'.

6" dia. D.Fir, double blazed and scribed "T29S R4W S35 CS BT",  
bears S.89°E., 30.7'.

SW DLC COR #37 - Condition report only

see ren. #149

Mon. Fd.- 2½" Dia. Brass cap on 1½" O.D. Iron pipe protruding 18" above  
ground. Base is surrounded by a 2½" dia. mound of stone.

Bt's Fd.- 18" now 56" dia. O.Ash with a previously opened blaze, illegible  
scribing visible, bears N.5°E., 82.5'. (agrees w/ rec.)

14" now 22" dia. O.Ash with a fully healed double blaze, bears  
N.59°E., 19.8' (agrees w/ rec.).

9" now 16" dia., O.Ash with a partially healed double blaze,  
illegible scribing visible bears, N.38°W., 26.3' (agrees w/  
rec.)

2" I.P. 6" below ground, bears S.87 3/4°E., 132' (rec. east  
132').

corner lies approx 70' north of S.Myrtle Co. Rd. in a N-S fence line

274