

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

Frank Cain Dep.
Recorded by
F. C. Frear
Oct. 14, 1920.

J. W. Cole

G. G. Stewart Deputy
Nov. 4, 1921.
Witnesses
George Nixon
A. W. Yokum

H. L. Eppstein
Oct. 30, 1921
H. L. McHenry
N. E. Richardson

G. G. Stewart Dep.
Nov. 28, 1921
H. M. Oatman
Jack Black
Frank Drake
Jim Dunniven

By B.B. Irving,
Deputy
Map File
M 1 - 61

F.B. 107 R. 36

F.B. 35 R. 39

1 CORNER OF SECTIONS 5 and 8. 22
Re-established from which
A White Oak 10" dia. bears S. 80° 10' W., 32 1/2 lks. 122
A Black Oak 24" dia. bears S. 65° 15' W., 136 lks.

1 CORNER BETWEEN SECTIONS 5 and 6. 23
Set post from which
A White Oak 30" dia. bears N. 87° 15' W., 105 lks. C.S.B.T.
A White Oak 22" dia. bears N. 23 1/2° E., 103 lks. C.S.B.T.

N.E. CORNER OF THE HADLEY D.L.C. NO. 37. 24
I renewed this corner from the original B.T. which
had been chopped open then over grown again causing scribe marks to rot off. I ran N. 12° 30' W., 89.7 ft. and set an Oak Post 4 x 4 x 40 also a 2" x 18" brass tube and erected a mound of rock from which I marked a new tree
An Oak 30" dia. bears S. 80° E., 73.7 ft. Per P.B. 50 Pg. 39

1 CORNER BETWEEN SECTION 2 and 11. 25
I find 24" Black Oak tree, and old blaze was evident and tree had been opened about 15 years ago and heart rotted out. Find faint mark of scribe in overgrown bark and consider this original B.T. Under tree missing. I established this quarter corner by a 4" square white oak Post and set new B.T.
A 12" Fir N. 76° W., 13 ft.
A 10" Fir S. 18° E., 22 ft.

1 CORNER BETWEEN SECTION 17 and 14. 26
Corner gone. I find one B.T. a 24" Black Oak. Set 4" Square White Oak Post for corner 116.0 ft. N. 30° E. from B.T.
A Maple 10" dia. bears N. 45° E., 84.3 ft. for new B.T. 114

SECTION CORNER BETWEEN 1, 2, 11 and 12. 27
I find three B.T.s the fourth a Black Oak had fallen. Set a 4" square White Oak post for corner and mark a new B.T.
A 18" Fir N. 90° W., 28 lks. Oak
NOT FOUND 8/12/70 W. PENNEY - C.S. 54/81 2ND SEARCH 4/26/72 V.R.T. (NO ADJ. EVIDENCE)

SET CORNER TO SECTIONS 11, 10, 14 and 15. 28
I renewed this corner from old B.T.s. I found two trees standing and two trees down. I set a 4" x 4" x 30" Yew Wood and marked new trees as follows
A 15" Fir bears S. 14° W., 31 lks.
A 15" Black Oak bears S. 62° 30' W., 50 lks. SEE # 8
A 12" Fir bears N. 80° E., 27 lks.
A 8" Fir bears S. 61° 30' E., 20 lks. 113

1 CORNER BETWEEN SECTION 21 and 28. 29
Renewed from one old B.T. Set a 1" Iron Pipe for corner. Marked new witness trees
Black Oak 24" dia. N. 41° W., 34 1/2 lks. # 5
White Oak 8" dia. S. 38° E., 112 lks. SEE CORNER NO. 127

SECTION CORNER 20, 21, 28 and 29. 30
Corner consisted of pile of rocks and stake. Found one B.T. standing and one fallen. I renew from these B.T.s. Set a one inch Iron Pipe for corner
A 12" Fir S. 82 1/2° W., 7.0 ft.
A 18" Fir S. 15° W., 15.8 ft.
A 12" Fir S. 63° E., 17.0 ft.
A 12" Fir N. 35 1/2° E., 34.5 ft. SEE CORNER NO. 126

Center 1/4 Corner Section 31 30-A
1" x 24" G. I. Pipe in mound of Rock.
Mkd. 8" White Oak S. 37° 46' W., 28 lks., cent. of S 31 CS BT. # 195.
April - May 1929