

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

✓ SECTION CORNER BETWEEN 16, 17, 20 and 21.
Found one B.T. others down. I reset by putting in
 $\frac{3}{4}$ " Iron Pipe with pile of rocks around it. Blazed new
B.T.s

A 30" Pine S. $3^{\circ}30'$ W., 100.0 ft.
A 36" Pine N. $5^{\circ}30'$ W., 252.0 ft.
A 30" Pine N. $45^{\circ}00'$ E., 55.4 ft. Old B.T.
Mound of rocks S. 49° E., 36 ft.

31

G. G. Stewart
Witnesses
Frank Drake
Jim Dunning
Jack Black
Nov. 26, 1921.

✓ SECTION CORNER FOR 15, 16, 21 and 22.
Found one B.T. Others down or gone. I set $\frac{3}{4}$ " Iron pipe
for corner. Marked new B.T.

A 6" Fir bears N. 93° E., 30.0 ft.
A 12" Fir bears S. 26° E., 31.0 ft.
A 12" Pine bears S. 5° W., 49.5 ft.
No other trees available.

32

G. G. Stewart
Nov. 28, 1921
Witnesses
Frank Drake
Jesse Davenport
S. Crear

✓ CORNER BETWEEN 14, 15, 22 and 23.
Set Iron Pipe from Original B.T. Marked

A 14" Alder S. 30° E., 53.0 ft. O.B.T.
A 6" White Oak S. $68\frac{1}{2}^{\circ}$ W., 58.8 ft.
A 12" White Oak N. 3° E., 117.0 ft.
No other trees available.

33

G. G. Stewart
Apr. 4, 1922
Witnesses
B. Hargis
S. Crear

✓ CORNER BETWEEN 3 and 4 (33 and 34 T. 28 S.)
Renewed from Original B.T. Set Iron Pipe and marked

A 16" Fir S. $28\frac{1}{2}^{\circ}$ E., 20.0 ft.
A 16" Fir S. $63\frac{1}{2}^{\circ}$ W., 6.2 ft.
A 16" Fir N. 38° E., 6.7 ft.
A 16" Fir N. 40° W., 41.1 ft.

34

G. G. Stewart
Witnesses
S. D. Whitsett
W. S. Crear
June 20, 1922.
Vol. 3 p. 123
CS 7/20

✓ $\frac{1}{2}$ CORNER NORTH SIDE OF SECTION 3.
Renewed from one O.B.T. Drove Iron Pipe and remarked
O.B.T. and marked

A 18" White Oak S. 36° W., 446.4 ft.

35

✓ CORNER OF 7, 8, 17 and 18.
Found B.T. to N.W. also S.W. and N.E. scribe marks on
one to N.W. Set 4" x 4" x 4" Oak Stake and marked new B.T.s
as follows

Black Oak 30" dia. N. $75^{\circ}30'$ W., 243 lks.
Black Oak 20" dia. S. $19^{\circ}00'$ E., 169 lks.
Black Oak 20" dia. N. $48^{\circ}00'$ E., 283 lks.
Maple 8" dia. S. $33^{\circ}00'$ W., 248 lks.
Large Rock bears North 49 lks.

36

H. L. Eppstein
Geo. S. Crear
Geo. Flindley
Mar. 27, 1926.

✓ $\frac{1}{2}$ CORNER BETWEEN 7 and 8.
Set corner from 30" Black Oak (old B.T.) which bears S.E.
Set 3" x 3" x 3" Oak stake and marked one new B.T. which
is as follows

A 15" White Oak N. 60° W., 27.4 ft.

37

✓ EXTERIOR "L" CORNER OF D.L.C. 46.
Set corner from old B.T. Scribe marks plain. Set 4" x 4" x 4"
stake. Marked new B.T.

A 30" Black Oak N. 65° E., 151.8 ft.
A 12" White Oak S. $70\frac{1}{2}^{\circ}$ E., 85.4 ft.

38

H. L. Eppstein
Witnesses
W. S. Crear
George Spam
Dec. 18, 1925.

✓ S.E. CORNER OF D.L.C. 46.
Set this corner by running from N.E. and S.W. corners of
claim to S.E. corner of claim. The distance and bearing
at corner found two trees which checks out as old B.T.s but
burnt out so set 4" x 4" x 4" stake and marked new B.T.

Fir 30" dia. S. $10^{\circ}15'$ W., 21.0 ft.

39

H. L. Eppstein
Witnesses
W. C. Banks
Geo. Spam
Dec. 18, 1925

✓ S.W. CORNER OF D.L.C. 46.
Set post from two old B.T.s. Scribe marks plain on one
(namely N. 86° E., 97 lks.). Marked new B.T.

A 12" White Oak N. 3° W., 70.8 ft.
A 10" White Oak S. $89\frac{1}{2}^{\circ}$ E., 41.8 ft.

40

57