

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

March 13, 1938.
H. L. Eppstein Co. Sur
Wit.
W.S. Crear

C.S. 6/53

C.S. 6/53

SEE Cor #83
N.W. CORNER OF CLAIM 50. 41
Set corner from old B.T. N.2°W., 43 lks. Scribe marks for B.T. plain. Set 1 1/2" x 20" Iron Pipe marked new B.T.
A 15" Fir N.19°E., 22 lks. 83
A 12" Fir N.57°W., 16 lks.

SEE CORNER NO. 82
1/4 CORNER BETWEEN SECTION 24 and 25. 42
Set corner from old B.T. a 12" Black Oak N.75°E., 23 lks. Scribe marks plan for B.T. Other tree gone. Set 3" x 3" x 3' Cedar Post and marked new B.T.s
12" Cedar N.5°W., 87 lks.
10" Fir N.74°E., 63 lks.

1/4 CORNER BETWEEN SECTIONS 30 and 31. 43
Renewed by setting a serpentine Rock 6" x 8' with X chisled on top and 1/4 S. on south face. Position identified from one Original B.T. a 40" Fir S.15°E., 185 lks. Set new B.T.s
Fir 8" dia. S.28°50'W., 11 lks. marked 1/4 S.31 C.S.B.T.
Fir 8" dia. N. 2°20'E., 54 lks. marked 1/4 S.30 C.S.B.T. 147

SECTION CORNER BETWEEN 25, 30, 36 and 31. (R.6:5) 44
Location identified from C.S. post and one B.T. set by Deputy County Surveyor Roberts some 20 years ago but not recorded. Renewed by setting a 4" Yewwood post with 3" x 36" Galvanized Iron Pipe driven along side. New B.T.s
Fir 36" dia. S.73 1/2°E., 82 lks. blazed and scribed T.29S. R.5 W., S.31 C.S.B.T.
Fir 28" dia. S.24°W., 129 lks. blazed and scribed T. 29 S., R. 6 W., S.36 C.S.B.T.
Fir 40" dia. N.13 1/2°E., 118 lks. blazed and scribed T. 29 S., R. 5 W., S.30 C.S.B.T. 148
Fir 36" dia. N.67 1/2°W., 64 lks. blazed and scribed T. 29 S., R. 6 W., S.25 C.S.B.T.

1/4 CORNER WEST SIDE OF SECTION 31. 45
Located by proportional distances between the S.W. and N.W. corner of section 31. Drove a Gal. Iron Pipe for corner from which
A White Oak 10" dia. bears S.75°W., 29 lks. blazed and scribed S.31 C.S.B.T. #193
A White Oak 8" dia. bears N.62°W., 20 lks. Blazed and scribed 1/4 S.36 C.S.B.T.

1/4 CORNER BETWEEN SECTION 31 and 32. 46
Conglomerate rock marked with X set in original B.T.s which I remark
White Oak 36" dia. N.60°W., 69 lks. 1/4 S.31 C.S.B.T. #131
White Oak 30" dia. S.15°E., 23 lks. 1/4 S.32 C.S.B.T.

CORNER TO SECTIONS 36 and 31, and 1 and 6, T.29 and 30 S. R. 5 and 6 W. 47
Location identified by an East and West blazed line and distance from Rocky ridge S.and N. called for in original notes. Drove 3" x 36" Gal. Iron Pipe and set in a mound of rock from which
A Pine 20" dia. bears S.37 1/2°E., 96 lks. blazed and scribed T. 29 S., R. 5 W., S.36 C.S.B.T. #194
A Pine 16" dia. bears N.63°E., 52 lks. blazed and scribed T. 29 S., R. 5 W., S.31 C.S.B.T.
A Pine 16" dia. bears S.32°W., 123 lks. blazed and scribed T. 30 S., R. 6 W., S.1 C.S.B.T.
A Pine 20" dia. bears N.65°W., 82 lks. blazed and scribed T. 29 S., R. 6 W., S.36 C.S.B.T.

REESTABLISHMENT OF NE COR. OF DLC#45, T. 29, R. 5 48
After making a thorough search for evidence of the original corner and bearing tree and finding no evidence of either I set a 1 1/2"x36" steel axle with a 6" hub flush with the ground at the point of intersection for the NE cor. of DLC #45 from which I marked a W. Oak 14" N 31°53' E. a distance of 18.3 ft. scribed NE, DLC #45 377. FD. OK 6/78 - W. RUPPERT PER 1170-21

Ben B. Irving
August 21, 1929
Witnesses
H. C. Baird
Weaver

Geo. C. Baker
Witnesses
R. B. Asbury
C. A. Earnhart
E. A. DuBell
Feb. 15, 1947
C.S. 40/5

ALSO FD. DEPT. ST. M. 1970
C.S. 1970

FD. AXLE #42
J. MERRIN MILES-20