

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 5 R. W. W. M.

S.W. CORNER OF HENRY JONES D.L.C. # 48. **CORNER NO. 134** 49  
Location identified by original B.T. and Cedar post properly marked as recorded by Briggs 1890, B.T. hollow and figures rotted off. Set for corner pointed sandstone 6" x 8" butt 16" long X chisled on top and 48 on N.E. face. Set 12" in ground. Blazed and scribed  
Fir 14" dia. S. 121° W., 35.9 ft. Cl. 48 CS BT  
B. Oak 36" dia. N. 29 1/2° W., 103.8 ft. Cl. 48 CS B.T.

N.W. CORNER OF D.L.C. 41. 50  
A Black Oak Tree was corner. This tree showed ax marks in hole in tree. J. T. Black said he had seen scribe marks on tree. Set post at foot of tree for corner and marked  
A 8" Fir S. 88° E., 11 lks. 3/162-Drove 3/4" I.R. AT COR. TREE. J.W.B.

1/4 CORNER BETWEEN SECTIONS 29 and 28. **SEE ALSO # 7** 51  
The two old down B.T.s showed ax marks but no scribe marks. J. T. Black said he had seen scribe marks on tree also stake there. Set post and piled up rock. Marked  
Fir 12" dia. N. 23° W., 10 lks.  
Fir 10" dia. N. 69° E., 45 lks.

CORNER BETWEEN 29, 28, 32 and 33. **SEE ALSO # 6** 52  
Set for corner angle Iron 2 ft. long flush with ground from old Oak B.T. Marked  
Prune 8" dia. N. 62° E., 143 lks.  
Prune 5" dia. S. 21° W., 66 lks.  
Maple 30" dia. S. 45° W., 229 lks.  
B. Oak 12" dia. N. 44° W., 398 lks.

N.W. CORNER OF J. H. BEAN D.L.C. 38 **CORNER NO. 182** 53  
Set White Oak post 4 inches square 31 feet long marked C. 38 C.S.  
White Oak 18" dia. S. 40 1/2° E., 50 lks. marked C. 38 C.S. B.T.

N.N.W. CORNER OF HUGH CARLSON D.L.C. # 50. **CORNER NO. 99** 54  
Set Cedar post and marked  
Black Oak 12" dia. S. 85° E., 108 lks.

1/4 CORNER BETWEEN 22 and 27. **SEE CORNER NO. 3** 55  
Renewed by running between Section 22 and 27 remarked two new trees  
An Ash 24" dia. N. 24° 30' E., 32.6 ft.  
An Alder 12" dia. S. 42° W., 11.6 ft.

SEC. COR. BETWEEN 21-22-28-and 27. (reference ties) 56  
Set an I.P. S 70° 04' W 90.81 ft. REF. TO. COL. # 72 A  
Set an I. P. S 68° 55' E 63.97 ft. # 4

S. W. CORNER D. L. C. 46, T. 29 S., R. 5 W. 57  
Found one B. T. and stump of the other set by H. L. Eppstein-1925-post gone <sup>40</sup> Set 1"x48" G. I. P. with brass cap marked County Surveyor S. W., D. L. C. 46  
Marked one new tree A. W. Oak 9" N. 18° E., 42.0 ft.  
March 11, 1947 C.S. 38/171

1/4 SECTION CORNER, SECTION 22 - 23 (determined by O.B.T.) 58  
A 22" B.O. bears S 55° W, 17.2 ft.  
A 15" B.O. bears S 35° E, 9.9 ft.  
At corner point set 1" x 30" I.P. from which  
A La. 9" in diam. bears N 45° E, 32.4 ft. dist. mkd. 1/4 S, Sec. 29  
A W.O. 20" in diam. bears S 45° W, 71.5 ft. dist. mkd. 1/4 S, Sec. 22 2880, B.T.

There is a fence running N-S-E from corner. **CORNER NO. 161**

Jno. H. Markham Jr.  
Wit: J.A. Cross  
G.S. Ausmus

Mar. 7, 1952

C.S. FILE NO. 40/386

G. C. Baker-Surv.  
R. D. Ashbury  
F. P. Fuchs  
Witnesses  
6-20-46  
C.S. 38/111

Ben B. Irving, Surveyor  
Witnesses  
NE. Richardson  
Milo Godfrey  
Les Kershner  
3-11-47

1929  
see Vol. 3, R. 293