

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97100

Ben B. Irving
County Surveyor

George Wenderoth
County Surveyor
Witness
Carl Felker
April 7, 1949
5-19-48

John H. Markham, Jr.
Witness:
Geo. Vaughn
E. H. Stonepord
7-22, 26, -1950
C.S. 40/259

John H. Markham, Jr.
Witness: Geo. Vaughn
August 1, 1950
C.S. 40/263

John H. Markham, Jr.
Witness - Wm. Markham
March 29, 1951
C.S. 40/259

V. 1 R. 218

V. C.S. 43/17

S.E. Corner C1 39 Set Post
Old B.T. gone Marked new B.T.
Black Oak 6" N 60° E 75 links.
May 30 1892 Briggs

59

1/4 COR. BET. SECS. 33-34

60

Found 1 1/4" water pipe (1 1/2" outside diam.) at a fence corner.
Shown this as 1/4 sec. cor. bet. Secs. 33-34, T 29 S, R 5 W, WM. by
Ray Norton of Myrtle Creek.
Deputy Co. Surv., Frear, Nov. 15-16, 1917, records 1/4 cor. ~~129~~ sec. 33-34, T 29 S, R 5 W, WM., as a 2" G. iron pipe and chilled plow share. Upon digging found a chilled plow share lying down 4" underground. Reset plowshare so that point was up and even with the ground, fence intersect about 2ft. North.
ALSO SEE VOL 3 PG 21
LEM

S W COR. DLC #45

61

Found 1 1/2 inch i. p. also stump of Old BT, 16" B. Oak N 27° 30' E 6.9 ft.
Mark new B.T. 18" W. Oak N 76° 04' W 3.6 ft.
10" Madrone S 9° 56' E 18.0 ft.

FO. OK 4/14 - G. BAUGHMAN 11 55-16 FO. OK 6/92 L. FRIAR 1992-0043

SEC. COR. 3-4-9-10

62

Renewed by double proportionate measurement.
At corner point set 3/4" x 30" I.P. 20" in ground, from which
A Cedar 16" diam. bears S 37° E 42.0 ft. dist. marked
S 10, 2880, B.T.
A Pine 11" diam. bears N 12° E 58.0 ft. dist. marked
S 3, 2880 B.T.
A Fir 10" diam. bears N 7° W 51.5 ft. dist. marked
S 4, 2880, B.T.
A Fir 9" diam. bears S 42° W 21.5 ft. dist. marked
S 9, 2880, B.T.

1/4 SEC. COR. 4 & 9

63

Determined by one proportionate measurement.
At corner point set 3/4" x 30" I.P. 20" in ground, from which
An Alder 13" diam. bears S 86° W 25.4 ft. dist. marked
S 9, T 29 S, R 5 W, 2880, B.T.
A log house bears N 57° E, 270.5 ft. dist. to door

SEC. COR. 2-3-10-11

64

Determined from remains of original B.T.
B. Oak 12" diam. bears N 87 1/2° E 24.0 ft. dist., I rescribe S 3
W. Oak 12" diam bears S 20° E 22 ft. dist., I remark this
original B.T., S 11, 2880, B.T.
At corner point fd. 5"x5"x5" stone, from which
A W. Oak 12" diam. bears S 3° W 345 ft. dist. marked S 10,
2880, B.T.

1/4 SEC. COR. 3 and 4

65

Determined by proportional distance.
At corner point set 3/4" x 30" I.P. 16" in ground, from which:
A Cedar 9" diam. bears S 85° E, 60.0 ft. dist. marked
S 3, 2880, B.T.
A Fir 7" diam. bears N 30° W, 8.5 ft. dist. marked
S 4, 2880 B. T.

S.E. SEC. COR., SEC. 34

66

Determined by O. B. T. - A Laurel 20 ins. diam. bears N 45° E,
103.0 ft. dist. O. B. T.
At corner point set 1" x 24" iron pipe, from which
A Fir 3 ins. diam. bears N 64° E, 17.0 ft. dist. marked S 35, B. T.
A Laurel 10 ins. diam. bears N 24° W, 19.0 ft. dist. marked S 34,
T 29 S, R 5 W, B. T.