

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

S.W. COR. SEC. 34

Set by 2 O.B.T.s

A dead B. O. 11 in. diam. bears N 45° E 15.0 ft. dist. I found scribe on this O.B.T.

A B. O. 18 in. diam. bears S 55° W 6.0 ft. dist. I remark this O.B.T.

RE-RENEWED, SEE CORNER NO. #224 67

SOUTH 1/4 SEC. COR. 34

At midpoint on township line set 1" x 30" iron pipe, from which

A Fir 6 in. diam. bears N 32° W 9.0 ft. dist. marked 1/4 S 34 B.T.

68

THE CORNER FOR TOWNSHIPS 29 & 30 S, RANGES 4 & 5 WEST

All of the O.B.T.'s are standing and in good shape and bear as follows:

12" Cedar N 75° E, 1.5'

15" Cedar N 17° W, 12.0'

16" Cedar S 76° W, 23.0'

24" Cedar S 66° E, 41.0'

At corner point found wood post and set 1" x 30" Iron Pipe from which:

A Fir 48" diameter bears S 80° e, 9.5' distant marked T 30 S,

R 4 W, S 6, B.T.

South 1/4 corner Section 31 bears N 76° 30' E, 700.0 distant

69

SECTION CORNER 15, 14, 22, 23

Found 1 1/4" Iron Pipe and 1 Bearing Tree - **REN. #33**

6" White Oak (now 15") S. 68 1/2° W. 58.8 feet

Blazed and scribed new bearing trees

6" Ash S 35° E. 33.0 feet marked T. 29, R. 5, S. 23, R.E. 2741, B.T.

10" Alder, N. 70° W. 105.0 feet, marked T. 29, R. 5, S. 15, R.E. 2741, B.T.

RE-RENEWED, SEE CORNER NO. 160 70

1/4 SECTION CORNER 12-13

as determined by original bearing trees

A White Oak 33" in diameter bears S. 37 1/2° W. 51.0 feet distant, O.B.T.

I remark 1/4 S. B.T.

A Black Oak 30" in diameter bears N. 55° E. 51.0 feet distant, O.B.T.;

I remark 1/4 S B.T.

At corner point found large stone and set 1" x 30" Iron Pipe from which

A Laurel 15" diameter bears N. 25 1/2° E. 25.0 feet distant marked 1/4 S. 12, T. 29 S, R. 5 W., B.T.

Range line bears East 2766 feet distant

This corner lies squarely on top of main ridge, in trail. Fences bear South, East and West from corner.

RE-RENEWED, SEE CORNER NO. #20471 71

CORNER SECTION OF 15, 14, 22 and 23 - DUPLICATE

Found 1 1/4" Iron pipe and O.B.T., 6" W.O. (now 15") S 68 1/2° W, 58.8 ft. (cut out)

Blazed and scribed N.B.T.s

6" Ash, S 35° E, 33.0 ft., mkd. T 29 R 5 S -23
R.E. 2741 B.T.

10" Alder, N70° W, 105.0 ft., mkd. T 29 S R 5 W, S - 15
R.E. 2741 B.T.

72

Section Corner 5-6-7-8, as determined by O.B.T.s

A B.O. 15" diam. bears N33E, 30.0' dist. fd. scribe & remarked S5 B.T.

A B.O. 15" diam. bears N27W, 31.0' dist. remarked S6,

At corner point found old scribed post and set 1" x 30" I.P. from which

A Fir 15" diam. bears S65° W, 16.8' dist. mkd. S7 B.T.

A B.O. 10" diam. bears S69° E, 32.5' dist. mkd. S8, 2880 B.T.

Corner Lies about 200' North of top of ridge.

RE-RENEWED, SEE CORNER NO. 120 72

John H. Markham, Jr. - Eng.
Wit. - Geo. & Wm. Vaughn
April 22, 1951
C. S. 40/259

John H. Markham, Jr.
Engineer
Geo. Vaughn
Witness
C. S. 40/259

Aug. 1951
C. S. 40/363
J. L. Clinton, Wit.

J. H. Markham, Jr.
Reg. Engineer 2880
Dennis Vaughn, Wit.
9-16-51
C. S. 40/375

A. R. Evans
Wit: Clinton
Mike Evans
August, 1951

Set by
John H. Markham Jr.
Witness: E. Sorenson
File #41 Env. 75