

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

FOR MAPMAN CO. EUGENE, ORE. 97196

John H. Markham Jr.
Witnesses:
C. C. Pruitt
J. E. Pruitt
Work done for J. E. Pruitt
July 2, 1954
C. S. file 41/279

Northeast corner section 24. (NW cor. sec. 19, T29S, R4W.)
Corner set by nonproportional measurement.

At corner point set 1" x 30" iron pipe and large rock, from which
A 13 inch Fir bears S.65°E., 21.0 feet dist. mkd. S 19 B.T.
A 14 inch Fir bears N.24°E., 10.0 feet dist. mkd. S 18 B.T.
A 6 inch Fir bears N.37°W., 16.0 feet dist. mkd. S 13 B.T.
A 10 inch Fir bears S.22°W., 33.0 feet dist. mkd. S 24 B.T.
West corner section 18 (T29S, R4W) bears North 2667.0 feet.
West corner section 19 (T29S, R4W) bears South 2600.0 feet.
Corner lies on a 75% North slope.
Top of divide lies South 650 feet.

85
Fd. O.K.
by G. GAUSS
Dec. 1981
RM 3-52
SEE BLM
SURVEY 1957
for

Section corner to secs. 9, 10, 15 and 16 ; - - -T29S R5WWM
Found:

4" x4" x 36" oak stake; 1" I.P. 3.0 from true corner position. -Ren #18
Set iron pipe in correct location from 4 O.B.T.'s
12" Fir S35°E., 36.0 ft.
30" Fir S80°W 22.3 ft. (correct dist. 21.3 ft.) (Cop. tag RE 2741)
14" Fir N75°W 63.8 ft.
12" Fir N75°E 43.5 ft. (correct dist. 42.5 ft.) (Cop. tag RE 2741)
(Distances to face)

1/4 sec. corner to secs. 10 and 15; - - -T29S R5W WM REN #10

Set 3/4" iron pipe from 2 O.B.T.'s (in Md. of rock)
8" W.O. N64°E. 136.0 ft. (Cop. tag RE 2741)
12" W.O. S70°E. 119.6 ft. (Cop. tag RE 2741)
Blaze and scribe N.B.T.
14" Alder S44°W. 97.8 ft. Mkd. 1/4 S 15 BT Cop. tag RE 2741
(distances O.B.T.'s to face, N.B.T. to center of tree)

RE-RENEWED, SEE CORNER NO. #228

Center - SECTION 15

1/4 corner set by intersection; S. 15 T29S R5W Wm
Set 1" iron post with brass cap and Md. of Rock Mkd. T 29S.,
R5W., C 1/4 S 15 R.E. 2741
Blaze and scribe 2 B.T.'s
24" W.O. N 82°W., 305.5 ft. (dist. to face) mkd.
C 1/4 S 15 BT (Cop. tag, RE 2741)
6 ft. clump of Myrtle N47°E., 274.0 ft. (dist. to face)
Mkd. C 1/4 S 15 B.T. (Cop. tag RE 2741)

1/4 corner secs. 15 and 16; - - -T29S R5W WM

Found:
1" I.P. and 2 BTS mkd. 1/4 S 15 1/4 S 16 - Ren #79
N40°22' E, 31.7 ft. from true corner position
Recorded in Co. Surveyor's office as set by J.H. Markham Jr.
Set by proportionate meas. the following:
Set:
7/8" iron rod, blaze and scribe 2 B.T.'s
18" Fir N 63 1/2° W 38.2 ft. mkd. 1/4 S 16 BT (Cop. tag RE 2741)
12" Fir N. 26 1/2° E 22.9 ft. mkd. 1/4 S 15 BT (Cop. tag RE 2741)
(distances to center of trees)

1/4 corner secs. 14 and 15; - - -T29S R5W WM

Found:
2 O.B.T.'s and cedar stake mkd. 1/4 S CS.
BTs-10" W.O. N65°W., 78 lks. (cut out)
14" W.O. N68°E., 51 lks.(stump)
Set:
7/8" iron rod; blaze and scribe 2 B.T.'s
20" Fir N44 3/4° W 16.2 ft. mkd. 1/4 S 15 B.T. (Cop. tag 2741)
15" W.O. S55 1/2° E 93.7 ft. mkd. 1/4 S 14 B.T. (Cop. tag RE 2741)

Sec. corner to secs. 15, 16, 21, and 22.

Found 2" iron pipe with Elbow.
12" Fir S.86°E., 31.0 (down).
Fir N.78°W., 30.0 ft. (cut out).
12" Pine S.5°W., 49.5 (dead).

(NOT A RENEWAL)
SEE # 32

RE-RENEWED, SEE CORNER NO. #146

Survey by A. E. Evans in September, 1954
Done for the City of Myrtle Creek, Oregon.
See County Surveyor's File No. 41/300.