

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97190

1/4 corner to secs. 15 and 22. 92  
Found 1/2 inch iron rod and two E. T. s. Ren. #75  
16 inch Fir, N. 32° E., 1.8 feet.  
10 inch Fir, S. 58° W., 37.2 feet. SEE CORNER NO. 128

Set by A. R. Evans  
For City of Myrtle Cr.  
September 1954.  
See County Surveyor's  
file No. 41/300.

John H. Markham Jr.  
Witness:  
J. D. Phillips  
October 25, 1954  
File No. 41/309.

S. E. corner of the H. Adams Donation Land Claim No. 427. #208 93  
Determined by:  
A 30 inch B. O. stump (sawed off) bears N. 53 1/2° W., 67.0 feet dist. -  
O. B. T.  
At corner point set 3/4 inch X 40 inch iron pipe,  
From which:  
A 16 inch W. O. bears N. 39° W., 83.0 feet dist. mkd. S. E. DLC T 29 S  
B. T.  
A 12 inch B. O. bears N. 5° E., 65.0 feet dist. mkd. S. E. Cl cor B. T.  
Fence corner bears N. 30° W., 6.0 feet dist. Fence runs North and West  
from corner.  
South line of D. L. C. measures 41.0 feet long. (?)  
(4/29/54 MARKHAM FIELD NOTES CHECKED - READ 41')

1/4 corner secs. 17 and 18. 94  
Found both orig. BTs. The S. E. BT checks for bearing and distance.  
The recorded N. E. BT (N. 18° E., 80 lks.) found to be N. 18° W., 80 lks.  
The S. E. BT scribed 1/4 BT. The N. W. BT has rotted center. No scrib-  
ing visible.  
Set 1 inch iron pipe with brass cap for corner mkd. County Surveyors  
Office, T29S, R5W., 1954 1/4 sec 18/17, on east west fence line.  
Blazed and Scribed:  
22 inch B. O., S. 41° E., 77.8 feet dist., mkd. 1/4 S 17 CS BT.  
24 inch B. O., N. 25° W., 47.6 feet dist., mkd. 1/4 S 18 CS BT.

James W. Byron, Deputy County Surveyor  
Ray Irving, John Fee  
November 22, 23, 1954  
See C. S. File No. 46/63.

Section corner to secs. 7 and 18, T29S, R5W., and secs. 12 and 13, 95  
T 29 S, R 6 W.  
Found: Original N. E. BT. Now down and rotted. Part of old blaze  
O. K., scribing T29 W visible. Orig. S. E. BT standing. center  
rotted. Shows old blaze. The NW and SW BTs gone.  
Set 1 inch iron pipe with brass cap at corner using N. E. BT and S. E.  
BT. Cap marked T29S T29S  
R6W 12 7 R5W County Surveyors Office.  
13 18 1954  
Blazed and scribed:  
10 inch W. O., N. 74° W., 37.5 feet dist., mkd. T 29 S, R 6 W., S 12  
CS BT.  
14 in. W.O., S. 6° W., 32.5 feet dist., mkd. T29S, R6W., S 13 CS BT.  
10 in. W.O., N. 21° E., 18.0 feet dist., mkd. T29S, R5W/, S 7 CS BT.  
12 inch W. O., S. 89° E., 21.4 feet dist., mkd. T29S, R5W, S 18 CS BT/

1/4 corner to Secs. 26 and 27. 96  
This corner set 14.5 west of the Southwest corner of the Ireland  
D. L. C. No. 47 as is given in the original notes. SEE CORNER NO. 150

Gene E. Johnson, R.E. No. 3561.  
October, 1955.  
C. S. File No. 42/32.

Section corner to sections 26, 27, 34 and 35. 97  
This corner re-established by proportional measurement as modified for  
latitude by calls to South Myrtle Creek as noted in the original  
field notes.  
Set: 3/4" X 30" Iron Rod, #120  
S. E. Corner concrete foundation N. 36° W., 109.1 feet.  
5" + on rock in rock outcrop S. 74° W., 61.2 feet. 156  
3/4" X 30" Iron Rod S. 78° 50' E., - 109.7 feet.  
Double Incense Cedar N. 82° 45' E., 397.0 feet. DUPLICATE #118 SEE NEXT PAGE.

1/4 corner to secs. 34 & 35. 98  
Set a 3/4 inch iron rod at average dist. from corner to 34/35 and corner #223  
to secs. 26, 27, 34 & 35.  
Corner point falls on East slope, 73 feet W. and 98 feet South of  
small creek in old logging slash. From which:  
24" Incense Cedar, N. 26° 30' E., 32.8 ft. mkd. 1/4 S BT RE 3561. (Both trees have X above)  
18" D. Fir, bears S. 57° 32' W., 30.4 ft. mkd. 1/4 S BT RE 3561. (face and 3 hacks on back)