

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 5 R. W. W. M.

KOKS-CHAPMAN CO., EUGENE, ORE. 21881

99

John H. Markham Jr.
Work for Umpqua Plywood Corp.
May 15, 1956
C. S. File No. 42/189.

North Northwest corner D. L. C. No. 50.
Point for corner determined by G. B. T.s:
A 16 inch W. O. stump bears S.15°W., 18.5 feet dist. - O.B.T.- found scribe.
An 18 inch B. O. stump bears S.85°E., 23.5 feet dist. - O. B. T. - found scribe. - *See Ren. #54*
Set a 1 inch x 24 inch iron pipe at corner point,
From which:
A 5 inch W. O. bears S.13°W., 20.0 feet dist. mkd. CL. 50, B. T.
A 6 inch La. bears N.79°E., 26.0 feet dist, mkd. CL. 50 B. T.
A 10 inch La. bears S.48°E., 43.0 feet dist. mkd. CL. 50 B. T.
Old fence corner bears S.45°E., 22.5 feet. Fence runs So. and East.
C. O. P. Co. transmission tower bears N.55°W., approx. 330 feet.

Gene E. Johnson
November 20, 1955.
C. S. File No. 42/32.

Section corner to sections 26, 27, 34 and 35. *DUPLICATE #77 SEE PRECEDING PAGE. 100*
Point for corner located at average distance E. & W. from N. E. corner of Sec. 36, and N. W. corner of Sec. 33.
Set a 3/4 inch iron rod at corner point which falls in Barnyard pasture, 8.0 ch. East, 8.0 ch. West and 2.0 ch N. of South Myrtle Creek.
From which: (New B. O.s and B. T.)
S. E. corner of new foundation for chicken house bears N.36°10'W., 109.1 feet dist.
RE-RENEWED, SEE CORNER NO. 156
8 inch and 6 inch double Incense Cedar bears N.82°45'E., 397.0 feet dist., scribed T 29 S, R 5 W., W. M., Sec. 26 B. T. - R.E. 356l.
3/4 inch iron rod in fence corner on South bank Myrtle Creek bears S.78°50'E., 109.70 feet dist.
5 inch long " + " on flat face of rock outcrop bears S.74°15'W., 61.2 feet distant.
South peak of barn ridge bears N.85°W.

George J. Wenderoth
1957
Map File M 5 - 38.

1/4 corner to secs. 9 and 10. *101*
Corner set by proportional measurement. (halfway between sec. corners).
Set 3/4 inch iron pipe,
from which:
RE-RENEWED, SEE CORNER NO. #241
10 inch Cedar bears S.77°11'E., 15.0 feet.
13 inch Cedar bears S.35°25'W., 35.8 feet.

1/4 corner to secs. 3 and 10. *102*
Corner set by proportional measurement. (halfway between sec. corners).
Set 3/4 inch iron pipe,
from which:
RE-RENEWED, SEE CORNER NO. #181
12 inch Cedar, S.68°48'W., 21.0 feet.
12 inch Cedar, S.2°22'E., 55.8 feet.

Section corner to secs. 2, 3, 10 and 11. *103*
This corner previously renewed by Markham on August 1, 1950. - *Ren #64*
Set 3/4 inch iron pipe,
from which:
RE-RENEWED, SEE CORNER NO. 145
16 inch W. Oak, S.3°W., 345.0 feet. (mkd. by Markham in 1950).
13 inch W. Oak, S.31°26'E., 22.5 feet.
16 inch Pine, N.30°13'W., 28.5 feet.
14 inch Pine, N.33°45'E., 38.2 feet.

Robert M. Thompson
For Patrick Lumber Co.
June 1958
C.S. File No. 41/62

Sec. Cor. to Secs. 1 & 12, T29-5 and Secs. 6 & 7, T29-4. *103-A*
At Sec. Cor., I find 24" stunted D. Fir which U.S. notes call "Redwood", S.57 1/2°W. 43 ft. Find scribe "5W, S1(2)" (2 routed out). Other BT's burned.
Renewed-Set 6x10x12 Conglomerate Stone & new BT's: *144*
40" D. Fir S.75°30'W. 46.0 ft. = 14" I. Ced. N.23°40'W. 36.4 ft.
40" D. Fir N.88°40'E. 57.2 ft. - 17" I. Ced. S.34°20'E. 21.2 ft.
This corner falls 6 ft. E. of Little Lick Cr. & approx. 120'E. old log. Rd.
1/4 Corner to Section I, T29-5W. & Sec. 16, T29-4W. 1/4 Cor. 1/6. *103-B*
Being unable to find W 1/4 Cor. Sec. 6 after diligent search, I run blank West Sec. Line, & find total dist. of 5180.0 ft. At Midpoint on true Line I set 3/4" I. Pipe & Scribe: 15" D. Fir S.51°E. 31.0 ft.
6" D. Fir S.78°30'W. 44.0 ft.