

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 S T. S. R 5 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

116
 $\frac{1}{4}$ Corner to Sections 2 and 11.
 Found - Both BT's. as recorded by Stewart, 1921. We open N.W. BT. & find good scribe marks. Ren #23
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961 $\frac{1}{4}$ S 2 T29S R5W S11
 Note - This corner is in the 1961 burn area. All trees near corner are now dead. I find $1\frac{1}{4}$ " I. P. bears S.53°E. 4.8 ft.

117
 $\frac{1}{4}$ Corner to Sections 4 and 3.
 Found - Both of Markham's BT's: 9", now 10" Cedar Stump, off of ground, shows face. I believe a scribe mark, it has been badly burned. Stump hole checks S.85°E. 60.0 ft. The N.W. BT. down and badly burned checks O.K.
 Also find $\frac{3}{4}$ " I. P. at corner. Ren #65
 Set - Brass Cap alongside I.P. & Mkd: County Surveyor's Office, 1961 $\frac{1}{4}$ S4/S3 T29S R5W
 New BT's: 22" R.Fir bears S.64°W: 40.0 ft. scribed $\frac{1}{4}$ S4 CS BT.
 21" Cedar bears N.20 $\frac{1}{2}$ °E. 143.0 ft. scribed $\frac{1}{4}$ S3 CS BT.

118
 Section Corner to Sections 7 - 8 - 17 - 18.
 Found - All of Eppstein's BT's. S.W. BT. shows scribing. Ren #36
 Also find Mound of Stone & old Sq. Stake at Corner.
 Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1962

S 7	S 8	T29S R5W
S18	S17	

 North - South Fence 1.5 ft. East.
 New BT: 7" W.Oak bears N.65°E. 81.3 ft. scribed S 8 CS BT.

119
 Section Corner to Sections 16 - 17 - 20 - 21.
 Found - $\frac{1}{2}$ " I. P. at Corner & S.W. BT. as recorded by Stewart, 1921. Other BT's. not found. Ren #31
 Chisel 3" + on top 12" x 16" x 18" high Stone bears N.20°E. 24.0 ft.
 No other trees near.

120
 Section Corner to Sections 5 - 6 - 7 - 8.
 Found - Orig. N.E. & N.W. BT's. & Markham's S.E. & S.W. BT's. S.W. BT., now stump, shows scribing. S.E. BT. down, shows scribing.
 Also find $1\frac{1}{2}$ " I. P. at Corner. Ren #72
 Set - Brass Cap alongside I. P. & Mkd: County Surveyor's Office, 1962

S 7	S 8	T29S R5W
S 7 E 5	S 7 E 8	

 New BT's: 5" W.Oak bears S.33°W. 17.3 ft. scribed S7 CS BT.
 10" Laurel bears S.11 $\frac{1}{2}$ °E. 42.2 ft. scribed S8 T29S R5W CSBT.

121
 $\frac{1}{4}$ Corner to Sections 6 and 5.
 Found - Both BT's. as recorded by Cain, 1920. We open N.E. BT. & find good scribing. N.W. BT. shows good scar. Ren #23
 Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S6/S5 T29S R5W
 New BT: 10" Laurel bears N.15°E. 20.4 ft. scribed $\frac{1}{4}$ S5 CS BT.
 Fence corner thus

122
 $\frac{1}{4}$ Corner to Sections 5 and 8.
 Found - Cain's 10", now 12" W.O. N.80 $\frac{1}{2}$ °E. 34.6 ft. We open & find good scribing $\frac{1}{2}$ " S. S.W. BT. not found. Ren #22
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

S 5	T29S R5W
S 8	

 New BT's: 10" W.Oak bears N.83 $\frac{1}{2}$ °E. 19.0 ft. scribed $\frac{1}{4}$ S 5 CS BT.
 7" W.Oak bears S.43 $\frac{1}{2}$ °W. 19.8 ft. scribed $\frac{1}{4}$ S 8 CS BT.
 Note - N. S. Fence bears East 50 feet.

James W. Hyron, Deputy County Surveyor
 Dale McFarland
 John Powell
 December 1961 and January 1961
 C. S. File No. 49/64