

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881



James W. Byron, Deputy Co. Surveyor
Dale McFarland and John Powell
February 1962
C. S. File No. 49/64

Sec. Cor. to Secs. 6 - 7, T29-5W. & Sec. 1 - 12, T29-6W. 123
Found - Orig. 8", now 14" B.Oak S.55°E. 13.9 ft., previously opened,
shows good reverse scribing on old chip "R".
Orig. 18", now 36" Laurel Snag N.87°E. 66.0 ft.
Orig. 12", now 20" W.Oak N.89°W. 23.1 ft., shows scars.
We do not open.
Orig. S.W. BT. not found.

Set - Brass Cap at Cor. Mkd: County Surveyor's

S 1	S 6
R6W S12	S 7 R5W T29S

New BT's: 8" W.Oak bears S.79°W. 52.0 ft. scribed S12 T29S R6W CS BT.
11" W.Oak bears N.58°E. 74.5 ft. scribed S 6 T29S R5W CS BT.
10" W.Oak bears S.69°E. 18.0 ft. scribed S 7 T29S R5W CS BT.

Note - Fence Corner Thus 
O.B.T. 

Section Corner to Sections 17 - 18 - 19 - 20. 124
Found - Orig. 10", now 34" W.Oak N.33°W. 142.6 ft. We open & find
good scribing. No other Orig. BT's. found.
Corner is in center of small stream. I set Wit. Cor. 20.0 ft. North.
Set - Brass Cap at Wit. Cor. & Mkd: W. C. 20 ft. South to

S 18	S17
S19	S20


 T29S R5W County Surveyor's Office, 1962

New BT's: 17" W.Oak bears N.27°E. 27.4 ft. scribed S17 W.C. T29SR5W CS BT.
8" B.Oak bears N.27°W. 38.6 ft. scribed W.C. S18 CS BT.
28" Maple bears S.79½°E. 56.6 ft. scribed W.C. S20 T29SR5W CS BT.
28" B.Oak S.7½°W. 70.1 ft. scribed W.C. S19 T29S R5W CS BT.

¼ Corner to Sections 21 and 22. 125
Found - 5/8" I.R. at corner & both BT's. as recorded by Evans. *Ren. 74*
N.E. BT., now snag, shows good scribing "¼ S22 BT".
N.W. BT. now stump.

Set - Brass Cap alongside I.R. & Mkd: County Surveyor's Office, 1962
¼ S21/S22 T29S R5W
New BT's: 9" R.Fir bears N.80°W. 27.0 ft. scribed ¼ S21 CS BT.
11" Laurel bears N.87½°E. 36.8 ft. scribed ¼ S22 CS BT.

Section Corner to Sections 20 - 21 - 28 - 29. *By Max Hull 1-9-1994-0029* 126
Found - 1" I.P. at Corner & BT's as recorded except, now 14" Fir bears
N.87½°W., not S.82½°W. *Ren. #30*
S.W. BT. now dead. S.E. BT. down. N.E. BT. dead.

Note - Fence Corner Thus: 
New BT's: 26" R.Fir bears S.49°W. 30.0 ft. scribed S29 T29S R5W CS BT.
20" B.Oak bears S.46°E. 46.3 ft. scribed S28 T29S R5W CS BT.

¼ Corner to Sections 21 and 28. 127
Found - Both BT's. as recorded by Wenderoth. S.E. BT., now snag.
S.W. BT. O.K. We also find 1" I.Pipe about 3' under surface. *Ren. 129*
Set - Brass Cap alongside Corner I.P. & Mkd: County Surveyor's
Office, 1962

¼ S21	T29S R5W
S28	

159

¼ Corner to Sections 15 and 22. 128
Found - ¾" I.R. at corner and both BT's. as recorded by Evans, except
now 12" Fir bears S.52°W., not S.58°W. *Ren. #75 + #92*
N.E. BT., now stump, shows scribing.
Set - Brass Cap alongside ¾" I.R. & Mkd: County Surveyor's

¼ S15	T29S R5W
S22	

 Office, 1962
New BT: 18" Cedar bears N.26°W. 44.0 ft. scribed ¼ S15 CS BT.
Note - 4 way Fence Corner & 1½" I.P. bears S.28°W. 74 feet.