

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29 S . T. S. R 5 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

~~RE-RENEWED SEE CORNER NO. #209~~  
 $\frac{1}{4}$  Corner to Sections 33 and 34. 129  
 Found - 1 $\frac{1}{2}$ " I. P. & Fence Corner as recorded. We do not find  
 either Old B.T. - Ren. #60

New BT's: 20" W.O. bears S. 52 $\frac{1}{2}$ °W. 66.6 ft. scribed  $\frac{1}{4}$  S33 CS BT.  
 7" Laurel bears N. 4 $\frac{1}{2}$ °E. 49.4 ft. scribed  $\frac{1}{4}$  S34 CS BT.

11/177 SEE NOTE IN ALSO SEE Vol 3 Pg 21 Lem  
 59/42 FAR CONDITION REPORT. v.R.

S. W. Corner D. L. C. No. 47. 129A  
 Found - Both BT's. and fence corners as recorded by Johnson.

Do not find monument at either  $\frac{1}{4}$  Corner or D. L. C. Corner.  
 Set - Brass Cap at D. L. C. Cor. Mkd: County Surveyor's  
 Office, 1962 S.W. Corner D.L.C. 47 T29S R5W. #198

~~RE-RENEWED SEE CORNER NO. #225~~  
 $\frac{1}{4}$  Corner Sections 19 and 30. 130  
 Found - Orig. 24", now 36" Pine Stump S. 58°W. 102.3 ft. We open  
 & find good scribing "4S"

Orig. N.W. BT., now Pine Stump, face burned.  
 Found Mound of Stone at Corner.  
 Note - Corner is on top of High North-South Ridge & 20' West  
 of Log Road.

Set - Brass Cap at Corner Mkd: County Surveyor's  $\frac{1}{4}$  S19 T29-5W  
 Office, 1962 S30  
 New BT's: 20" Pine bears S. 47 $\frac{1}{2}$ °W. 142.9 ft. scribed  $\frac{1}{4}$  S30 CS BT.  
 7" Cedar " S. 10 $\frac{1}{2}$ °W. 150.9 ft. scribed  $\frac{1}{4}$  S30 CS BT.

~~RE-RENEWED SEE CORNER NO. #199~~  
 $\frac{1}{4}$  Corner to Sections 31 and 32. 131  
 Found - Both BT's. as recorded by B.B.E. 1920 N.W. BT Down  
 & rotted, shows old axe marks. S.E. BT. shows good  
 scar and it is black oak, not white oak. - Ren. #26

6" x 2" (wedge shape) 3" above ground with + on S. face, Stone.  
 New BT: E.W. Oak bears N. 59°W. 57.5 ft. scribed  $\frac{1}{4}$  S31 CS BT.  
 Note - Fence Corner 14 ft. South. (COR. FOUND FEB. 1973 - M 47-63)

Sec. Cor. Secs. 18 & 19, T29-5W & Secs. 13 & 24, T29-6W. 132  
 Found - Orig. 12", now 44" B.Oak, opened years ago, center  
 rotted, S. 85°W. 45.0 ft., not 56.1 ft.

1" I.P. at corner & remains of N.W. & N.W. Orig. BT's.  
 Show axe work, check record.

Note - N.S. & Fence to West corner bears S. 25°E. 4 ft.  
 New BT's: 40" B.Oak bears N. 0 $\frac{1}{2}$ °E. 72.8 ft. scribed S18 T29S  
 R5W CS BT. (This BT. previously bark scribed)  
 48" B.Oak bears N. 82°W. 75.0 ft., previously scribed.  
 44" B.Oak, O.B.T. S. 85°W. 45.0 ft. We scribed CS BT,  
 (previously bark scribed)  
 W. Oak bears S. 15°E. 134.4 ft. We scribe CS BT.

Sec. Cor. to Secs. 4 & 5, T30-5W. & Secs. 32 & 33, T29-5. 133  
 Found - 1 $\frac{1}{2}$ " I.P. 14" under at corner & both BT's. as recorded. - Ren. #15

Set - Brass Cap Mkd: Wit. Cor. 192.0 ft. West to  
 S32 | S33 T29S R5W County Surveyor's  
 S 5 | S 4 T30S R5W Office, 1962

Note - Wit. Cor. is 10 ft. West of ditch Line.  
 New BT: 24" W.Oak bears N. 16 $\frac{1}{2}$ °E. 163.8 ft. scribed W.C. S33  
 T29S R5W CS BT.

James W. Byron, Deputy County Surveyor  
 Dale McFarland and John Powell  
 February 1962  
 C. S. File No. 49/64.