

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29 S T. S. R 5 W R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

142

Section Corner to Sections 8 - 9 - 16 - 17.

Found - Orig. N.E. - N.W. & S. W. BT's., all now down & rotted.

Well find good reverse scribing on Orig. SW BT.

BT's. are Pines, not R. Fir.

Set - Conical Stone 12" X 12" x 15" high at Corner; chisled  
2" + on North Face & small + on pointed top.

Corner is 2ft. South of E. W. Fence.

New BT's: 14" Pine bears N. 11° E. 114.7 ft. scribed S9 T29S R5W CS BT.

11" R. Fir bears N. 0 1/2° W. 111.0 ft. scribed S8T29S R5WCS BT.

No trees near South of E. W. Line.

**RE-RENEWED CORNER NO. # 242**

143

Sec. Cor. to Sec.s. 12 & 13, T29-5W & Secs. 7 & 18, T29-4W.

Found - 1" I.P. at Corner & BT's., bark scribed, as recorded

by Evans, 1953. I rescribe 22" R. Fir N. 30° E. 11.4 ft.

S 7 T29S R4W CS BT.

New BT's: 12" R. Fir bears S. 37° E. 25.3 ft. scribed S18 CS BT.

14" R. Fir bears S. 29° W. 44.0 ft. scribed S13 T29S R5W CS BT.

Note - Corner under E. W. Fence.

144

Sec. Cor. to Secs. 1 & 12, T29-5W. & Secs. 6 & 7, T29-4W.

Found - Stone at Corner & BT's. as recorded by Thompson, except

SW. BT., now stump and N.E. BT., down. - Ren. # 103-A

Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's

	S 1	S 6		T29S		Office, 1962
R5W	S12	S 7	RAW			

Note - Corner is 6 ft. East of Stream.

New BT: 5" R. Fir bears N. 45 1/2° E. 6.7 ft. scribed S 6 CS BT.

145

Section Corner to Sections 2 - 3 - 10 - 11.

Found - 2" I.P. at corner & BT's. as recorded by Wenderoth, 1957, Ren. # 103

except N.W. & N.E. BT's., now dead, burned in 1961 fire.

Set - Brass Cap alongside I.P. & Mkd: County Surveyor's Office, 1962.

	S 3	S 2		T29S R5W
S10	S11			

New BT: 14" R. Fir bears S. 69 1/2° W. 63.2 ft. scribed S10 T29S R5W CS BT.

No other live trees near.

By F.D.K.  
Raymond Brown  
1/94  
1994-0021  
A-15

James W. Byron, Deputy County Surveyor  
Dale McFarland and John Powell  
March 1962  
C. S. File No. 49/64

146

Section Corner to Sections 15 - 16 - 21 - 22.

Found - 2" I.P. at Corner. 6", now 19" R. Fir N. 78° W. 30.0 ft., face

opened, pitched over. - Ren. # 32 & 91

12", now 24" Fir Stump S. 86° E. 31.0 ft., shows scar.

12", now 16" Pine, S. 5° W. 49.5 ft., opened, center rotted

& burned, shows faint scribing.

New BT's: Rescribe now 19" R. Fir N. 78° W. S 16 CS BT.

30" Dbl. R. Fir N. 30° E. 8.4 ft. scribed S15 T29S R5W CS BT.

16" R. Fir bears S. 59 1/2° W. 50.2 ft. scribed S21 T29S R5W CS BT.

15" R. Fir bears S. 28° E. 114.5 ft. scribed S22 T29S R5W CS BT.

Set - Brass Cap alongside Corner Pipe & Mkd: County Surveyor's

	S16	S15		T29S R5W	Office, 1962
S21	S22				

1/2 Corner to Sections 30 and 31.

Found - Both BT's, as recorded by B.B.I. except distances are transpd.

Should be 8" Fir S. 28° 50' W. 54 lks. & 8" Fir N. 2° 20' E. 11 lks.

Stone set for Corner, now broken into small parts. - Ren. # 43

Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S30 T29S R5W

Office, 1962 S31

Note - E. W. Fence is 1.0 ft. South of Corner.

April 1962

Section Corner to Sections R6W S25 | S30 R5W T29S

	S36	S31	
--	-----	-----	--

Found - 2" I.P. at corner. Orig. 10", now 38" Fir S. 60° W. 11.2 ft.,

shows scbg. on old face. Also find stump of B.B.I. N.E. BT.,

& now down. SW BT., NW BT. & SE BT. of B.B.I. O.K. bark scribed.

New BT's: 6" R. Fir bears N. 7° E. 15.5 ft. scribed S30 CS BT.

9" R. Fir bears S. 81° E. 26.2 ft. scribed S31 T29S R5W.

**RE-RENEWED CORNER NO. # 192**

148

James W. Byron  
and Crew.  
April 30,  
1962

C.S. File  
No. 49/139