

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T.S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

Frank Cain, Dep. Co. Surv.  
F.C. Frear, Co. Surv.  
January 1920  
Recorded in Volume 2,  
Page 280 - 281

Center of Section 8.

Set - A Pitch Pine Post  $3\frac{1}{2}$ " x 4" x  $3\frac{1}{2}$ " from which:  
A Pine 36" in dia. mkd.  $\frac{1}{16}$  CS bears S.80°35'E. 264 lks.  
A Pine 36" in dia. mkd.  $\frac{1}{16}$  CS bears N.80°35'E. 314 $\frac{1}{2}$  lks.  
SW face of a rock 7' x 12' x 4' high bears S.41°W. 237 links.  
No tree near in NW $\frac{1}{4}$  of Section

Var. used in taking bearings to these BTs -- 20°E--

Note - Formation in Sec. 8 largely Serpentine and its associated rocks,  
which makes much local attractions and very little if any  
dependence can be placed on magnetic bearings.

For other Corners of this survey by Frank Cain See Cors. No. 19 thru No. 23.

149

\* deleted  
Per research  
8/98  
FB 107  
Pg 16

James W.  
Byron &  
Crew  
For Doug. Co.  
March 1962  
M 23 - 35

$\frac{1}{4}$  Corner to Sections 27 and 26.

Set from tie to S.W. Corner DLC No. 47, per gov't notes. REN. #96

Set - Brass Cap at Cor. Mkd:  $\frac{1}{4}$  S27/S26 T29S R5W County Surveyor's  
Office, 1962

New BT: 13" B.Oak bears S.53°E. 153.6 ft. scribed  $\frac{1}{4}$  S26 CS BT.

FD B.C. 4/92  
J. ARTMAN  
M 115-20

150

C.W. Springer,  
D.C.S.  
Cor. No. 4,  
T28-5W.

$\frac{1}{4}$  Corner to Sec. 32, T28-5W. & Sec. 5, T29-5W.

I set corner from old Oak tree which was standing and  
in good shape. Old Ash B.T. in evidence but down.  
Marked - A 15" Alder for the B.T. which bears S.28°W. 559 lks.

February 1923

Section Corner to Secs. 4 - 5, T29-5W. & Secs. 32 - 33, T28-5W.

I renewed this corner from 3 Old BT's. Other tree was gone.

Set - Oak Post. Fence Post at Corner. Old BT's. are badly rotted. #106

Marked New Bearing Trees, as follows:

Bl. Oak 20" bears S.66°W. 170.7 feet.

Bl. Oak 14" bears N.28°30'W. 68.8 feet

W. Oak 10" bears N.78°E. 148.8 feet

Bl. Oak 10" bears S.24°E. 120.0 feet.

N. W. Corner of Sec. 31, T29-4W.  $\frac{S25}{R5W} \frac{S30}{S36} \frac{S31}{S31} \frac{R4W}{R4W}$  (as det. by O.B.T's.)

A Black Oak windfall 8" diam. bears N.55°E. 35.0 ft. dist. O.B.T.

A Bl. Oak 14" diam. bears S.64°E. 20.0 ft. O.B.T.

At Corner Point, I set 1" x 30" Iron Pipe, from which:

A Fir 5" bears S.24°E. 10.5 ft. mkd. S31 B.T.

A Fir 6" bears S.20°W. 24.5 ft. mkd. S36 B.T.

A Laurel 12" bears N.28°W. 13.0 ft. mkd: S25 BT.

A Bl. Oak 10" bears N.87°E. 28.0 ft. mkd: S30 BT.

$\frac{1}{4}$  Corner to Section 13, T29-5W. & Sec. 18, T29-4W.

Set a 1" x 30" Iron Pipe with Brass Cap 18" above ground, mound of stone.

Positive identification by both Original Bearing Trees.

Blazed and scribed: 24" W.O. S.80°E. 37 ft. mkd:  $\frac{1}{4}$  S18 CS BT.

Reblazed & Scribed O.B.T. N.18°W. 38 lks. (24" W.O.) and Mkd:

$\frac{1}{4}$  S13 CS BT. Orig. record showed this BT. N.78°W, sh. be N.18°W.

$\frac{1}{4}$  Corner to Sec. 36, T29-5W. & Sec. 31, T29-4W. (as det. by O.B.T's)

B.O. Stump Hole bears W. 24.4 feet

B.O. Stump Hole bears N. 3°W. 42.9 feet.

20" Fir bears S.32°W. 16.0 ft. dist.

O.B.T. - I rescribe  $\frac{1}{4}$  S36 BT.

At Corner Point Set 2" x 30" Truck Axle from which:

50" Fir bears S.66°E. 4.0 ft. dist., bark scribed  $\frac{1}{4}$  S31 BT.

6" Maple " S.33°E. 42.6 ft. dist. mkd:  $\frac{1}{4}$  S31 BT.

10" Fir bears N.11°E. 70.0 ft. dist. mkd:  $\frac{1}{4}$  S31 BT.

Top & Road bears East 270.0 ft. - Top & Road bears South 390.0 ft.

Ben B. Irving  
Wit: J. Byron  
R. Irving  
July 24, 1953  
C.S. File 45/234

154

155

John H. Markham, Jr.  
Wit: R.G. Boyd.  
For: Stomar Lumber  
April 22, 1958  
CS File No. 42/345

RE-NEWED CORNER NO. 202

RE-NEWED CORNER NO. #200 - #106