

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

S. E. Corner D. L. C. No. 46. 170
This corner set from survey at pro-rated distance. *REN. #39*
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969 T 29 S R 5 W S E. Cor. DLC #46 S 35

New BT's: 13" D. Fir S. 79°W. 38.5 ft. mkd: " S.E. DLC 46 CS BT."
8" D. Fir N. 8°E. 12.1 ft. mkd: " S.D. DLC#46 CS BT".

SEE 2011 C.S. POSSIBLE FOR E.P.
N. E. Corner D. L. C. No. 46. *FOOK 8/92 BY RUPPERT M112-55* 171
Found $\frac{1}{2}$ " I. Pipe N. $1\frac{1}{2}$ °W. 5.07 ft. from DLC Cor. #46, no record.
Orig. 12", now 30" W. Oak, N. 75°E. 58.2 ft., opened, shows scribe "B".
Unrecorded 16" W. Oak S. 66 $\frac{1}{2}$ °E. 65.3 ft., shows good scar.
Reset this corner from Orig. bear. & dist. from Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969 T 29 S R 5 W N. E. Cor. D.L.C. #46 S 26

New BT's: 16" W. Oak S. 66 $\frac{1}{2}$ °E. 65.3 ft. mkd: "N.E. DLC #46 CS BT".
14" W. Oak N. 63 $\frac{1}{2}$ °E. 97.8 ft. mkd: N.E. DLC #46 CS BT".

Note: This corner lies on south slope N. 77°W. 11.0 ft. from a 3-way fence corner, see sketch in file.

South $\frac{1}{4}$ Corner to Section 35 only. 172
This corner set from survey at pro-rated distance.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969 T 29 S R 5 W $\frac{1}{4}$ S 35

New BT's: 13" D. Fir N. 4 $\frac{1}{2}$ ° E. 46.8 ft. mkd: " $\frac{1}{4}$ S35 CS BT".
10" Laurel N. 58° E. 22.3 ft. mkd: " $\frac{1}{4}$ S35 CS BT".

This corner lies north 4.0 ft. of east-west fence line.

$\frac{1}{4}$ Corner South Side Section 33 only, T29-5W. *FO. 9/72 W. RUPPERT M115-70* 173
This corner set from survey at prorated distance.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970 T 29 S R 5 W $\frac{1}{4}$ S 33 T 30 S

New BT's: 14" W. Oak N. 65°E. 85.5 ft. mkd: " $\frac{1}{4}$ S33 CS BT".
18" B. Oak N. 12°W. 129.0 ft. mkd: " $\frac{1}{4}$ S33 CS BT".

This corner lies 6.0 ft. N. of E-W Fence Line & 140.0 ft. S. of ravine. 2/5/70

North $\frac{1}{4}$ Corner to Section 4 only, T30-5W. #222 174
This corner set from survey at prorated distance:
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1970 T 29 S R 5 W T 30 S R 5 W S 4

New BT's: 6" B. Oak S. 77 $\frac{1}{2}$ °W. 4.5 ft. mkd: " $\frac{1}{4}$ S 4 CS BT".
13" Laurel S. 80°W. 42.3 ft. mkd: " $\frac{1}{4}$ S4 CS BT". 3/2/70

$\frac{1}{4}$ Corner to Sec. 6, T29-5W. & Sec. 1, T29-6W. 175
Prorated $\frac{1}{4}$ corner, See Map M 33 - 63.
Set - Brass Cap Mkd: Eng. #2128 Nov. 1969, $\frac{1}{4}$ Cor. T29S R6W Sec. 1, T29S R5W Sec. 6.
New BT: 24" Forked Ash by creek, N. 89°E. 162.4 ft. mkd: " $\frac{1}{4}$ S6 BT".

$\frac{1}{4}$ Corner to Sections 6 and 7. 176
Prorated $\frac{1}{4}$ Corner, See M 33 - 63.
Set - Brass Cap Mkd: Eng. No. 2128, Nov. 1969, $\frac{1}{4}$ Cor. 6/7 T29S R5W
New BT's: 26" Oak N. 34°W. 263.8 ft. mkd: " $\frac{1}{4}$ S 6 BT".
30" Oak S. 11°W. 111.3 ft. mkd: " $\frac{1}{4}$ S7 BT".

N. E. Corner D. L. C. No. 37. 177
Found - 30" Oak B. T. S. 80° E. 73.7 ft., See Ren. #24.
Set - Brass Cap, mkd: Eng. No. 2128- Nov. 1969, N.E. Corner DLC 37.

James W. Byron, Co. Surv.
John M. Powell & Crew
April, 1969
C. S. File No. 54/84 M 37 - 44

James W. Byron, Co. Surveyor
John M. Powell & Crew
March, 1970 C.S. File 54/108
Map File M 39 - 45

Wm. S. Barnes
For Otis Clayton
Nov. 1969 C.S. File 55/136
Map File M 33 - 63