

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

178

Wm. S. Barnes
For: Otis Clayton
C.S. 55/136
M 33 - 63

Center of Section 6.
Set - Brass Cap to Mark Center of Section 6 Mkd: Eng.#2128, Nov. 1969
T29S, R5W. C 1/4 S 6
New BT's: 20" D.Fir N.38°E. 28.9 ft. mkd: C 1/4 S6 BT.
18" D.Fir S.51°W. 45.9 ft. mkd: C 1/4 S6 BT.
- FD OK, MJA-31, Apr 1994, Ruppert - Nov. 1969

179

John M. Powell
&
Crew
C.S. File
No.
49/64

1/4 Corner to Sections 13 and 14.
Found - 12", now 30" B.Oak, N.25°W. 31.0 ft., opened for scribing
No trace of S. E. Bearing Tree. ^{FD. BC. OK. by G. GRUBB DEC. 81}
Set - Brass Cap at Cor. Mkd: County Surveyor's T29S R5W RM 3-52
Office, 1971 1/4 S 14 S 13
New BT's: 30" W.Oak S.70°E. 48.7 ft. scribed "1/4 S13 CS BT".
14" D.Fir N.80°W. 24.0 ft. scribed "1/4 S14 CS BT".
10/15/71

180

James Byron, Deputy
M. Darby
Wm. Stoffel
1962 - June 1963
C.S. 49/64

Corner to Sections 35 and 36 only.
Found - Brass Cap at Corner. S35/S36 T29 R5W
13" Fir N.87°W. 27.7 ft., shows scribing. T30
15" Fir N.46°E., 49.5 ft., now down.
New BT: 12" Fir N.86°E. 29.3 ft. scribed T29S R5W S36 CS BT.
June 10, 1963

181

Gary Langlitz
P. Earle
C.S. 56/41
12/12/73

1/4 Cor. for Secs. 3 and 10.
Found - 3/4" Iron pipe. Ren. #102
12" Incense cedar snag, down, bears S.69°W., 21.4 ft.
(record S.68°48'W., 21.0 ft.) We remove soil from
scribe area and find scribing "1/4" BT.
12" Fir stump bears S.3°E., 55.8 ft. (record 12" Cedar,
S.2°22'E., 55.8 ft.) Scribing "1/4 BT" visible
Set - Brass cap mkd. COUNTY SURVEYORS T 29 S
OFFICE 1/4 3
1973 10
R 5 W WM
with 3/4" I.P. alongside from which I mark New BT's:
22" D. Fir, bears N.70°W., 125.7 ft. scribed 1/4
S3 CS BT.
18" D. Fir, bears N.14 1/2°W., 88.7 ft. scribed 1/4
S3 CS BT.
12/12/73

RE RENEWED
SEE CORNER NO. 238

182

Gary Langlitz, County Surveyors Office
P. Earle
C.S. 56/51
4/26/74

Sec. Cor. for Secs. 29, 28, 32, 33
Found - 13" now 16" bigleaf maple, mkd. in 1957 by BLM,
showing a well healed blaze.
12" now 16" Fork of a triple-forked bigleaf maple
mkd. in 1957 by BLM, showing a well-healed blaze.
A reference monument, a brass cap mounted on an I.P.
mkd. Bureau of Land Management, Cadastral Survey
T29S R5W S33 1957, with an arrow pointing approx.
toward the true cor. This R.M. has been struck with
farm machinery and moved out of position. ^{#219}
30" now 60" Bigleaf maple with partial scribing
"29 S32 CS" visible on previously opened blaze. See
Ren. #52
It is noted that discrepancies appear in both bearings and dis-
tances when attempting to determine the true cor. positon using
the 60" maple in conjunction with the two 16" maples. Holding
the distance from the 60" maple causes the bearings and distances
from the remaining BT's to be in error.
At the true cor. point;
Set - a 5/8" x 30" I.R., buried 18" below ground surface in
a garden area. No trace of rifle barrel or angle iron
was found.
BT's - 12" now 16" Maple bears N.52 1/4°W., 165.7 ft. (rec.
N.52 1/4°W., 165.7 ft.) showing a well-healed blaze.
13" now 16" fork of a forked maple bears S.79 1/2°W.,
90.4 ft. (rec. S.79 1/2°W., 90.4 ft.) showing a well-
healed blaze.

CONT.