

Douglas County Surveyor's Record of
Government Corners Renewed

T 29

T. S. R 5

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

188

C O N T.

Set - I move brass cap S.59°34'20"W., 4.31 ft. Cap is set 7" above ground in a 18" mound of stone and stamped "Reset 1977" above "1969".

I set a 5/8" x 30" I.R. in orig. brass cap location with a 1 1/2" Alum. cap set 6" above ground in a 18" mound of stone and marked "Douglas Co." 1977 Surveyor.

No new accessories. N-S fence bears east 3.7 ft.

12/14/77

189

1/4 Corner for Sec. 19; and Sec. 24 of T29-6

Found - 1969 County Surveyors office brass cap set 14" above ground properly marked. Corner was proportioned between the NW cor. Sec. 19 and SW cor. Sec. 30. Needs resurveyed since the SW Cor. Sec. 19 has been found Ren. #163 and M37-20

A 10" D. Fir bears N.68 1/2°W., 14.4 ft. (Rec. S.87°W., 21.3 ft.) with a well healed double blaze.

A 7" W. Oak bears N.86°E., 23.9 ft. (Rec. N.82°E., 16.1 ft.) with visible scribing "S19" in partly healed double blaze.

Set - I reset brass cap S.74°21'34"W., 8.85 ft. Cap is 6" above ground in a 18" mound of stone and marked "Reset 1977".

Set - I set a 1" x 30" I.R. in orig. brass cap location with a 1 1/2" alum. cap set 6" above ground in a 18" mound of stone and marked "Douglas Co." 1977 Surveyor.

No new accessories. N-S fence bears East 20.3 ft. Boomer Hill Rd. bears North 124 ft.

12/13/77

190

South 1/16 for Sec. 19; and Sec. 24 of T29-6.

Found - A 1" x 36" I.P. with 1969 County Surveyor brass cap set 16" above ground properly marked. Cor. was set by proportion between the NW cor. Sec. 19 and SW cor. Sec. 30. Need for resurvey since the SW cor. Sec. 19 has been found.

A 17" now 18" D. Fir bears N.73°E., 35.6 ft. (Rec. N.73°E., 25.2 ft.) with a well healed double blaze.

A 9" now 12" D. Fir bears S.0 1/2°E., 19.2 ft. (Rec. S.27°W., 27.0 ft.) with a well healed double blaze.

Set - I reset brass cap S.70°04'W., 12.96 ft. Cap is 5" above ground and marked "Reset 1977" above "1969".

Set - A 1" x 30" I.R. in orig. cap location with a 1 1/2" alu.. cap set 4" above ground and marked "Douglas Co." 1977 Surveyor.

No new accessories. A N-S fence bears East 39.6 ft.

12/13/77

191

North 1/16 Corner for Sec. 30; and Sec. 25 of T29-6.

Found - A 1" x 36" I.P. with 1969 County Surveyors brass cap set 13" above ground properly marked.

I remove and reset to proportioned point between NE and SE section corner Sec. 25. Cor. was orig. proportioned between the NW cor. Sec. 19 and SW cor. Sec. 30. Needs resurveyed since the SW cor. Sec. 19 was found.

A 24" now 26" Ash, measured below the fork, bears N.18°E., 59.2 ft. (Rec. N.6°E., 52.5 ft.) with visible scribing "N 1/16 CS BT" in partially healed double blaze.

A 16" Cedar bears N.61°E., 65.5 ft. with visible scribing "CS" in partially healed single blaze.

Set - I reset brass cap 8" above ground in a 15" dia. mound of stone, at proportioned location, stamped "Reset 1977" above "1969".

Set - a 5/8" x 30" I.R. in a 15" mound of stone with alum. cap stamped "Douglas Co" 1977 Surveyor, at old location of brass cap. 1 1/2" Alum. cap bears N.70°26'E., 13.05 ft.

No new accessories. Corner is 0.8 ft. north of east-west fence. Corner of fence to south and west bears S.87°E., 25.2 ft.

12/12/77

R. B. Kimberling, Douglas County Surveyors Office
F. C. Sliagy
December, 1977
C.S. 59/42