

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 T. S. R 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

225

1/4 Corner for Sections 19 and 30
Found - A 1962 DCSO 2 1/2" dia. brass cap on a 1 3/8" O.D. x 36" long iron pipe is found out of ground. Ren. #130
36" now 24" dia. 3 ft. high ponderosa pine stump, no blazes or marks visible, bears N.3 3/4°W., 50.4 ft. (Rec. N.2°W., 49.5 ft. dist. is a possible face meas.) Orig. BT.
Orig. 24" Southwest Pine is gone, probably scraped out by cat work.
20" now 27" dia. Ponderosa Pine with a fully healed double blaze bears S.46 1/2°W., 142.9 ft. (Rec. S.47 1/2°W., 142.9 ft.) Ren.#130
7" now 25" dia. 2 1/2 ft. high cedar stump, evidence of blaze visible bears S.9 3/4°W., 150.9 ft. (Rec. S.10 1/2°W., 150.9 ft.)
From Ren. No. 130
Set -Set - Reset 1962 DCSO BC/IP at a point determined from intersecting distances from bearing trees (See Accessories Fd.) The marks "RESET 1990" are added to brass cap BC/IP now protrudes 6" above ground, and is surrounded by a 2 ft. dia. mound of stone.
New BTs - 15" dia. Jeff. Pine double blazed and scribed "1/4 S19 CS BT" bears N.17 1/4°E., 108.6 ft.
16" dia. Ponderosa Pine double blazed and scribed "1/4 S19 CS BT" bears N.57 1/2°W., 65.8 ft.
Corner lies on top of a North-South ridge, approx. 20 ft. West of a dirt road. A metal wit. post and sign is set 2 ft. East of corner.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Jan. 17, 1990
C. S. 64/5

1/17/90

226

Section Corner for Secs. 10, 11, 14 and 15
Found - A 1961 2 1/2" dia. DCSO brass cap on a 1 1/4" O.D. iron pipe protruding 12" above ground. Ren. #113
1" I.D. iron pipe is found along north side of BC/IP. 1" IP protrudes 20" above ground and is bent to the southeast. Ren.#8
No original BTs found.
15" now 18" dia. 2 ft. high rotted and burnt D. fir stump no blaze or scribing visible, bears N.14°W., 21.4 ft. (Rec. N.14W, 20.5 ft. possible face measurement) Ren. No. 28
8" Fir now depression in ground bears S.61 1/2°E., 13.2 ft. (agrees with record) Ren. No. 28
20" now rotted and burnt D. fir stump of indeterminate size, bears N.11°W., 108.8 ft. (agrees w/rec.) Ren. No. 113
Northeast BT from Ren. No. 113 is gone.
11" now 9" dia. 25 ft. tall D. fir snag with a unhealed single blaze with scribing visible "T29S R5W S10 CS BT" bears N.10°W., 130.5 ft. (agrees with record) Ren. No. 165
New BTs - 5" dia. madrone bark scribed T29S R5W S15 CS BT" bears S.22 1/2°W., 5.6 ft.
6" madrone bark scribed 'T29S R5W S15 CS BT" bears S.83 1/2°W., 17.0'
4" dia. madrone bark scribed "T29S R5W S14 CS BT" bears S.64°E., 13.5 ft.
4" dia. D. fir double blazed and scribed "X BT" bears N.9°E., 41.6 ft.
Corner lies approx 2 ft. west of a northerly-southerly fence line.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
June 6, 1990
C.S. 64/9

6/6/90

227

Closing Corner for Section 36 & Sections 1 & 2 T.30 R.5
Found - 3 1/4" dia. B.L.M. brass cap on 2 1/2" O.D. iron pipe, protruding 7" above ground. BC/IP leans approx 3" Northeast of plumb. Cap stamped 1969.
15" now 20" d. fir with a fully healed single blaze, bears S.32 1/4°E., 54.8 ft.(agrees with record)
12" now 18" d. fir with a fully healed single blaze bears S.7 1/4°W., 85.8 ft. (agrees with record)
New BTs- 4" dia. d. fir double blazed and scribed "X BT" bears S.2°E. 26.2 ft.
11" dia. d. fir double blazed and scribed "T30S R5W S1 CC CS BT" bears S.70°E., 71.7 ft.
Note - Corner is along the north edge of a dirt road.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Terrie Franssen
March 15, 1991
C.S. 64/13

3/91