

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 6 R. W. W. M.

SET by State  
Baker, State  
High Way Eng  
Wit.  
J. M. Ledgerwood  
Wood.  
Apr. 12, 1942

SECTION CORNER COMMON TO SECTIONS 25-26-35 & 36. 1  
SET a 4 inch square stake for corner, scribed C. S.  
From which; **RE-RENEWED SEE CORNER NO. 20 & 184**  
A Fir Bears S. 1° 40' W. 333.3 feet distance.  
Scribed S. 35, B. T. **SEE ALSO # 20**

N.W. CORNER OF WM. DOOLEY D.L.C. NO. 43. 2  
Renewed by original B.T. decayed, marking plain. Set  
an Oak Post 4" x 4" x 3½" marked C. 43 T. 29 S., R. 6 W. C.S.  
A Fir 16" dia. marked C.S. C.43 T.29S., R.6W., bears  
N.71°W., 36 lks.  
A Fir 12" dia. marked C.S. C.43 T.29S., R.6W., bears  
S.58½°W., 8 lks.

EXTERIOR N.W. CORNER #43 3  
No evidence of original B.T. at proper distance. Set  
Fir post 4"x 4"x 3½' marked C.S. C.43 T.29S., R.6W. from  
which  
A Fir 36" dia. marked C.S. C.43 T.29S., R.6W., bears  
N.67°40'E., 86 lks.  
A Fir 32" dia. marked C.S. C.43 T.29S., R.6W., bears **J.M.P.**  
N.51°30'W., 26 lks. **11/10/70 - NOT FOUND - SEE C.S. 49/139**

S.W. CORNER #43 4  
Renew by original B.T.'s decayed marks plain. Set Fir  
Post 4" x 4" x 3½' marked C.S. C.43 T.29S., R.6W., from  
which **RE-RENEWED SEE CORNER NO. # 212**  
A Fir 50" dia. marked C.S. C.43 T.29S., R.6W., bears  
S.23½°E., 55 lks.  
A Fir 20" dia. marked C.S. C.43 T.29S., R.6W., bears  
N.23°W., 79 lks.  
A Fir 9" dia. marked C.S. C.43 T.29S., R.6W., bears  
S.52½°W., 20 lks.

S.E. CORNER #43 5  
Renew by original B.T., decayed and fallen down but  
marks plain. Set an Oak post marked C.S. C.43 T.29S., R.6W.  
from which  
A Fir 14" marked C.S. C.43 T.29S., R.6W. bears  
N.56½°E., 15 lks. **RE-RENEWED SEE CORNER NO. # 211**  
A Fir 17" marked C.S. C.43 T.29S., R.6W., bears  
N.35½°W., 50 lks.  
Above corner established in presence of  
E. L. Rice, S. B. Swickard and S. C. Meriaith  
Field Book No. 19 page 35.

A. D. WILLIS D.L.C. NO. 45 6  
Interior "L" corner Post (Fir) marked C.S. C.45 T.29S.,  
R.6W., from which **4/19/71 - Not Found - See C.S. 49/139**  
A Fir 12" marked C.S. C.45 T.29S., R.6W., bears  
S.15°W., 49 lks.  
A Fir 30" marked C.S. C.45 T.29S., R.6W., bears  
N. 6°W., 24 lks.  
Note: This corner found as described January 24, 1929.  
Drove car axle for corner and remarked B.T.s on Bark.  
Stake at new corner axle in mound of stone 2½ dia. x 1' high.  
Ben B. Irving  
Dep. Co. Sur.

S.E. CORNER D.L.C. #45 7  
Fir Post 4 x 4 x 3½ marked C.45 T.29S., R.6W. from which  
A Maple 14" dia. marked C.S. C.45 T.29S., R.6W., bears  
S.20°W., 8 lks.  
A Maple 16" dia. marked C.S. C.45 T.29S., R.6W., bears  
N.72°W., 72 lks. **RE-RENEWED SEE CORNER NO. # 215**

Corners renewed by  
Frank Cain  
April 28-29, 1916.

Corner renewed by  
Frank Cain  
February 19, 1915.  
Vol. R. P. 267