

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

6

R. W. W. M.

Corner Renewed by
Frank Cain
February 19, 1915.
1/2 p. 207

✓ S.W. CORNER OF CLAIM NO. 45. 8
Post 4" x 4" x 3 1/2' marked C.45 T.29S., R.6W from which
A Fir 48" dia. marked C.45 X bears S.70°W., 11 lks.
Corner established in presence of O.L. Willis, Frank Royer
and Ceive Willis. 216
Note: Corners renewed by original B.T.s where found and
in other case at proper distances. See records of surveys
Vol. 2 p. 201.

✓ CORNER SECTION BETWEEN 11, 12, 13 and 14. 9
I renew as per old B.T.s by setting a 3/4" x 36" Iron Bar
from which 200
A 8" White Oak bears N.48 1/2°W., 1.205 chs. C.S.B.T.
A 30" White Oak bears N. 8°W., 7.50 chs. Old B.T.
A 30" White Oak bears S.73 1/2°W., 0.39 chs. Old B.T.
A 40" White Oak bears S.52 1/2°E., 4.00 chs. Old B.T.

✓ 1/4 CORNER BETWEEN SECTIONS 13 and 14. 10/180
Set a 3/4" x 36" Iron Rod from which
A 28" Black Oak bears N.83°W., 6 1/2 lks. C.S.B.T.
A 20" White Oak bears S.78°E., 64 1/2 lks. C.S.B.T.

SECTION CORNER BETWEEN 13, 14, 23 and 24. 11
Renewed from old B.T.s. I set a 1 1/2" x 50" Iron Wire 129
for corner from which
A 6" White Oak bears S.84 3/4°E., 11 lks. C.S.B.T.
A 4" White Oak bears N.52 1/4°E., 8 lks. C.S.B.T.
A 8" White Oak bears N.42°W., 21 lks. C.S.B.T.
A 6" Fir bears S.58 1/2°W., 14 lks. C.S.B.T.

✓ SECTION CORNER BETWEEN SECTIONS 14 and 23. 12
Renewed from old B.T. by setting a 3/4" x 1 1/2" x 36" Iron
Bar from which 179
A 8" White Oak bears N.50 3/4°E., 2.60 chs. C.S.B.T.
A 24" Cedar bears S.19 1/4°E., 1.82 chs. C.S.B.T.

✓ SECTION CORNER BETWEEN 14, 15, 22, and 23. 13
I re-establish from old B.T. namely a 30" White Oak 97
N.24°E., 5.00 ch. which I remark and set a 1" x 30"
Iron Pipe and 3" x 36" Oak Stake from which
A 18" Fir bears N.16°W., 22 1/2 lks. C.S.B.T.
A 12" Fir bears N.83 1/2°W., 42 1/2 lks. C.S.B.T.
A 24" Fir bears S.29 1/2°E., 32 lks. C.S.B.T.
A 14" Fir bears N.44 1/2°E., 40 lks. C.S.B.T.

✓ SECTION CORNER BETWEEN SECTION 14 and 15. 14
Renewed from old B.T.s which I remarked and set a
3/4" x 36" Gal. Iron Pipe for corner from which 182
A 8" Fir bears S.69°E., 10 lks. C.S.B.T.
A 5" White Oak bears S.57 1/2°W., 7 lks. C.S.B.T.

✓ SECTION CORNER BETWEEN 10, 11, 14 and 15. 15
Renewed from old B.T.s by setting a 5" x 5" x 40" Oak 172
Stake from which
A 10" Laurel bears N.44°E., 13 1/2 lks. C.S.B.T.
A 20" Fir bears S.62 1/4°E., 18 lks. C.S.B.T.
A 20" Fir bears S.75°W., 39 lks. C.S.B.T.
A 12" Fir bears N.63 1/4°W., 30 lks. C.S.B.T.

✓ SECTION CORNER BETWEEN SECTIONS 11 and 14. 16
Renewed from old B.T.s by setting a 1" x 36" Gal. Iron
Pipe from which 213
A 8" White Oak S.23°E., 19 1/2 lks. C.S.B.T.
A 8" White Oak N.35 1/2°W., 41 lks. C.S.B.T.

✓ S.E. CORNER OF J.S. BURNETT D.D.C. NO. 42 17
I reset from 30" White Oak N.41°W., 150 lks. Remarkd
and set a 3/4" x 36" Iron Rod for corner from which
A 4" White Oak bears S.57°E., 52 lks. C.S.B.T.

F. C. Frear Dep. Co. Sur.
Witnesses
Fred Smith
Ora Rank
Lou Sarrisson
May 1919.